

Rpt. 13.

No. 48481

REPORT ON ELECTRIC FITTINGS.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

17 OCT 1928

Date of writing Report **3.10 1928** When handed in at Local Office **23.10 1928** Port of **GLASGOW.**
 No. in Survey held at **GREENOCK** Date, First Survey **6.9.28.** Last Survey **8.10. 1928**
 Reg. Book. **91867** on the **S.S. "ROSSINGTON COURT"** (Number of Visits... 5)
 Tons Gross **5285.**
 Net **1928**
 Built at **GOVAN** By whom built **THE FAIRFIELD S & E. CO LTD** Yard No. **631** When built **1928**
 Owners **UNITED BRITISH S.S. CO LTD** Port belonging to
 Electric Light Installation fitted by **THE FAIRFIELD S & E. CO LTD** Contract No. **631** When fitted **1928**

System of Distribution **2 WIRE**
 Pressure of supply for Lighting **110** volts, Heating **NONE** volts, Power **110** volts.

Direct or Alternating Current, Lighting **DIRECT** Power **DIRECT**

If alternating current system, state frequency of periods per second

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off **YES**

Generators, do they comply with the requirements regarding rating **YES**, are they compound wound **YES**

are they over compounded 5 per cent. **YES**, if not compound wound state distance between each generator

Where more than one generator is fitted are they arranged to run in parallel **ONE GENERATOR ONLY**, is an adjustable regulating resistance fitted in series with each shunt field **YES**

Are all terminals accessible, clearly marked, and furnished with sockets **YES**, are they so spaced or shielded that they cannot be accidentally earthed, short circuited, or touched **YES**

Position of Generator **ENGINE ROOM.** Are the lubricating arrangements of the generators as per Rule **YES**

is the ventilation in way of the generators satisfactory **YES**, are they clear of all inflammable material **YES**

if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the generators **NONE** and **NONE**, are the generators protected from mechanical injury and damage from water, steam or oil **YES**

are their axes of rotation fore and aft **YES**

Earthing, are the bedplates and frames of the generating plant efficiently earthed **YES** are the prime movers and their respective generators in metallic contact **YES**

Main Switch Boards, where placed **ENGINE ROOM.**

If the generators and main switchboard are not placed in the same compartment, is each generator provided with a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard **IN SAME COMPARTMENT**

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes **YES**

are they protected from mechanical injury and damage from water, steam or oil **YES**, if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the switchboards **NONE** and **NONE**

are they constructed wholly of durable, non-ignitable non-absorbent materials **YES**, is all insulation of high dielectric strength and of permanently high insulation resistance **YES**

if semi-insulating material is used, are all conducting parts insulated from the slab with mica or micanite or other non-hygroscopic insulating material, and the slab similarly insulated from its framework **YES**

and is the frame effectively earthed **YES**. Are the fittings as per Rule regarding:— spacing or shielding of live parts

YES, accessibility of all parts **YES**, absence of fuses on back of board **YES**, proportion of omnibus bars **YES**

individual fuses to voltmeter, pilot or earth lamp **YES**, connections of switches **YES**

Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches **THE GENERATOR HAS ONE MAIN 150 AMP. D.P. SWITCH & D.P. FUSES. OUTGOING CIRCUIT FOR SEARCHLIGHT HAS A 75 AMP. D.P. SWITCH & D.P. FUSES AND THE OTHER 4 OUTGOING CIRCUITS HAVE EACH A 30 AMP. S.P. SWITCH & D.P. FUSES.**

Instruments on main switchboard **1** ammeters, **1** voltmeter, synchronising device for paralleling purposes.

Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system **EARTH LAMPS WITH SWITCHES & FUSES ON EACH POLE**

Switches, Circuit Breakers and Fusible Cut-outs, do these comply with the requirements of the Rules **YES**

Joint Boxes Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per rule **YES**



W450-0188 1/2

Cables: Single, twin, concentric, or multicore SINGLE are the cables insulated and protected as per Tables IV or V of the Rules. YES

Fall of Pressure, state maximum between bus bars and any point of the installation under maximum load. 4.98 VOLTS

Cable Sockets and other connections, are the ends of all cables having a sectional area of 0.04 square inch and above provided with soldering sockets. YES

Paper Insulated Cables. If cables are paper covered, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound. NONE

Cable Runs, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage. YES

Support and Protection of Cables, state how the cables are supported and protected. L.C. ARMoured & BRAIDED CABLES FIXED ON SHEET IRON PLATES WITH GALV. IRON CLIPS, L.C. CABLES FIXED WITH BRASS CLIPS, V.I.R. CABLES RUN IN TUBING.

If cables are run in wood casings, are the casings and caps secured by screws. NONE, are the cap screws of brass. —, are the cables run in separate grooves. —. If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VIII. YES

Refrigerated Chambers, if lights are fitted, are the cables and fittings in accordance with the special requirements. NONE

Joints in Cables, state if any, and how made, insulated, and protected. NONE

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands. YES

Bushes in Beams and Non-watertight Partitions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed. YES, state the material of which the bushes are made. SHEET LEAD

Earthing Connections, state what earthing connections are fitted and their respective sectional areas. NONE

—, are their connections made as per Rule. —

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule. YES

Emergency Supply, state position and method of control of the emergency supply and how the generator is driven. NONE

Navigation Lamps, are these separately wired. YES, controlled by separate switch and separate fuses. YES, are the fuses double pole. YES, are the switches and fuses grouped in a position accessible only to the officers on watch. YES

has each navigation lamp an automatic indicator as per Rule. YES

Secondary Batteries, are they constructed and fitted as per Rule. NONE

Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight. YES

are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected. NONE

are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected. NONE

—, how are the cables led. —

where are the controlling switches situated. —

Searchlight Lamps, No. of 1-20", whether fixed or portable. FIXED, are their fittings as per Rule. YES

Arc Lamps, other than searchlight lamps, No. of NONE, are their live parts insulated from the frame or case. —, are their fittings as per Rule. —

Motors, are their working parts readily accessible. YES, are the coils self-contained and readily removable for replacement. YES

are the brushes, brush holders, terminals and lubricating arrangements as per Rule. YES, are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material. YES

are they protected from mechanical injury and damage from water, steam or oil. YES, are their axes of rotation fore and aft. YES

if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type. YES, if not of this type, state distance of the combustible material horizontally or vertically above the motors. — and —

Control Gear and Resistances, are the generator field and motor speed regulators, starters and controllers constructed and fitted as per Rule. YES

Lightning Conductors, where lightning conductors are required, are these fitted as per Rule. NONE

Ships carrying Oil having a Flash Point less than 150° F. Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings. —

If portable lamps for use in dangerous spaces are supplied, are they of a type approved by the Home Office. —

PARTICULARS OF GENERATING PLANT.

DESCRIPTION OF GENERATOR.	No. of	RATED AT			Revs. per Min.	DRIVEN BY	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.	
		Kilowatts.	Volts.	Amperes.			Fuel Used.	Flash Point of Fuel.
MAIN	1	15	110	136	340	ROBEY SINGLE CYLINDER OPEN TYPE STEAM ENGINE		
AUXILIARY								
EMERGENCY								
ROTARY TRANSFORMER								

LIGHTING AND HEATING CONDUCTORS.

Ref. No.	DESCRIPTION.	No. of Conductors.	Effective Area of each Conductor. Sq. Ins.	COMPOSITION OF STRAND.		Total Maximum Current. Amperes.	Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
				No.	Diameter.				
	MAIN GENERATOR	2	.14780	37	.072	136	30	PURE RUBBER	L.C. ARM ^{ED} & BRAIDED
	EQUALISER CONNECTIONS								
	AUXILIARY GENERATOR								
	EMERGENCY GENERATOR								
	ROTARY TRANSFORMER								
	AUXILIARY SWITCHBOARDS								
	ENGINE ROOM	2	.01462	7	.052	8.18	12	" "	" "
	BOILER ROOM								
	ACCOMMODATION								
	CAPTAIN'S ACCOM. CHART R.M., WIT, DINING SALOON, PURSER, STEWARD, COMPASS & TELEGRAPHS, CREWS' ACCOM. FORMS, CARGO CLUSTERS, & NAVIGATION LIGHTS	2	.03960	19	.052	41.4	260	" "	V.I.R.
	OFFICERS' ACCOM. CREWS' ACCOM. AFT. & CARGO CLUSTERS	2	.01046	7	.044	20.54	100	" "	" "
	WIRELESS	2	.01046	7	.044	13.6	285	" "	" "
	SEARCHLIGHT 20"	2	.03960	19	.052	60	580	" "	" "
	MASTHEAD LIGHT								
	SIDE LIGHTS								
	COMPASS LIGHTS								
	POOP LIGHTS								
	CARGO LIGHTS								
	ARC LAMPS								
	HEATERS								

MOTOR CONDUCTORS.

Ref. No.	DESCRIPTION.	No. of Motors.	Effective Area of each Conductor. Sq. Ins.	COMPOSITION OF STRAND.		Total Maximum Current. Amperes.	Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
				No.	Diameter.				
	BALLAST PUMP								
	MAIN BILGE LINE PUMPS								
	GENERAL SERVICE PUMP								
	EMERGENCY BILGE PUMP								
	SANITARY PUMP								
	CIRC. SEA WATER PUMPS								
	CIRC. FRESH WATER PUMPS								
	AIR COMPRESSOR								
	FRESH WATER PUMP								
	ENGINE TURNING GEAR								
	ENGINE REVERSING GEAR								
	LUBRICATING OIL PUMPS								
	OIL FUEL TRANSFER PUMP								
	WINDLASS								
	WINCHES, FORWARD								
	WINCHES, AFT								
	STEERING GEAR								
	(a) MOTOR GENERATOR								
	(b) MAIN MOTOR								
	WORKSHOP MOTOR								
	VENTILATING FANS								

W450-0188 2/2

All Conductors are of annealed copper conforming to British Standard Specification No. 7.
 The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.
 The foregoing is a correct description.

Elkiner Electrical Engineers. Date 8th October 1928

COMPASSES.

Distance between electric generators or motors and standard compass 116 FEET
 Distance between electric generators or motors and steering compass 110 "
 The nearest cables to the compasses are as follows :—
 A cable carrying .254 Ampères IN feet from standard compass feet from steering compass.
 A cable carrying .254 Ampères IN feet from steering compass.
 A cable carrying " Ampères " feet from standard compass " feet from steering compass.
 Have the compasses been adjusted with and without the electric installation at work at full power YES
 Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted YES
 The maximum deviation due to electric currents was found to be NIL degrees on ANY course in the case of the standard compass, and NIL degrees on ANY course in the case of the steering compass.

FOR THE FAIRFIELD S.B. & E. CO., LIMITED. Builder's Signature. Date

Is this installation a duplicate of a previous case No. If so, state name of vessel

General Remarks (State quality of workmanship, opinions as to class, &c.) This installation has been fitted on board under special survey. Tested under full working conditions and found satisfactory. The materials and workmanship were found to be good and sound.

A.G.
13/10/28

It is submitted that this vessel is eligible for THE RECORD. Elec. Light.
 26/10/28

Total Capacity of Generators 16 Kilowatts.

The amount of Fee ... £ 15.0.0 : When applied for, 9 OCT 1928
 Travelling Expenses (if any) £ 10.6 : When received, 14.11.28

J. Rankin
 Surveyor to Lloyd's Register of Shipping.

Committee's Minute GLASGOW 16 OCT 1928
 Assigned Elec. Light

1m.127.—Transfer.
 (The Surveyors are requested not to write on or below the space for Committee's Minute.)