

FRAMING, depth of girders
FLOORS, depth and thickness of Floor Plate
at mid-line for $\frac{1}{2}$ length amidships...
Bulb Spacing

Angles or Bulb Angles
Plate above floors, for
in E.S. length
Rider plate P.S. E.S.
36
3 3

2,500, 11, 31.

1

"Arela"

Sent to Chief Surveyors

Received from Chief Surveyors

VESSEL'S NAME *Stul 55 MAYFIELD*

Report

gls

No. *41876*


For the CHIEF SHIP SURVEYOR and CHIEF ENGINEER SURVEYOR.

(In cases which have to be submitted to the Classing Committee "the endorsement to contain a succinct summary of any repairs that have been required and to show the cause or causes of such repairs, and also to bring out clearly any exceptional features in connection with the case so that the Classing Committee may have all the salient points presented in the endorsement."—Extract from Sub-Committee's Report 24/5/92.)

Nature of Survey

When due

* 100-A-1. (Stul)
12% (pt Stul) Well Deck.
All DB/ 103' 153t, FPT 39t, APT 3t,
8% 7/4, 384, Cenn, Plytho A.C.P. Q 46' B11' F31'



Wichy Off 2020

M

J

It is Concluded that the Waterballast tanks have been tested as required
but the Surveyors should be requested to state if this is so

W 472-0109

BEAMS, Second Deck, Single Angle, Bulb
Angle, Plate, Tee Bulb, or Channel
Spacing
BEAMS, Third and Fourth Deck, Single Angle

Deck, Material & thickness
Deck Stringer Plate, breadth & thickness

34x38 - 16x
3 2