

EXT 27-10-32

Lloyd's Register of British & Foreign Shipping.

SURVEYS FOR FREEBOARD.-STEAM SHIPS.

WED. JUN. 30. 1915

No. 35259

24322

PARTICULARS RELATING TO ALL STEAM SHIPS EITHER FLUSH DECKED, OR WITH TOP GALLANT FORECASTLES, SHORT POOPS AND BRIDGE HOUSES DISCONNECTED, OR WITH TOP GALLANT FORECASTLES HAVING LONG POOPS, OR RAISED QUARTER DECKS CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE.

Port of Survey Glasgow
Date of Survey Building
Name of Surveyor Henry C. Tarnat

Address 20, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100, 105, 110, 115, 120, 125, 130, 135, 140, 145, 150, 155, 160, 165, 170, 175, 180, 185, 190, 195, 200, 205, 210, 215, 220, 225, 230, 235, 240, 245, 250, 255, 260, 265, 270, 275, 280, 285, 290, 295, 300, 305, 310, 315, 320, 325, 330, 335, 340, 345, 350, 355, 360, 365, 370, 375, 380, 385, 390, 395, 400, 405, 410, 415, 420, 425, 430, 435, 440, 445, 450, 455, 460, 465, 470, 475, 480, 485, 490, 495, 500, 505, 510, 515, 520, 525, 530, 535, 540, 545, 550, 555, 560, 565, 570, 575, 580, 585, 590, 595, 600, 605, 610, 615, 620, 625, 630, 635, 640, 645, 650, 655, 660, 665, 670, 675, 680, 685, 690, 695, 700, 705, 710, 715, 720, 725, 730, 735, 740, 745, 750, 755, 760, 765, 770, 775, 780, 785, 790, 795, 800, 805, 810, 815, 820, 825, 830, 835, 840, 845, 850, 855, 860, 865, 870, 875, 880, 885, 890, 895, 900, 905, 910, 915, 920, 925, 930, 935, 940, 945, 950, 955, 960, 965, 970, 975, 980, 985, 990, 995, 1000
Ship's Name Whealsheaf
Port of Registry and Nationality British
Official Number 136981
Gross Tonnage 500
Date of Build 1915
Particulars of Classification +100 A.I. Contemplated

Registered dimensions from Ship's Register.	LENGTH. <u>162-8</u>	BREADTH. <u>25-6</u>	DEPTH. <u>9-8</u> <i>ordinary floor 11-4 1/2</i>	UNDER DECK TONNAGE. <u>330-78</u>
Length on LOADLINE.	<u>162-0</u>	Frame Depth Rule <u>5-3</u>	Ceiling fitted <u>3</u>	Peak Tanks <u>2</u>
CORRECTED DIMENSIONS.	<u>162-0</u>	<u>25-27</u>	<u>10-79</u>	<u>323-78</u>

Moulded Depth as measured..... 12-0

NOTE - If the depth is measured when vessel is afloat, the details of measurement should be reported.

Co-efficient of fineness..... .73
Any modification necessary [Para. 4 (a) to (e)]* Cell D.B
Co-efficient as corrected..... .71

CORRECTION FOR LENGTH.

Length of Ship on Loadline.....	<u>162</u>
Length in Table.....	<u>144</u>
Difference.....	<u>18</u>
Correction for 10ft., Table A.....	<u>.9</u>
x Difference divided by 10.....	<u>1.62</u>
If 1/10th length covered divide by 2.....	<u>.81</u>

Table C. (if required.) + 3/4

Sheer {Stem..... 72 } 117 + 2 = 58-5 Mean
at {Sternpost... 45 }
Sheer at 1/2 of the length from {Stem 39-6 } 64-3 ÷ 2 = 32-1 1/2 Mean
{Sternpost 24-7 } 58-4 ÷ 2 = 29-2
Gradual mean Sheer..... 58-4
Standard mean Sheer [Table, Para. 18]..... 26-20 Correction
Difference..... 32-25 ÷ 4 = 8-06
§ If limited as Para. 18 (f)..... - 8"

CORRECTION FOR IRON DECK.
Proportion covered, if less than 1/7th length covered.....
Thickness of usual wood deck, less stringer..... 3"

Rise in Sheer from amidships [Para. 18 (e)]
At front of bridge house.....
At after end of forecastle.....
Fall in Sheer [Para. 18 (d)] + 2 =
Length uncovered.....
Correction

CORRECTION FOR ROUND OF BEAM.

Breadth at Gunwale amidships.....	<u>25-6</u>
Round of Beam.....	<u>6 1/2</u>
Normal round.....	<u>6 3/4</u>
Difference.....	<u>+ 2 =</u>

Proportion of Deck uncovered (Para. 19).....

NOTE - The round of beam should be reported on the full breadth of vessel at the gunwale.

ALLOWANCE FOR DECK ERECTIONS :-
Freeboard, Table C..... 3 1/4
Correction for Length, if required (Para. 12, 13, and 14).....
Freeboard by Table A, corrected for sheer, and for length, if required (Para. 12, 13, and 14)..... 1-0 3/4
Difference..... 9 1/2
Percentage as below..... 70-0
Correction for R. Q. Dk. if engine and boiler openings not covered by bridge house (Para. 11)..... 6-65
Allowance for Deck Erections..... + 20
= 6 1/2

Freeboard, Table A.....	<u>1-8 3/4</u>
Correction for Sheer.....	<u>- 8</u>
Correction for Length.....	<u>+ 3/4</u>
Allowance for Deck Erections.....	<u>1-1 1/2</u>
Correction for Round of Beam.....	<u>- 6 1/2</u>
Correction for fall in Sheer (if any).....	<u>3</u>
Correction for Iron Deck (if required).....	<u>4</u>
Other Corrections (if any) <u>Height of R.Q. Dk.</u>	<u>4-0</u>
Winter Freeboard.....	<u>4-4</u>
Summer Freeboard.....	<u>4-2 1/4</u>
Indian Summer Freeboard.....	<u>4-0 1/2</u>
N. A. Winter Freeboard.....	<u>4-0 1/2</u>
Correction necessary because clearside amidships, measured in accordance with the Statute is not taken at the intersection of the wood or iron deck with side.....	<u>1"</u>

Forecastle.....	Length. <u>24-0</u>	Length allowed. <u>22-08</u>	Height. <u>7-0</u>
Bridge House.....	<u>10-75 Side</u>	<u>11-94</u>	<u>7-0</u>
† Raised Qr. Dk.....	<u>12-54 Centre</u>	<u>95-50</u>	<u>4-0</u>
Poop.....	<u>95-50</u>	<u>95-50</u>	<u>4-0</u>
Total.....	<u>129-52</u>	<u>162-0</u>	<u>= .80</u>

Length of Ship..... 162-0
Corresponding percentage (Para. 11, 12, 13, or 14)..... 70%

WINTER FREEBOARD recommended amidships from centre of Disc to top of Statutory Deck Line, Wood (Iron) Deck :-

Fresh Water Line above centre of Disc.....	<u>4-3</u>
Indian Summer Line " " ".....	<u>2 1/2</u>
Winter Line below " " ".....	<u>2</u>
Winter North Atlantic Line " " ".....	<u>2 1/2</u>

Winter Freeboard from deck line..... 4-5
Summer " " "..... 4-3 1/4
Indian Summer " " "..... 4-3 1/4
N. A. Winter " " "..... 4-3 1/4

† In vessels obtaining an allowance for deck erections under Para. 11 where the sheer drops abaft amidships the height of the R.Q.D. is to be taken from the level of the top of the amidship beam.
‡ In flush-decked vessels the total standard mean sheer means the sheer measured at the stem and sternpost. In vessels having poops and forecastles, it means the sheer measured at points distant one eighth of the vessel's length from stem and sternpost.

† State dimensions of freeing port area on back of this form.
The Surveyor should state whether the fall in sheer as reported is measured relatively to the straight line of keel or to the water line. If measured relatively to water line the vessel's draft at time of survey, and also the usual load draft forward and aft should be reported.

ms BRS 36/6/15
w481-0171

© 2020

Lloyd's Register Foundation

Do all the Frames extend to the top height in the Poop? Raised Quarter Deck? *yes* Bridge House? *yes* Forecastle? *yes*
 To what height do the Reverse Frames extend? *None*
 Has the Poop or Raised Quarter Deck an efficient Iron Bulkhead at the fore end? *yes*
 Give particulars of the means for closing the openings in Bulkhead *No openings*
 Is the Poop or Raised Quarter Deck connected with the Bridge House? *yes* Has the Bridge House an efficient Bulkhead at the fore end? *yes*
 Give particulars of the means for closing the openings in Bulkhead *No openings*
 What is the thickness of the Bridge Front plating? *.26* and Coaming plate? *.26*
 Give scantlings and spacing of the Stiffeners *B.A. 5x3x40, spaced 29 apart*
 Are bracket plates fitted at each end of the Stiffeners? *yes* Are hor'l. brackets fitted connecting Bridge Bulk'd. with Bulwarks? *yes*
 Has the Bridge House an efficient Iron Bulkhead at the after end? *yes*
 How are the openings closed? *No openings*
 Is the Forecastle at least as high as the main or top-gallant rail? *yes* Has the Forecastle an efficient Iron or Wood Bulk'd. at after end? *Steel*
 Are the Engine and Boiler openings covered by a Bridge, Poop, Raised Quarter Deck, or enclosed by a Strong Iron or Steel Deckhouse? *Raised Quarter D.K. & Strong steel deck house*
 If the openings are not so protected are the exposed parts of the Casings efficiently constructed?
 Give thickness of plating; scantlings and spacing of Stiffeners
 What is the height of the exposed Casings? *7.0* Are suitable means provided for closing all openings in them in bad weather? *yes*
 Are the Weather Deck Hatchways efficiently constructed and at least equal to the requirements of Section 28 of the Rules for 1904-5? Give particulars below: *yes*


Position and Size.	No. 1 - 23 3/2 x 15.0		No. 2 - 26.10 1/2 x 15.0		Ship.	Rule.	Ship.	Rule.	Ship.	Rule.
	Item.	Ship.	Rule.	Ship.						
COAMING.	Height above top of DECK	3.8 1/2		2.11 1/2						
	Thickness {	Sides.....	.46		.46					
		Ends.....	.40		.40					
SHIFTING BEAMS OR WEB PLATES.	Number	4		5						
	Section and Scantlings	40	<input checked="" type="checkbox"/>	40	<input checked="" type="checkbox"/>					
	Material	steel		steel						
* FORE AND AFTERS.	Number	None		None						
	Section and Scantlings									
	Material									
HATCHES Thickness		3"	<input checked="" type="checkbox"/>	3"	<input checked="" type="checkbox"/>					
Remarks.....										

* When the Fore and Afters are of wood the depth should be stated from the underside of the hatches.
 (If the sill of the lowest side scuttle will be less than 6 inches above the Indian Summer Load Line if assigned under the tables, state vertical distance from top of deck at side amidships to lower edge of lowest side scuttle.)

The following information is to be given in all Cases of vessels dealt with under Paras. 11, 12 (under 15 feet moulded depth) and under Shelter Deck Rules.
 What is the thickness of the Bridge Sheerstrake? *.26* Strake between Main and Bridge Sheerstrakes? *.40*

Delete the words { The Crew ~~are~~ are not, berthed in the bridge house.
 that do not apply { The arrangements to enable them to get backwards and forwards from their quarters are, ~~are not~~ satisfactory.

Length of Bulwarks in well *30.5*
 Area of Freeing Ports required by Para. 11 (e) each side of vessel = *9.55* Sq. ft.
 Ft. Tenths. Ft. Tenths. No. } Freeing Ports = *10.5* Sq. ft.
 3.0 x 1.75 x 2 (each side of vessel)
 Total deficiency or excess = *1.0* Sq. ft. *0.95*



Show hereon line of Floors or Tank Top with position of any Breaks in same; also height of Peak Tank tops, &c., &c.

State any special features in the construction of the Vessel *The plans of midship section and amended profile are enclosed for reference*
The prebanded request form is attached.

Owners

Address

Fee £

Received by me



© 2020

Lloyd's Register Foundation