

11b.

33897

Lloyd's Register of Shipping.

~~COPYRIGHT SURVEYS FOR FREEBOARD.-STEAM SHIPS.~~

PARTICULARS RELATING TO ALL STEAM SHIPS EITHER FLUSH DECKED, OR WITH TOP GALLANT FORECASTLES, SHORT POOPS AND BRIDGE HOUSES DISCONNECTED, OR WITH TOP GALLANT FORECASTLES HAVING LONG POOPS, OR RAISED QUARTER DECKS CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE.

Port of Survey NEWCASTLE-ON-TYNE
Date of Survey 22nd Sep 1930
Name of Surveyor El Brown

Ship's Name. O. V. "CHEYENNE" Palmers Co's No. 1001 Number in Register Book 89938	Port of Registry and Nationality. NEWCASTLE	Official Number. 161559	Gross Tonnage. 8900 approx	Date of Build. 1930	Particulars of Classification. +100A1 carrying passengers (Contemplated) Longitudinal framing at bottom + decks.
Registered dimensions from Ship's Register.	Length. 477.0 Breadth. 63.8 Depth. 34.8 Under Deck Tonnage. 8083.99				
Length on LOADLINE.	Frame Depth 9" Ceiling +20 Rule " 7½ Sheer +1.27 $\times 2 = -25 \frac{1}{2}$ Nostirring +.33	Peak { incl'd Tanks	D.B.MER +57 depth floors } +24 ft.		
CORRECTED DIMENSIONS.	470.0 63.88 36.27	8158.99			

nt of fineness.....	749.
ication necessary	LONGITUDINAL BOTTOM FRAMING
1 (a) to (e)]*	
as corrected	76
	102.73 57.00
em..... 132" { 202" - Mean	36 45.73
ernpost ... 70" } 101" Mean	127
of the length from Stem 74" { 113 ÷ 2 = 56½" Mean	
Sternpost 39" } ÷ 55 = 102.73	
mean Sheer allowed 101.86	
mean Sheer [Table, Para. 18] 57.00	Correction
Difference..... 44.86	÷ 4 = 11.21
ed as Para. 18 (f)	- 11/4

Sheer }	At front of bridge house.....
idships }	
3 (e)] At after end of forecastle	-

Sheer }	÷ 2 =
3 (d) }	
uncovered	Correction

ALLOWANCE FOR DECK ERECTIONS :—		
Table C.....	9'-4½" - 3-2" =	6'-2½"
for Length, if required (Para. 12, 13, and 14)		+ 4½
by Table A, corrected for sheer, and for length, if required (Para. 11, 12, 13, and 14)	6'-7"	
e	9'-2¾"	
as below	2'-7¾"	
	22.73%	
	722	

n for R. Q. Dk. if engine and boiler openings not covered by bridge house (Para. 11)

a for Deck Erections

Length.	Length allowed.	Height.
eno overhang 40.5	40.5	7.9"
ouse	27.0' ^{alast} 81.0 abcs.	27.0' 29.66
Qr. Dk.....	104.5	100.75
"	104.5	7.9"
otal	172.0	172.0
f Ship	470.0	170.91 = .3636
ading percentage (11, 12, 13, or 14)	2273	

OARD recommended amidships from centre of Disc to top of Statutory Deck Line, Wood (Steel) Deck :—

Fresh Water Line	above centre of Disc	...
Indian Summer Line	" "	...
Winter Line	below "	...
Winter North Atlantic Line	" "	...

If the frames, skin planking, or ceiling are of unusual thickness the breadth of vessel to inside of ceiling should be reported.

In vessels obtaining an allowance for deck erections under Para. 11 where the sheer drops about amidships the height of the R.Q.D. is to be taken from the level of the top of the amidships beam.

In flush-decked vessels the total standard mean sheer means the sheer measured at the stem and stern-post. In vessels having poops and forecastles, it means the sheer measured at points distant one-eighth of the vessel's length from stem and stern-post.

$$\frac{17868}{40 \times 59.8} = 7.46$$

* State dimensions of freeing port area on back of this form.

The Surveyor should state whether the fall in sheer as reported is measured relatively to the straight line of keel or to the water line. If measured relatively to water line the vessel's draft at time of survey, and also the usual load draft forward and aft should be reported.

DISPLAT AT 28' DRAFT 183.84 TONS
178.66 TONS
171.68 TONS

© 2020

Lloyd's Register Foundation

20 SEP 1930

2m 1.90 T.

WS10-0250

Do all the Frames extend to the top height in the Poop? Yes - Raised Quarter Deck? Bridge House? Yes - Forecastle? No. 11
 To what height do the Reverse Frames extend? Deep frames -
 Has the Poop or Raised Quarter Deck an efficient Iron Bulkhead at the fore end? Yes, plating 14" stiffeners 10x3½x40 BA, spaced 2' 3" to 2' 7" thick.
 Give particulars of the means for closing the openings in Bulkhead 2 tonnage openings closed by steel plate secured by hook bolts 12" spacing, not passing through.
 Is the Poop or Raised Quarter Deck connected with the Bridge House? No - Has the Bridge House an efficient Bulkhead at the fore end? Yes
 Give particulars of the means for closing the openings in Bulkhead 2 STEEL W.T. DOORS, HINGED, CAN BE CLOSED OR FASTENED FROM OUTSIDE 18" SILLS.
 What is the thickness of the Bridge Front plating? 14" and Coaming plate? 14" -
 Give scantlings and spacing of the Stiffeners 10" 3½" x 40" BA, spaced 2' 4" to 2' 7"
 Are bracket plates fitted at each end of the Stiffeners? Yes - Are hor'l. brackets fitted connecting Bridge Bulk'd. with Bulwarks? Yes
 Has the Bridge House an efficient Iron Bulkhead at the after end? Yes
 How are the openings closed? 2 tonnage openings, closed by steel plate, secured by hook bolts 12" spacing (see plan) not passing through.
 Is the Forecastle at least as high as the main or top-gallant rail? Yes - Has the Forecastle an efficient Iron or Wood Bulk'd. at after end? Steel
 Are the Engine and Boiler openings covered by a Bridge, Poop, Raised Quarter Deck, or enclosed by a Strong Iron or Steel Deckhouse? Covered by poop. - + 2 opening with hinged steel bolted plate
 If the openings are not so protected are the exposed parts of the Casings efficiently constructed?
 Give thickness of plating; scantlings and spacing of Stiffeners
 What is the height of the exposed Casings? Are suitable means provided for closing all openings in them in bad weather?
 Are the Weather Deck Hatchways efficiently constructed and at least equal to the requirements of the Rules? Give particulars below:-

Position.	TO NO1 GARDEN PORT ON UPPR DECK						
Size.	6'-9" x 10'-0"						
COAMING. Height above top of DECK	2'-6"						
Thickness { Sides.....	.44"						
Thickness { Ends.....	.44"						
STIFFENERS ON COVER SHELVING { Number	3-F.R.A 5x3x40 angle						
BEAMS OR WLD. PLATES. { Section and Scantlings	2 THWARTSHIP 5x3x40 angle						
Material							
* FORE AND AFTERS. { Number	v						
* FORE AND AFTERS. { Section and Scantlings							
HATCHES Thickness steel plate W.T.	3½"						
Remarks.....							

* The depth of Fore and Afters should be stated from the underside of the hatches in all cases.

(If the sill of the lowest side scuttle will be less than 6 inches above the Indian Summer Load Line if assigned under the tables, state vertical distance from top of keel to lower edge of lowest side scuttle.)

The following information is to be given in all Cases of vessels dealt with under Paras. 11, 12 (under 15 feet Moulded depth) and under Shelter Deck Rule.

What is the thickness of the Bridge Sheerstrake? Strake between Main and Bridge Sheerstrakes?

Delete the words { The Crew are, are not, berthed in the bridge house.
that do not apply { The arrangements to enable them to get backwards and forwards from their quarters are, are not satisfactory.

Bulwarks 3.5 ft. Area fore 463

Length of Bulwarks in well aft well 165.8', for well 132.2' Fwd aft


Area of Freeing Ports required by Para. 11 (e) each side of vessel = 26.44 33.16 Sq. ft.

Ft. Tenths.	Ft. Tenths.	No.	Freeing Ports (each side of vessel)	Sq. ft.
aff well 18 FREEING PORTS 5.0'	0 .67'	18		
" 5 "	2.5' x 0 .67'	5		
FOR well 14 "	5.0' x 0 .67'	14		
3 "	2.5' x 0 .67'	3		
			Total deficiency or excess	25.48 35.51 Sq. ft.

{ Class all for
only have bottom
level of to
shelv-

Static

A.P.



Show hereon line of Floors or Tank Top with position of any Breaks in same; also height of Peak Tank tops, &c., &c.

State any special features in the construction of the Vessel Visual longitudinally framed at bottom & decks.
3 tanks abreast, no trunks.

Builder's name and yard number Palmers SB & J.C. Ltd. N°1001

Names of sister vessels

Owners Anglo-American Oil Co. Ltd.

, Address

Estimated Fee £ 11 : 13 : 4

Received by me See J.G. Report.



© 2020

Lloyd's Register
Foundation