LENGTH on Deck as per Rule	Feet. 352	Inches. 6	BREADTH— Moulded	Feet. 50	Inches. 7½	DEPTH, ACTUAL—Top of Floors to top of Upper Dk. Beams Do. do. do. do. Second Dk. Beams	Feet. 24	Inches. 11½	No. of No. of

Moulded depth ft 3 44 ins 7 5 To Bridge Dk. Rou Dk.

ed by Chief Ship Surveyor 7/10/11. Received from Chief Ship Surveyor

EL'S NAME Stl. S.S. "Rothley" Rpt. Nwc. No. 61138

The remarks of the Chief Ship Surveyor are desired on this case for the consideration of the Classing Committee.

("The endorsement to contain a succinct summary of any repairs that have been required and to show the cause or causes of such repairs, and also to bring out clearly any exceptional features in connection with the case, so that the Classing Committee may have all the salient points presented in the endorsement."—*Extract from Sub-Committee's Report*, 24/5/92.)

e of Survey 1st Entry.

It is submitted that before this case receives the consideration of the Committee, this report should be returned to the Newcastle Surveyors, and they should be requested to state the height of the brackets above the tank margin at bilge; the thickness of J & K strakes in way of the bridge, the equipment letter, and the ~~dam~~ test of the stream and kedge anchors, as this information has been omitted from the report.

Sr. Nwc. 7/10/11

R.A. 7/10/11

© 2021 Lloyd's Register Foundation
WS2-0189

„ Spacing		25			25		„ Tie Plates	Carr plated
BEAMS, Forecastle Deck, ~~Angle~~, Bulb Angle.)	8	3	4½	8	3	4½	Deck, Material and thickness	Steel wood