

REPORT ON MACHINERY.

No. 18282
-5 NOV 1924

Date of writing Report 18 Aug 1924 When handed in at Local Office 18 Aug 1924 Port of Greenock.
No. in Survey held at Reg. Book. Port Glasgow Date, First Survey 24 July Last Survey 28 July 1924
on the single screw steamer "GOLDEN CAPE" (Number of Visits 2)
Master Built at Port Glasgow By whom built Wm Hamilton & Co. Ltd. Tons Gross Not
Engines made at Glasgow By whom made D. Rowan & Co. Ltd. When built 1924
Boilers made at By whom made when made 1924
Registered Horse Power Owners when made
Nom. Horse Power as per Section 28 Is Refrigerating Machinery fitted for cargo purposes Port belonging to Is Electric Light fitted

ENGINES, &c.—Description of Engines

Dia. of Cylinders Length of Stroke Revs. per minute No. of Cylinders No. of Cranks
Is the screw shaft fitted with a continuous liner the whole length of the stern tube Dia. of Screw shaft as per rule Material of screw shaft
in the propeller boss If the liner is in more than one length are the joints burned Is the after end of the liner made water tight
between the bearings in the stern tube, is the space charged with a plastic material insoluble in water and non-corrosive If the liner does not fit tightly at the part
liners are fitted, is the shaft lapped or protected between the liners Length of stern bush
Dia. of Tunnel shaft as per rule Dia. of Crank shaft journals as per rule Dia. of Crank pin Size of Crank webs Dia. of thrust shaft under
collars Dia. of screw Pitch of Screw No. of Blades State whether moveable Total surface
No. of Feed pumps Diameter of ditto Stroke Can one be overhauled while the other is at work
No. of Bilge pumps Diameter of ditto Stroke Can one be overhauled while the other is at work
No. of Donkey Engines Sizes of Pumps No. and size of Suctions connected to both Bilge and Donkey pumps
In Engine Room In Holds, &c.

No. of Bilge Injections sizes Connected to condenser, or to circulating pump Is a separate Donkey Suction fitted in Engine room & size
Are all the bilge suction pipes fitted with roses Are the roses in Engine room always accessible Are the sluices on Engine room bulkheads always accessible
Are all connections with the sea direct on the skin of the ship yes Are they Valves or Cocks Both
Are they fixed sufficiently high on the ship's side to be seen without lifting the stokehold plates Are the Discharge Pipes above or below the deep water line
Are they each fitted with a Discharge Valve always accessible on the plating of the vessel Are the Blow Off Cocks fitted with a spigot and brass covering plate yes.
What pipes are carried through the bunkers How are they protected
Are all Pipes, Cocks, Valves, and Pumps in connection with the machinery and all boiler mountings accessible at all times
Are the Bilge Suction Pipes, Cocks, and Valves arranged so as to prevent any communication between the sea and the bilges
Is the Screw Shaft Tunnel watertight Is it fitted with a watertight door worked from

BOILERS, &c.—(Letter for record) Manufacturers of Steel

Total Heating Surface of Boilers Is Forced Draft fitted No. and Description of Boilers
Working Pressure Tested by hydraulic pressure to Date of test No. of Certificate
Can each boiler be worked separately Area of fire grate in each boiler No. and Description of Safety Valves to
each boiler Area of each valve Pressure to which they are adjusted Are they fitted with easing gear
Smallest distance between boilers or uptakes and bunkers or woodwork Mean dia. of boilers Length Material of shell plates
Thickness Range of tensile strength Are the shell plates welded or flanged Descrip. of riveting: cir. seams
long. seams Diameter of rivet holes in long. seams Pitch of rivets Lap of plates or width of butt straps
Per centages of strength of longitudinal joint rivets plate Working pressure of shell by rules Size of manhole in shell
Size of compensating ring No. and Description of Furnaces in each boiler Material Outside diameter
Length of plain part top Thickness of plates crown Description of longitudinal joint No. of strengthening rings
bottom Working pressure of furnace by the rules Combustion chamber plates: Material Thickness: Sides Back Top Bottom
Pitch of stays to ditto: Sides Back Top If stays are fitted with nuts or riveted heads Working pressure by rules
Material of stays Area at smallest part Area supported by each stay Working pressure by rules End plates in steam space:
Material Thickness Pitch of stays How are stays secured Working pressure by rules Material of stays
Area at smallest part Area supported by each stay Working pressure by rules Material of Front plates at bottom
Thickness Material of Lower back plate Thickness Greatest pitch of stays Working pressure of plate by rules
Diameter of tubes Pitch of tubes Material of tube plates Thickness: Front Back Mean pitch of stays
Pitch across wide water spaces Working pressures by rules Girders to Chamber tops: Material Depth and
thickness of girder at centre Length as per rule Distance apart Number and pitch of stays in each
Working pressure by rules Steam dome: description of joint to shell % of strength of joint
Diameter Thickness of shell plates Material Description of longitudinal joint Diam. of rivet holes
Pitch of rivets Working pressure of shell by rules Crown plates Thickness How stayed
SUPERHEATER. Type Date of Approval of Plan Tested by Hydraulic Pressure to
Date of Test Is a Safety Valve fitted to each Section of the Superheater which can be shut off from the Boiler
Diameter of Safety Valve Pressure to which each is adjusted Is Easing Gear fitted

If so, is a report now forwarded?

The foregoing is a correct description,

Manufacturer.

Dates of Survey while building	{	During progress of	{	(1924) July 24-28.
		work in shops - -		
		During erection on		
		board vessel - -		
		Total No. of visits		2

Is the approved plan of main boiler forwarded herewith

“ “ “ *donkey* “ “

Dates of Examination of principal parts—Cylinders *Slides* *Covers* *Pistons* *Rods*
Connecting rods *Crank shaft* *Thrust shaft* *Tunnel shafts* *Screw shaft* *Propeller*

Stern tube Steam pipes tested Engine and boiler seatings 24.7.24 Engines holding down bolts

Completion of pumping arrangements	Boilers fixed	Engines tried under steam
------------------------------------	---------------	---------------------------

Completion of fitting sea connections 24.7.24 Stern tube 24.7.24 Screw shaft and propeller 28.7.24

Main boiler safety valves adjusted	Thickness of adjusting washers

Material of Crank shaft..... Identification Mark on Do..... Material of Thrust shaft..... Identification Mark on Do.....

<i>Material of Tunnel shafts</i>	<i>Identification Marks on Do.</i>	<i>Material of Screw shafts</i>	<i>Identification Marks on Do.</i>
----------------------------------	------------------------------------	---------------------------------	------------------------------------

Material of Steam Pipes	Test pressure
Cast iron	100 lb. per sq. in.
Wrought iron	150 lb. per sq. in.
Steel	200 lb. per sq. in.

Is an installation fitted for burning oil fuel _____ Is the flash point of the oil to be used over 150° F.

Have the requirements of Section 49 of the Rules been complied with

Is this machinery duplicate of a previous case _____ If so, state name of vessel _____

General Remarks (State quality of workmanship, opinions as to class, &c.)

This vessel has proceeded to Glasgow where the machinery will be fitted on board.

Certificate (if required) to be sent to

The amount of Entry Fee	...	£	:	:	When applied for,
Special	...	£	:	:	19.....
Donkey Boiler Fee	...	£	:	:	When received,
Travelling Expenses (if any)	£	:	:	:	19.....

S. F. Doney.
Engineer Surveyor to Lloyd's Register of Shipping.

Committee's Minute GLASGOW -4 NOV 1927
Assigned See Gls Rpt. No. 43990.