

S.S. D. ROWAN & CO 966

S.H. No. 496

PARTICULARS REQUIRED FOR LLOYDS REGISTER.

Type of Superheater.	NE.M. SMOKE - TUBE.
Tube Manufacturers.	TALBOT - STEAD.
Header -do-	FRODINGHAM STEEL CO.
Number of Elements (Total).	112.
Material of Tubes.	SOLID DRAWN STEEL.
Internal dia. & thickness.	17 m/m — 2 1/2 m/m
Material of Headers.	FORGED STEEL.
Tensile strength of Headers.	26-30 TONS/□"
Thickness of Headers.	7/8"
Can the Superheater be shut off and Boiler worked separately.	SEE D. ROWAN & CO.
Is a Safety Valve fitted to every part of Superheater which can be shut off from Boiler.	" " " "
Area of Safety Valve.	" " " "
Are safety valves fitted with Easing Gear.	" " " "
W.P. as per rules.	220 lbs/□"
Pressure to which Safety Valves are adjusted.	SEE D. ROWAN & CO.
<u>Hydraulic test pressure:-</u>	
Tubes.	1500 lbs/□"
Headers.	660 lbs/□"
Assembled in place.	SEE D. ROWAN & CO.
Are drain cocks fitted to free Superheater from water where necessary.	YES
H.P. CYLINDER LINER INCREASED FROM	DIA. TC DIA.

