

GENERAL REMARKS—(continued).

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of ^{R&D} ~~10~~ ^{10.83} ft., R.Q.D. . . . ft., Bridge ^{15.33} ft., Forecastle ²⁸ ft. (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated.

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given should appear in the Register Book) *See dk. (sk.)*
 Official No. *1143,668*; Signal Letters . . . State if Machinery is fitted aft *Yes*.
 How are the surfaces preserved from oxidation? Inside *Paint & Cement*. Outside *Paint*.

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors *Cell. D.B.*

Where Fitted.	*Length. Feet.	Water Capacity. Tons.	Where Fitted.	*Length. Feet.	Water Capacity. Tons.
Double bottom, aft,			Fore peak tank,		
Double bottom, under Engines and Boilers,			After peak tank,		
Double bottom, if under Engines only,			Deep tank, aft,		
Double bottom, if under Boilers only,			Deep tank, forward,		
Double bottom, forward,			Other tanks, if fitted,		
	<i>136</i>	<i>215</i>	(If necessary, furnish further information by sketch.)		
	Total capacity of double bottom	<i>215</i>			

* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules. *Yes.*

Order for Special Survey No. *5247*

Date *23.6.19.*

No. *266* in builder's yard.

DATES of Surveys held while building

1919. Sept. 10. 30. Oct 30. Nov 4. 5. 11. 14. 19. Dec 5. 10. 16. 19. 20. Jan 21. 26. Feb 5. 11. 14. 20. 25. Mar 2. 16. Apr 2. 9. 14. 28. May 12. June 8. 10. 11. 16. 22. July 1. 13. 26. Aug 5. 17. Sept 7. 8.

Surveyor's Signature

M. Macleod

© 2021

Total No. of Visits *34*

Lloyd's Register Foundation