

REPORT ON ELECTRIC LIGHTING INSTALLATION. No. 25923

Port of London. Date of First Survey 25 Nov. Date of Last Survey 28 Nov. No. of Visits 2
 No. in Reg. Book 55 Anglo-Brazilian on the Iron or Steel London Port belonging to
 Built at Sunderland By whom Shat Bros. When built 1913
 Owners Nitrate Producers Ltd Owners' Address London
 Yard No. 381 Electric Light Installation fitted by Messrs. Clarke Chapman & Co. Ltd When fitted 1913

DESCRIPTION OF DYNAMO, ENGINE, ETC.

One single cylinder double acting open type vertical engine direct coupled to a continuous current compound wound dynamo.

Capacity of Dynamo 136 Amperes at 110 Volts, whether continuous or alternating current continuous

Where is Dynamo fixed in Engine Room Whether single or double wire system is used double

Position of Main Switch Board near dynamo having switches to groups A B C D E of lights, &c., as below

Positions of auxiliary switch boards and numbers of switches on each each light & group of lights provided with switches as required

If fuses are fitted on main switch board to the cables of main circuit Yes and on each auxiliary switch board to the cables of auxiliary circuits Yes and at each position where a cable is branched or reduced in size Yes and to each lamp circuit Yes

If vessel is wired on the double wire system are fuses fitted to both flow and return wires or cables of all circuits including lamp circuits Yes

Are the fuses of non-oxidizable metal Yes and constructed to fuse at an excess of 50 per cent over the normal current

Are all fuses fitted in easily accessible positions Yes Are the fuses of standard dimensions Yes If wire fuses are used are permanent instructions fitted on or near each switch board giving particulars of proper size of fuse for each circuit Yes

Are all switches and fuses constructed of incombustible materials and fitted on incombustible bases Yes, slate & porcelain

Total number of lights provided for 164-160P arranged in the following groups :-

A	<u>37</u>	lights each of	<u>16</u>	candle power requiring a total current of	<u>18.9</u>	Amperes	
B	<u>33</u>	lights each of	<u>16</u>	candle power requiring a total current of	<u>16.8</u>	Amperes	
C	<u>44</u>	lights each of	<u>16</u>	candle power requiring a total current of	<u>22.4</u>	Amperes	
D	<u>25</u>	lights each of	<u>16</u>	candle power requiring a total current of	<u>12.7</u>	Amperes	
E	<u>25</u>	lights each of	<u>16</u>	candle power requiring a total current of	<u>12.7</u>	Amperes	
<u>2</u>	Mast head light with	<u>1</u>	lamps each of	<u>32</u>	candle power requiring a total current of	<u>1</u>	Amperes
<u>2</u>	Side light with	<u>1</u>	lamps each of	<u>32</u>	candle power requiring a total current of	<u>1</u>	Amperes
<u>4</u>	Cargo lights of	<u>6-16</u>	candle power, whether incandescent or arc lights	<u>incandescent</u>			

If arc lights, what protection is provided against fire, sparks, &c. —

Where are the switches controlling the masthead and side lights placed in Chart Room

DESCRIPTION OF CABLES.

Main cable carrying 136 Amperes, comprised of 37 wires, each 15 S.W.G. diameter, 15000 square inches total sectional area

Branch cables carrying 22.4 Amperes, comprised of 7 wires, each 18 S.W.G. diameter, 01246 square inches total sectional area

Branch cables carrying 12.7 Amperes, comprised of 1 wires, each 14 S.W.G. diameter, 00502 square inches total sectional area

Leads to lamps carrying 51 Amperes, comprised of 1 wires, each 18 S.W.G. diameter, 00781 square inches total sectional area

Cargo light cables carrying 3 Amperes, comprised of 168 wires, each 38 S.W.G. diameter, 00502 square inches total sectional area

DESCRIPTION OF INSULATION, PROTECTION, ETC.


Vulcanized india rubber taped & braided & lead covered where exposed steel armored & braided cable.

Joints in cables, how made, insulated, and protected no joints except mechanical ones

Are all the joints of cables thoroughly soldered, and the flux used not containing acids or other corrosive substances Yes Are all joints in accessible positions, none being made in bunkers, cargo spaces, or spaces which may at any time be used for carrying cargo, stores, or baggage Yes No

Are there any joints in or branches from the cable leading from dynamo to main switch board No

How are the cables led through the ship, and how protected lead covered armored & braided cable clipped to beam on underside of deck with strong galvanized iron clips



DESCRIPTION OF INSULATION, PROTECTION, ETC.—continued.

Are they in places always accessible no

What special protection has been provided for the cables in open alleyways or where exposed to weather or moisture lead lined & steel
armoured

What special protection has been provided for the cables near galleys or oil lamps or other sources of heat lead lined & steel armoured

What special protection has been provided for the cables near boiler casings " " "

What special protection has been provided for the cables in engine room " " "

How are cables carried through beams in lead bushes through bulkheads, &c. in W T glands

How are cables carried through decks in galvanized iron deck tubes

Are any cables run through coal bunkers Yes. or cargo spaces Yes. or spaces which may be used for carrying cargo, stores, or baggage Yes.

If so, how are they protected lead lined armoured & braided steel.

Are any lamps fitted in coal bunkers or spaces which may at times be used for cargo, coals, or baggage No

If so, how are the lamp fittings and cable terminals specially protected _____

Where are the main switches and fuses for these lights fitted _____

If in the spaces, how are they specially protected _____

Are any switches or fuses fitted in bunkers no.

Cargo light cables, whether portable or permanently fixed portable How fixed to W T connection boxes.

In vessels fitted on the single wire system, how is the dynamo terminal fixed to the hull of vessel double wire system

How are the returns from the lamps connected to the hull _____

Are all the joints with the hull in accessible positions _____

Is the installation supplied with a voltmeter Yes. and with an amperemeter Yes. fixed in hatchboard

VESSELS BUILT FOR CARRYING PETROLEUM.

In vessels built for carrying petroleum, are all switches and fuses fitted in positions not liable to the accumulation of petroleum vapour or gas _____

Are any switches, fuses, or joints of cables fitted in the pump room or companion _____

How are the lamps specially protected in places liable to the accumulation of vapour or gas _____

The copper used is guaranteed to have a conductivity of not less than that of the Engineering Standards Committee's standard, and the wires are protected by tinning from the sulphur compounds present in the insulating material.

Insulation of cables is guaranteed to have a resistance of not less than 600 megohms per statute mile at 60° Fahrenheit after 24 hours' immersion in water, the test being made after one minute's electrification at not less than 500 volts and while the cable is still immersed.

The foregoing statements are a correct description of the Electric Light installation fitted by us on this vessel and we declare that it is at this date in good order and safe working condition.

For Clarke, Chapman & Co. Ltd.

Electrical Engineers

Date Dec 16th 1913

COMPASSES.

Distance between dynamo or electric motors and standard compass 112 ft

Distance between dynamo or electric motors and steering compass 106 "

The nearest cables to the compasses are as follows:—

A cable carrying	.51	Amperes	12	feet from standard compass	6	feet from steering compass
A cable carrying	.51	Amperes	6	feet from standard compass	12	feet from steering compass
A cable carrying	—	Amperes	—	feet from standard compass	—	feet from steering compass

Have the compasses been adjusted with and without the electric installation at work at full power Yes.

The maximum deviation due to electric currents, etc., was found to be nil. degrees on all. course in the case of the standard compass and nil. degrees on all. course in the case of the steering compass.

FOR SHORT BROTHERS, LIMITED.

Builder's Signature.

Date 18th December 1913.

GENERAL REMARKS.

Joseph Short
MANAGING DIRECTOR

The installation has been satisfactorily fitted in the vessel tested at full load and found good.

It is submitted that this vessel is eligible for THE RECORD, Elec. light-

Lewis Harris
Surveyor to Lloyd's Register of British and Foreign Shipping.

Committee's Minute

Im. 912.—Transfer.

THE SURVEYORS ARE REQUESTED NOT TO WRITE ACROSS THIS MARGIN.



© 2021

Lloyd's Register Foundation