

25887

S.S. "UMBE"

N.B.—If this Report is copied by Copying Press, special care must be taken that the copying paper is not so much dampened as to spread the ink, or to cause it to show through to the other side.

OF THE SURVEYORS ARE REQUESTED NOT TO WRITE ACROSS THIS MARGIN.

When Anchors or Cables are supplied, the particulars are to be reported in the following form:—

ANCHORS.

Number of Certificate.	Anchors.*	WEIGHT, EX. STOCK.			WEIGHT OF STOCK.			TEST, PER CERTIFICATE.			WEIGHT REQUIRED by TABLE 30 or 31.			Description of Anchor.	Makers.	Where and when tested and Superintendent.
		Cwts.	qrs.	lbs.	Cwts.	qrs.	lbs.	Tons.	Cwts.	qrs.	lbs.	Cwts.	qrs.			
16370	1st Bower ...	40	1	0	STOCKLESS	35	18	3	0	38	3	0	Byers Stockless	Not Stated	LPH-5 10/12/12 L. Haffner	
	2nd "															
	3rd "															
	Collector Weight.															
	Stream															
	Kedge.....															

* When a bower anchor is supplied it must be clearly stated whether it is a 1st, 2nd, or 3rd bower.

CHAIN CABLES.

Number of Certificate.	Length, and size supplied.		Test per Certificate.		WEIGHT OF CHAIN CABLE.		Length and size per Table 30 or 31.		Description.	Makers of Cables.	When and where tested and Superintendent.
	Length.	Diam.	Statutory.	Breaking.	Supplied.	Per Table 30 or 31.	Length.	Diam.			
4116	14 3/4	1 1/8	598	824	25.014		240	1 7/8	STUB LINK	Not Staked	LPH-T 31/10/12 Perrins
4117	15 1/2	"	"	"	26.23				"	"	"
41357	15 1/2	"	"	"	25.022				"	"	5/12/12
41358	15	"	"	"	25.020				"	"	"
Iron Steam Chain or Steel Wire...					102.03	99.122					