

REPORT ON ELECTRIC FITTINGS.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

Received at London Office

19 JAN 1927

Date of writing Report 21. 12. 1926 When handed in at Local Office 10.1.27 10 Port of GLASGOW.

No. in Survey held at GREENOCK. Date, First Survey 18th May Last Survey 27th Decr 1926
Reg. Book. S. S. "RODNEYSTAR" (Number of Visits... 27)

81410 on the Tons { Gross 10583
Net

Built at PORT GLASGOW By whom built MESSRS LITHGOW & CO Yard No. 785 When built 1926.

Owners THE BLUE STAR LINE (1920) LTD Port belonging to LONDON.

Electric Light Installation fitted by MESSRS TELFORD GRIER & MCKAY Contract No. 785 When fitted 1926.

System of Distribution Two Wire ✓
Pressure of supply for Lighting 220V. ✓ volts, Heating 220V. ✓ volts, Power 220V. ✓ volts.

Direct or Alternating Current, Lighting Direct ✓ Power Direct ✓

If alternating current system, state frequency of periods per second —

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off yes ✓

Generators, do they comply with the requirements regarding overload yes ✓, are they compound wound yes ✓

are they over compounded 5 per cent. yes ✓, if not compound wound state distance between each generator —

Where more than one generator is fitted are they arranged to run in parallel yes ✓, is an adjustable regulating resistance fitted in series with each shunt field yes

Are all terminals accessible and clearly marked yes, are they so spaced or shielded that they cannot be accidentally earthed,

or short circuited yes Are the lubricating arrangements of the generators as per Rule yes

Position of Generators Starboard Side Lower Engine Room. are they clear of all inflammable material yes

is the ventilation in way of the generators satisfactory yes, if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the generators

and —, are the generators protected from mechanical injury and damage from water, steam or oil yes

are their axis of rotation fore and aft yes are the prime movers and

Earthing, are the bedplates and frames of the generating plant efficiently earthed yes

their respective generators in metallic contact yes

Main Switch Boards, where placed Aft Bulkhead Engine Room

If the generators and main switchboard are not placed in the same compartment, is each generator provided with a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard —

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes yes

are they protected from mechanical injury and damage from water, steam or oil yes, if situated near unprotected

woodwork or other combustible material, state distance of same horizontally from or vertically above the switchboards — and —

are they constructed wholly of durable, incombustible non-absorbent materials. yes, is all insulation of high dielectric strength and of

permanently high insulation resistance Slate Base, if semi-insulating material is used, are all conducting parts connected to one pole

insulated from the slab with mica or micanite and the slab similarly insulated from its framework yes, and is the

frame effectively earthed yes Are the following fittings as per Rule, viz.:— spacing or shielding of live parts

yes, accessibility of all parts yes, absence of fuses on back of board yes, proportion of omnibus

bars yes, individual fuses to voltmeter, pilot or earth lamp yes, connections of switches yes

Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches

Each Generator is protected with 3 pole (2 Pole + Equalizer) overload No Volt & Reverse Circuit Breaker.

Larger Circuits D.P. Overload Circuit Breaker Smaller Circuits M.P. Switch D.P. Fuses.

Instruments on main switchboard 3 ammeters 2 voltmeters — synchronising device for paralleling purposes.

Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system

Switch Fuse & Lamp in Circuit between each Bus Bar & Earth.

Switches, Circuit Breakers and Fusible Cut-outs, do these comply with the requirements of the Rules yes

Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per rule yes



© 2020

Lloyd's Register
Foundation
WTJ-0158(112)

Insulation of Cables, state type of cables, single or twin *Single* are the cables insulated and protected as per Tables III or IV of the Rules *yes*
Fall of Pressure, state maximum between bus bars and any point of the installation under maximum load *8 Volts Lighting 12V Power*
Cable Sockets and other connections, are the ends of all cables having a sectional area of 0.007 square inch and above provided with soldering sockets *yes*

Paper Insulated Cables, If cables are paper covered, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound *yes*
Cable Runs, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage *yes*

Support and Protection of Cables, state how the cables are supported and protected *Clipped to Bulkheads & Under Side of Deck. Run in Steel Tube where exposed on Deck.*
If cables are run in wood casings, are the casings and caps secured by screws —, are the cap screws of brass —, are the cables run in separate grooves —. If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VI *yes*

Refrigerated Chambers, if lights are fitted, are the cables and fittings in accordance with the special requirements *yes*
Joints in Cables, state if any, and how made, insulated, and protected *none*

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands *yes*
Bushes in Beams and Non-watertight Positions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed *yes* state the material of which the bushes are made *lead*
Earthing Connections, state what earthing connections are fitted and their respective sectional areas —, are their connections made as per Rule *yes*

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule *yes*
Emergency Supply, state position and method of control of the emergency supply and how the generator is driven —

Navigation Lamps, are these separately wired *yes*, controlled by separate switch and separate fuses *yes*
are the fuses double pole *yes*, are the switches and fuses grouped in a position accessible only to the officers on watch *yes*
has each navigation lamp an automatic indicator as per Rule *yes*, are separate screens provided for the use of oil and electric side lights *yes*
are separate oil lanterns provided for the mast head lights and side lights *yes*
Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight *yes*
are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected *yes*
Well Glass Fittings enclosed in Strong Metal Guard.
are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected —, how are the cables led —

where are the controlling switches situated —

Searchlight Lamps, No. of —, whether fixed or portable —, are their fittings as per Rule —
Arc Lamps, other than searchlight lamps, No. of —, are their live parts insulated from the frame or case —, are their fittings as per Rule —
Motors, are their working parts readily accessible *yes*, are the coils self-contained and readily removable for replacement *yes*
are the brushes, brush holders, terminals and lubricating arrangements as per Rule *yes*, are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material *yes*
are they protected from mechanical injury and damage from water, steam or oil *yes* are their axis of rotation fore and aft *yes*
if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type —, if not of this type, state distance of the combustible material horizontally or vertically above the motors — and —

Control Gear and Resistances, are the generator field and motor speed regulators, starters and controllers constructed as per Rule *yes*

Lightning Conductors, where lightning conductors are required, are these fitted as per Rule *yes*

Ships carrying Oil having a Flash Point less than 150° F. Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings. —

If portable lamps for use in dangerous spaces are supplied, are they of a type approved by the Home Office —

PARTICULARS OF GENERATING PLANT.

DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY.	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE	
		Kilowatts.	Volts.	Ampères.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.
MAIN	2	150	220	750	350	Steam engine (Compound).		
AUXILIARY	—	165						
EMERGENCY	—							
ROTARY TRANSFORMER								

LIGHTING AND HEATING CONDUCTORS.

Ref. No.	DESCRIPTION.	No. of Conductors.	Effective Area of each Conductor. Sq. Ins.	COMPOSITION OF STRAND.		Total Maximum Current. Amperes.	Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
				No.	Diameter.				
	MAIN GENERATORS, each	2	.600	91	.093	750	45	V.I.R.	L.C.A. & B.
	AUXILIARY GENERATOR	—	.500	61	.103				
	EMERGENCY GENERATOR	—							
	ROTARY TRANSFORMER	—							
Refrig.	AUXILIARY SWITCHBOARD	1	.150	37	.072	212	144	Paper	L.C.A. & B.
	ENGINE ROOM	—							
	BOILER ROOM	—							
	Navigation	1	.0045	4	.029	4	618	V.I.R.	L.C.A. & B.
	Machinery Space	1	.007	4	.036	23	42	V.I.R.	L.C.A. & B.
	Forward Cargo	1	.007	4	.036	12	396	V.I.R.	L.C.A. & B.
	Aft Cargo	1	.0045	4	.029	11	336	V.I.R.	L.C.A. & B.
	Deck Lights	1	.0045	4	.029	10	156	V.I.R.	L.C.A. & B.
	Engineers & Poop	1	.007	4	.036	20	156	V.I.R.	L.C.A. & B.
	Saloon & Locde.	1	.0225	4	.064	25	522	V.I.R.	L.C.A. & B.
	Heater Dis. Box fed from Saloon D.B.	1	.007	4	.029	10	60	V.I.R.	L.C.A. & B.
	WIRELESS	1	.007	4	.036	4	618	V.I.R.	L.C.A. & B.
	SEARCHLIGHT	1	.003	3	.036	1/2		V.I.R.	L.C.A. & B.
	MASTHEAD LIGHT	1	.003	3	.036	1/2		V.I.R.	L.C.A. & B.
	SIDE LIGHTS	1	.003	3	.036	1/2		V.I.R.	L.C.A. & B.
	COMPASS LIGHTS	—							
	POOP LIGHTS	1	.003	3	.036	2		V.I.R.	L.C.A. & B.
	CARGO LIGHTS	—							
	ARC LAMPS	1	.003	3	.036	4		V.I.R.	L.C.A. & B.
	HEATERS	—							

MOTOR CONDUCTORS.

Ref. No.	DESCRIPTION.	No. of Motors.	Effective Area of each Conductor. Sq. Ins.	COMPOSITION OF STRAND.		Total Maximum Current. Amperes.	Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
				No.	Diameter.				
	BALLAST PUMP	—							
	MAIN BILGE LINE PUMPS	—							
	GENERAL SERVICE PUMP	—							
	EMERGENCY BILGE PUMP	—							
	SANITARY PUMP	—							
	CIRC. SEA WATER PUMPS	—							
	CIRC. FRESH WATER PUMPS	—							
	AIR COMPRESSOR	—							
	FRESH WATER PUMP	—							
	ENGINE TURNING GEAR	—							
	ENGINE REVERSING GEAR	—							
	LUBRICATING OIL PUMPS	—							
	OIL FUEL TRANSFER PUMP	—							
	WINDLASS	—							
	WINCHES, FORWARD	—							
	WINCHES, AFT	—							
	STEERING GEAR	—							
	WORKSHOP MOTOR	1	.0045	4	.029	15	252	V.I.R.	L.C.A. & B.
	VENTILATING FANS Ford Box	1	.04	19	.052	56	330	V.I.R.	L.C.A. & B.
	" Aft Box	1	.04	19	.052	56	270	V.I.R.	L.C.A. & B.
	Refrig. Forward Box	1	.100	19	.083	110	102	V.I.R.	L.C.A. & B.
	" Aft Box	1	.100	19	.083	98	120	V.I.R.	L.C.A. & B.
	Brine Pumps Box	1	.100	19	.083	98	90	V.I.R.	L.C.A. & B.
	Forced Draught Box	1	.150	37	.072	208	132	Paper	L.C.A. & B.
	6 Fans on C.O. Surs. each	1	.01	4	.044	28	30/200	V.I.R.	L.C.A. & B.
	4 Refrig. Pumps each	1	.06	19	.064	66	48	V.I.R.	L.C.A. & B.
	2 Brine Pumps each	1	.06	19	.064	66	75	V.I.R.	L.C.A. & B.
	2 Forced Draught each	1	.2	37	.083	167	30/80	V.I.R.	L.C.A. & B.

All Conductors are of annealed copper conforming to British Standard Specification No. 7.
The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.
The foregoing is a correct description.

TELFORD, GRIER & MACKAY, LTD.

Electrical Engineers.

Date 24/12/26

COMPASSES.

Distance between electric generators or motors and standard compass 170 ft San Motor 72 ft.
Distance between electric generators or motors and steering compass 170 ft " " 70 ft.

The nearest cables to the compasses are as follows:—

A cable carrying 4 Amperes 8 feet from standard compass 5 feet from steering compass.

A cable carrying 1/2 Amperes one feet from standard compass one feet from steering compass.

A cable carrying Amperes feet from standard compass feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power yes

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted yes

The maximum deviation due to electric currents was found to be his degrees on amp. course in the case of the standard compass, and his degrees on amp. course in the case of the steering compass.

LITHGOWS LIMITED.

G. J. Allan

Director & Secretary

Builder's Signature.

Date

24/12/26

Is this installation a duplicate of a previous case no. If so, state name of vessel

General Remarks (State quality of workmanship, opinions as to class, &c.)

This installation has been fitted on board under special survey tested under full working conditions and found satisfactory. The workmanship was found to be good and sound.

It is submitted that this vessel is eligible for THE RECORD. Elec. light.

Total Capacity of Generators

300

Kilowatts

The amount of Fee

£ 39.0.0

When applied for

Travelling Expenses (if any)

£ 1.1.0

When received

Committee's Minute

GLASGOW 18 JAN 1927

Assigned

Elec. Light.

TUES. 19 JUL 1927

FRI. 14 FEB 1930

WED. 11 APR 1929

FRI. 16 NOV 1928

TUE. 4 JUN 1926

FRI. 19 DEC 1931

FRI. 27 FEB 1931

FRI. 1 MAY 1931

Lloyd's Register Foundation