



WORKING PRESSURE = 180 LBS. PER SQ. INCH. TEST PRESSURE = 360 LBS. PER SQ. INCH. TO LLOYDS REQUIREMENTS.

ALL PLATES, RIVETS & STAYS OF STEEL. TUBES OF IRON LAP WELDED. ALL HOLES TO BE DRILLED IN POSITION.

TENSILE STRENGTH OF SHELL PLATES, GIRDERS & BUTTSTRAPS TO BE NOT LESS THAN 20% OR MORE THAN 33 TONS PER SQ. INCH.

OTHER	26	20%
LONGITUDINAL STAYS	28	52
RIVETS & SCREW STAYS	26	50

ELONGATION OF SHELL PLATES, BUTTSTRAPS, GIRDERS, & LONGITUDINAL STAYS, TO BE NOT LESS THAN 20% IN A LENGTH OF 8".

OTHER	25%	
SCREW STAYS	23%	3 TIMES DIA. OF TEST PIECE
RIVETS	25%	

13/9/12
N^o 986

SUNDERLAND

GEORGE CLARK LTD

(2) BOILERS NO 986

W.P. = 180 LBS

S.P. AUSTIN & SON SpN^o 268

Mark on boilers:—

NO 3118

LLOYD'S TEST

360 LBS

5-6-1913 L.C.D.



S.S. "Moto"

Sld Rpt © 1223457



Lloyd's Register
Foundation

W847-0222