

Guard rails on shelter deck, forward & aft 42" high, 3 rails, stanchions spaced about 55" apart.
Steel bulwark 22" & fore end of breakwater 42" "

Lloyd's Register of Shipping.

COPY OF FREEBOARD REPORT.

Ship's Name **LANGLEECRAG**Official Number **161528**Type **Complete Superstructure with Tonnage Opening.**

PARTICULARS OF SUPERSTRUCTURES.

	Mean covered length.	Height.
Poop enclosed - - - - -	30.00	8.75
„ overhang - - - - -		
R.Q.D. enclosed - - - - -		
„ overhang - - - - -		
Bridge enclosed - - - - -	379.75	8.75
„ overhang aft - - - - -		
„ overhang forward - - - - -		
F'cle enclosed - - - - -		
„ overhang - - - - -		
Trunk aft - - - - -		
„ forward - - - - -		
Tonnage opening aft - - - - -	5.25	
„ „ forward - - - - -		
TOTAL - - - - -	415.00	

5m. 4.37.



© 2020

Lloyd's Register
Foundation

Exposed machinery casings on Superstructure Decks44	.38	32 x 22 x .34	31.	Knees at Top	56 x 24	18	7-6
Machinery Casings within Superstructures not fitted with Class I Closing Appliances38	.32.	3 x 3 x .38	31	attached to beams over	7/16 and 2-6 x 16 Boiler Casing	12.	8-9.