

Any modification necessary
[Para. 4 (a) to (e)]*

CD13 760

Correction for 10ft., Table A. 1.45 ✓
× Difference divided by 10 18.02 (if req
If $\frac{1}{10}$ ths length covered divide by 2 5.01 ✓

Name of Vessel *S. S. "LANGLEECRAG"*

No. in Register Book

	FEET.	INCHES.
Moulded Depth	28	3
Stringer Plate		$\frac{1}{2}$
Thickness of wood sheathing if required		✓
Statutory deck line above intersection of <u>actual</u> deck at side		$1\frac{3}{4}$
Total depth from top of statutory deck line to top of keel	28	$5\frac{1}{4}$
Freeboard recorded	3	8
Moulded Draft	24	$9\frac{1}{4}$
Add for keel—Flat or Bar		$2\frac{1}{4}$
Draught	24	$11\frac{1}{2}$
<i>Δ Scale</i>	24	$11\frac{3}{8}$
Draught for record	24	$11\frac{1}{4}$



© 2020

Lloyd's Register
Foundation

frames, skin planking, or ceiling are of unusual thickness the breadth of vessel to inside
galling should be reported if possible.
In obtaining an allowance for deck erections under Para. 11 where the sheer drops abaft amid-
ship the height of the R.Q.D. is to be taken from the level of the top of the amidship beam.
In vessels having poops and forecastles, it means the sheer measured at the stem and stern-
length of the vessel's length from stem and stern.

State dimensions of freeing port area on back of this form.
The Surveyor should state whether the fall in sheer is measured relatively to
line of keel or to the water line. If measured relatively to the vessel's
line of keel or to the water line. If measured relatively to the vessel's
line of keel or to the water line. If measured relatively to the vessel's