

3 JAN 1936

Amended to 5/8" thickness  
and 28/32 Tensile. Am. B. Edwards  
Hull. 10/1/36.

See attached  
sketch for  
detail of welding  
WELDING WITH  
APPROVED ELECTRODES.

DRAIN  
COCK.

ENDS. 1 1/4" THICK 28/32 TENSILE

VOLUME 9 Cu. ft.

ONE DOUBLE RIVETED LAP 7/8" RIV 3 DIAS APART. CR TO CR.

5'-4 9/16"

Details of riveting  
to Surveyors satisfaction

1/2" ST PIPE THREAD

2" 1 3/4" DIA HOLE

1/2" ST PIPE THREAD

Stop Valve for Pipe  
to RAMP HEATING. REQUIRED.  
Not Required

Stop Valve for Pipe to  
REV. VALVE ON GOVERNOR

Stop Valve for Pipe to CHARGING  
VALVE OF PIST. CYLINDER

This hole not  
to be less  
than 2" dia  
for inspection  
purpose.

PROPOSED. AIR. RECEIVER. FOR. M.V. LIZZIE & ANNIE.

WORKING. PRESSURE 280 Lbr.

UNION DRY DOCK & ENG CO LTD  
HULL.



© 2018

Lloyd's Register  
Foundation



S.S. Lizzie & Annie

HULL REPORT No. 46562.

LR-FAF-SA13-P-18



© 2018

Lloyd's Register  
Foundation