


PARTICULARS OF LONGITUDINAL FRAMING.

FRAMING.		AMIDSHIPS.			ENDS.			AMIDSHIPS.			ENDS.			RIVETING.			
		In Ship.			In Ship.			Per Rule or as approved.			Per Rule or as approved.			Rivets in Longitudinal Frames. Diam. Spacing.	Spacing of Rivets on each side of Transverses and Bulkheads.	Rivets in Brackets to Bulkheads.	
		Plt.	Plt.	Plt.	Plt.	Plt.	Plt.	Plt.	Plt.	Plt.	Plt.	Plt.	Plt.			Number.	Diameter.
Framing of 																	
Frames in Bridge 'tween Decks ...		✓	✓	✓													
Frames from Uppermost Continuous Deck		230	90	11				230	90	11				25	150	8	22
Framing from Awning, Shelter or Upper Deck to Margin Plate.																	
" 1		230	90	11				230	90	11							
" 2																	
" 3																	
" 4		210	85	14				210	85	14							
" 5		260	90	14				260	90	14					10 Rivets at 100	10	22
" 6																	
" 7																	
" 8																	
" 9		300	100	16				300	100	16					10 Rivets at 90	12	22
" 10																	
" 11		181	102	14 1/2				181	102	14 1/2						16	
" 12																22	
" 13																16	
" 14																16	
" 15																22	
" 16																22	
Spacing of Longitudinal Frames																	
Amidships		760						760									
At Ends																	
Double Bottoms																	
Tank Top Longitudinals		457	100	16 1/2				457	100	16 1/2				25	110		
Bottom		432	102	17 1/2				432	102	17 1/2				25	150	10 Rivets at 90	
Spacing of Longitudinals																	
Amidships		760						760									
At Ends																	
Transverses.																	
In Bridge																	
'tween Decks																	
Depth and Thickness		✓	✓	✓													
Face Angles		✓	✓	✓													
Lugs to Shell*		✓	✓	✓													
In Awning, Shelter or Upper 'tween Decks.																	
Depth and Thickness		✓	✓	✓													
Face Angles		✓	✓	✓													
Lugs to Shell*		✓	✓	✓													
In Hold.																	
Depth and Thickness		990	11														
Face Angles		180	90	13													
Lugs to Shell*		150	150	14										25	100		
Brackets		11															
Spacing of Transverse Frames		3048															
* State if joggled or liners.																	
Longitudinal Beams of																	
Bridge Deck ...		✓	✓	✓													
Awg. or Shltr. Dk.		✓	✓	✓													
Upper		200	85	14				200	85	14				760			
Second		✓	✓	✓				✓	✓	✓				✓			
Third		✓	✓	✓				✓	✓	✓				✓			
Transverse Beams.																	
In Ship.																	
Plt.		610	11	130	90			610	11	130	90						
Angles		✓	✓	✓				✓	✓	✓							
As approved.																	
Plt.		610	11	130	90			610	11	130	90						
Angles		✓	✓	✓				✓	✓	✓							

The particulars of framing in peaks (if ordinary), Floors, Centre Girder, Side Girders and Margin Plate and their angle attachments, etc., to be entered in their respective places provided for on the Report Forms.

NOTE:—This slip to be pasted on the fourth page of the Report, and reference to same to be made under framing, etc., on the first page.