

Equivalent Depth

For LONDON OFFICE ONLY

LLOYD'S REGISTER OF SHIPPING

UNITED WITH THE BRITISH CORPORATION REGISTER

SURVEYS FOR FREEBOARD

(COMPUTATION FOR STEAMER, SAILING SHIP, TANKER)

Received

Index No.

Govt. Copy

Owners C11

Ship's Name <i>Ansaldo 918</i>	Official Number	Nationality and Port of Registry	Gross Tonnage	Date of Build	Port of Survey
Moulded Dimensions: Length <i>626.77</i>	Breadth	Depth <i>35.8' actual</i>			Date of Survey
Freeboard Length					Surveyor's Signature
Moulded displacement at moulded draught = 85 per cent. of moulded depth (excluding bossing)					Particulars of Classification <i>+ 100 A1</i>
Coefficient of fineness for use with Tables <i>68 Actual</i>					<i>con temperature</i>

DEPTH FOR FREEBOARD (D). Moulded depth <i>Actual</i> ... <i>35.80</i> Stringer plate ... <i>03</i> Wood Sheathing on exposed deck $T \left(\frac{L-S}{L} \right) =$ Depth for Freeboard (D) = <i>35.83</i>	DEPTH CORRECTION. (a) Where D is greater than Table depth (D-Table depth) R = (b) Where D is less than Table depth (if allowed) (Table depth-D) R = <i>41.29 - 35.83 = 5.46</i> If restricted by superstructures <i>17.88</i>	ROUND OF BEAM CORRECTION. Moulded Breadth (B) Standard Round of Beam = $\frac{B \times 12}{50} =$ Ship's Round of Beam = Difference Restricted to Correction = $\frac{\text{Diff}}{4} \times \left(1 - \frac{S_1}{L} \right) =$
---	---	---

DEDUCTION FOR SUPERSTRUCTURES.

	Mean Covered Length (S)	Equivalent Enclosed Length (S ₁)	Height	Height Correction	Effective Length (E)
Poop enclosed ...					
„ overhang ...					
R.Q.D. enclosed ...					
„ overhang ...					
Bridge enclosed ...					
„ overhang aft ...					
„ overhang forward ...					
F'cle enclosed ...					
„ overhang ...					
Trunk aft ...					
„ forward ...					
Tonnage opening aft ...					
„ „ forward ...					
Total ...					

Standard Height of Superstructure *7.5'*
„ „ R.Q.D. *42'*
Deduction for complete superstructure *42'*
Percentage covered $\frac{S}{L} =$
„ $\frac{S_1}{L} =$
„ $\frac{E}{L} =$
Percentage from Table, Line A.
(corrected for absence of forecastle (if required))
Percentage from Table, Line B.
(corrected for absence of forecastle (if required))
Interpolation for bridge less than .2L (if required)
Deduction =

SHEER CORRECTION.

Station	Standard Ordinate	S	M	Product	Actual Ordinate	Effective Ordinate	S	M	Product
A.P. ...		1					1		
$\frac{1}{4}L$ from A.P. ...		4					4		
$\frac{2}{8}L$ „ ...		2					2		
Amidships ...	○	4	○	○	○	○	4	○	○
$\frac{2}{8}L$ from F.P. ...		2					2		
$\frac{1}{4}L$ „ ...		4					4		
F.P. ...		1					1		
Total ...									

Correction = $\frac{\text{Difference between sums of products}}{18} \left(.75 - \frac{S}{2L} \right) =$ *- .5*
If limited on account of midship superstructure.

Mean actual sheer aft
Mean standard sheer aft =
Mean actual sheer forward
Mean standard sheer forward =
Length of enclosed superstructure forward of amidships =
„ „ aft of „ =

If limited to maximum allowance of $1\frac{1}{2}$ ins. per 100 ft.


Deduction for Tropical Freeboard. Addition for Winter and Winter North Atlantic Freeboard. Depth to Freeboard Deck = <i>35.83</i> Summer freeboard = <i>1.30</i> Moulded draught (d) = <i>29.53</i> Keel allowance = Extreme draught = Deduction for Tropical freeboard and addition for = Winter freeboard = $\frac{d}{4}$ inches = Addition for Winter North Atlantic Freeboard (if required) =	Deduction for Fresh Water. Displacement in salt water at summer load water line $\Delta =$ Tons per inch immersion at summer load water line T = Deduction = $\frac{\Delta}{40 T}$ inches =	TABULAR FREEBOARD corrected for Flush Deck (if required) Correction for coefficient Depth Correction ... Deduction for superstructures ... Sheer correction ... Round of Beam correction ... Correction for Thickness of Deck amidships ... Other corrections, scantlings, etc. ... Summer Freeboard = <i>75.64</i>
---	---	--

SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, Wood, Steel, Deck :-

Tropical Fresh Water Line above Centre of Disc	...	Tropical Fresh Water Freeboard	...
Fresh Water Line	...	Fresh Water	...
Tropical Line	...	Tropical	...
Winter Line below	...	Winter	...
Winter North Atlantic Line	...	Winter North Atlantic	...

A new form should be prepared if any alterations that affect the freeboard have been made. If no such alterations have been made, the Surveyor should endorse the form on this side with his signature and the date.

41.79
 7.79
 34.70
 29.53
 17.88
 $447 \times \frac{4}{3} = 596$
 41.79
 31.83



Trade of ship


Names of sister ships

Builder's name and yard number

Owners

Fee £ : :

List of plans forwarded for reference. (See "Instructions to Surveyors, Part 4, 1950," paragraph 11.)



© 2019

Lloyd's Register
 Foundation