

Low Scantlings only

copy for Lender

Index No. \_\_\_\_\_  
(For London Office only.)

# Lloyd's Register of Shipping.

## SURVEYS FOR FREEBOARD.

(COMPUTATION FOR STEAMER, SAILING SHIP, TANKER.)

Ship's Name <b>TRANWERT.</b>	Official Number ✓	Nationality and Port of Registry ✓	Gross Tonnage	Date of Build	Port of Survey <b>Hamburg</b>
YARD NOS. 1940-195					Date of Survey
Moulded Dimensions: Length <b>140.0</b> Breadth <b>32.5</b> Depth <b>12.25</b> <b>12.27</b>					Surveyor's Signature <b>Link</b>
Moulded displacement at moulded draught = 85 per cent. of moulded depth _____ tons					Particulars of Classification <b>100 A1</b> <b>(contemplated)</b>
Coefficient of fineness for use with Tables <b>.68 (assumed)</b> ✓					

DEPTH FOR FREEBOARD (D).	DEPTH CORRECTION.	ROUND OF BEAM CORRECTION.
Moulded depth ... .. <b>12.25</b>	(a) Where D is greater than Table depth (D-Table depth) R =	Moulded Breadth (B) <b>32.5</b>
Stringer plate <b>7 1/2</b> ... .. <b>.023</b>	(b) Where D is less than Table depth (if allowed) (Table depth-D) R =	Standard Round of Beam = $\frac{B \times 12}{50} = 7.8$ ✓
Sheathing on exposed deck $T \left( \frac{L-S}{L} \right) =$ ✓	<b>(12.66-12.27) × 1.461 = .57</b> ✓	Ship's Round of Beam = <b>nil</b> ✓
Depth for Freeboard (D) = <b>12.273</b>	If restricted by superstructures	Difference = $\frac{7.8}{4} = 1.95$ ✓
		Restricted to
		Correction = $\frac{\text{Diff}}{4} \times \left(1 - \frac{S_1}{L}\right) = 1.95 \times .033 = .064$ ✓

## DEDUCTION FOR SUPERSTRUCTURES.

	Mean Covered Length (S)	Equivalent Enclosed Length (S <sub>1</sub> )	Height	Height Correction	Effective Length (E)	
Poop enclosed ... ..	<b>6.21</b>				<b>183.8</b>	Standard Height of Superstructure <b>6.0</b> ✓
" overhang ... ..	<b>2.00</b>				<b>1.00</b>	" " R.Q.D. _____
R.Q.D. enclosed ... ..						Deduction for complete superstructure <b>25.0</b> ✓
" overhang ... ..						Percentage covered $\frac{S}{L} = 100\%$ ✓
Bridge enclosed ... ..			<b>8.0</b>			" " $\frac{S_1}{L} = 98.7\%$ <b>98.68</b> ✓
" overhang aft ... ..	<b>.20</b>				<b>.15</b>	" " $\frac{E}{L} = 98.6\%$ ✓
" overhang forward ... ..					<b>184.95</b>	Percentage from Table, Line A.
F'cle enclosed ... ..	<b>(190.0)</b>				<b>190.00</b>	(corrected for absence of forecastle (if required))
" overhang ... ..	<b>(6.2)</b>				<b>5.05</b>	Percentage from Table, Line B.
Trunk aft ... ..	<b>(183.9)</b>					(corrected for absence of forecastle (if required)) <b>98.23%</b> <b>98.37</b> ✓
" forward ... ..						Interpolation for bridge less than .2L (if required)
Tonnage opening aft ... ..	<b>4.00</b>		<b>5.05 × .5</b> ✓		<b>2.53</b>	Deduction = <b>25.0 × .9823 = 24.589</b> ✓
" " forward ... ..						
Total ... ..	<b>190.0</b>	<b>183.8</b>			<b>187.48</b>	

SHEER CORRECTION. *Measured from rough 100 scale general arrangement*

Station	Standard Ordinate	S	Product	Actual Ordinate	Effective Ordinate	S	Product
24 A.P. ... ..	<b>29.0</b>	✓ 1		<b>23.0</b>	<b>47.0</b>	✓ 1	<b>47.0</b>
1/6 L from A.P. ... ..		4				4	
2/6 L " ... ..		2				2	
0 Amidships ... ..	<b>0</b>	4		<b>0</b>	<b>0</b>	4	<b>0</b>
2/6 L from F.P. ... ..		2				2	
1/6 L " ... ..		4				4	
24 F.P. ... ..	<b>58.0</b>	✓ 1		<b>61.0</b>	<b>85.0</b>	✓ 1	<b>85.0</b>
Total ... ..			<b>261</b>			<b>6</b>	<b>132.0</b>

Mean actual sheer aft = **22.0**  
Mean standard sheer aft = **14.5**  
 $\frac{22.0}{7.5} = 1.88$  ✓

Mean actual sheer forward = **14.5**  
Mean standard sheer forward = **7.5**

Length of enclosed superstructure forward of amidships = **396**  
" " aft of " = **261**  
 $\frac{141}{18} \times \frac{1}{4}$

Correction =  $\frac{\text{Difference between sums of products}}{18} \left( .75 - \frac{S}{2L} \right) =$   
If limited on account of midship superstructure.

If limited to maximum allowance of 1 1/2 ins. per 100 ft.

Deduction for Tropical Freeboard.	Deduction for Fresh Water.	TABULAR FREEBOARD corrected for Flush Deck (if required)
Addition for Winter and Winter North Atlantic Freeboard.	Displacement in salt water at summer load water line	Correction for coefficient
Depth to Freeboard Deck = <b>12.273</b>	$\Delta =$	Depth Correction ... .. <b>0.57</b> ✓
Summer freeboard = <b>11.67</b>	Tons per inch immersion at summer load water line	Deduction for superstructures ... .. <b>24.58</b> ✓
Moulded draught (d) = <b>12.106</b>	T =	Sheer correction ... .. <b>1.88</b> ✓
Deduction for Tropical freeboard and addition for	Deduction = $\frac{\Delta}{40 T}$ inches	Round of Beam correction ... .. <b>1.06</b> ✓
Winter freeboard = $\frac{d}{4}$ inches =		Correction for Thickness of Deck amidships ... .. <b>2.57</b> ✓
Addition for Winter North Atlantic Freeboard (if required) =	<b>12.1</b>	Other corrections, scantlings, etc. ... .. <b>2.63</b> ✓
		Summer Freeboard = <b>2.00</b> ✓


## SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, Wood, Steel, Deck :-

Tropical Fresh Water Line above Centre of Disc ... ..	Tropical Fresh Water Freeboard ... ..
Fresh Water Line " " ... ..	Fresh Water " " ... ..
Tropical Line " " ... ..	Tropical " " ... ..
Winter Line below " " ... ..	Winter " " ... ..
Winter North Atlantic Line " " ... ..	Winter North Atlantic " " ... ..



A new form should be prepared if any alterations that affect the freeboard have been made. If no such alterations have been made, the Surveyor should endorse the form on this side with his signature and the date.

Tonnage Hatch



$$\begin{aligned}
 B_1 &= 32.5 \\
 L &= \frac{15.6}{16.9} \\
 &= \frac{16.9}{32.5} = .52
 \end{aligned}$$

Trade of ship \_\_\_\_\_

Names of sister ships \_\_\_\_\_

Builder's name and yard number \_\_\_\_\_

Owners \_\_\_\_\_

Fee £ \_\_\_\_\_

*Surveyor's Signature*  
*10/10/10*



© 2020

Lloyd's Register  
Foundation