

REPORT ON ELECTRICAL EQUIPMENT.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

26 AUG 1936

25 AUG 1936

Received at London Office

Date of writing Report

10

When handed in at Local Office

10

Port of

HULL

No. in Survey held at

Hull.

Date, First Survey

31st July 1936

Last Survey

12th August 1936

Reg. Book.

68602 on the Steel S.S. K. "Ocean Monarch"

(Number of Visits.....)

Tons

Gross 440.47

Net 168.17

Built at

Selly

By whom built

Cochrane & Sons Ltd.

Yard No.

1165

When built

1936.8.

Owners

Ocean Steam Fishing Co. Ltd.

Port belonging to

Hull.

Electric Light Installation fitted by

Wm Broady & Son

Contract No.

When fitted

1936.

Is the Vessel fitted for carrying Petroleum in bulk

No.

System of Distribution

Low voltage

Pressure of supply for Lighting

100

volts, Heating

volts, Power

volts.

Direct or Alternating Current, Lighting

Direct

Power

If alternating current system, state frequency of periods per second

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off

Yes

Generators, do they comply with the requirements regarding temperature rise

Yes

are they compound wound

Yes

are they over compounded 5 per cent.

Yes

if not compound wound state distance between each generator

Where more than one generator is fitted are they arranged to run in parallel

Yes

is an adjustable regulating resistance fitted in

series with each shunt field

Yes

Have certificates of test results for machines under 100 kw. been submitted and

approved

Makers' Cert. Enclosed

Have machines over 100 kw. been inspected by the Surveyors during manufacture and testing

Are all terminals accessible, clearly marked, and furnished with sockets

Yes

are they so spaced or shielded that they cannot be accidentally earthed,

short circuited, or touched

Yes

Are the lubricating arrangements of the generators as per Rule

Yes

Position of Generators

Starboard side of engine room.

in way of the generators satisfactory

Yes

are they clear of all inflammable material

Yes

if situated near unprotected

woodwork or other combustible material, state distance of same horizontally from or vertically above the generators

are the generators protected from mechanical injury and damage from water, steam or oil

Yes

are their axes of rotation fore and aft

Yes

Earthing, are the bedplates and frames of the generating plant efficiently earthed

Yes

are the prime movers and their respective generators

in metallic contact

Yes

Main Switch Boards, where placed

Beside generator.

If the generators and main switchboard are not placed in the same compartment, is each generator provided with

a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes

Yes

are they protected from mechanical

injury and damage from water, steam or oil

Yes

if situated near unprotected woodwork or other combustible material, state distance of same

horizontally from or vertically above the switchboards

Yes

are they constructed wholly of durable, non-ignitable non-absorbent

materials

Yes

is all insulation of high dielectric strength and of permanently high insulation resistance

Yes

is it of an approved type

Yes

if semi-insulating material is used, are all conducting parts insulated from the slab with mica or micanite or other

non-hygroscopic insulating material, and the slab similarly insulated from its framework

Yes

is the non-hygroscopic insulating material of an approved

type

Yes

and is the frame effectively earthed

Yes

Are the fittings as per Rule regarding:— spacing or shielding of live parts

Yes

Yes

accessibility of all parts

Yes

absence of fuses on back of board

Yes

temperature rise of

omnibus bars

Yes

individual fuses to voltmeter, pilot or earth lamp

Yes

are moving parts of switches alive in the

"off" position

No

are all screws and nuts securing connections effectively locked

Yes

are any fuses fitted on the live side of

switches

No

Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches

D.P. linked switches for generator

A.P. switches for outgoing circuits

Are turbine driven generators fitted with emergency trip switch as per rule

Are cupboards or compartments containing switchboards composed of

fire-resisting material or lined with approved material

Yes

Instruments on main switchboard

One

ammeters

One

voltmeters

Yes

synchronising device for paralleling purposes. For compound machines is the ammeter connected on the opposite pole to equaliser connection

Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system

Earth lamps

Switches, Circuit Breakers and Fusible Cut-outs,


do these comply with the requirements of the Rules

Yes

are the fusible cutouts of an approved type

Yes

have the reversed



Lloyd's Register

Foundation

002038-002050-0152 1/2 2

current protection devices been tested under working conditions ✓ **Joint Boxes, Section and Distribution Boards**, is the construction, protection, insulation, material, and position of these as per rule Yes.

Cables: Single, twin, concentric, or multicore Twin are the cables insulated and protected as per Tables IV, V, X or XI of the Rules Yes.

If the cables are insulated otherwise than as per Rule, are they of an approved type ✓ **Fall of Pressure**, state maximum between bus bars and any point of the installation under maximum load Nil.

area of 0.04 square inch and above provided with soldering sockets Yes **Paper Insulated and Varnished Cambric Insulated Cables.**

If conductors are paper or varnished cambric insulated, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound none, or waterproof insulating tape Cambric **Cable Runs**, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage Yes Are cables in machinery spaces, galleys, laundries, bathrooms and lavatories lead covered or run in conduit Lead covered.

Support and Protection of Cables, state how the cables are supported and protected Armoured cables with 4.1 clips Lead covered cables with brass clips

If cables are run in wood casings, are the casings and caps secured by screws ✓, are the cap screws of brass ✓, are the cables run in separate grooves ✓. If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VIII Yes.

Refrigerated Chambers, are the cables and fittings in accordance with the special requirements none.

Joints in Cables, state if any, and how made, insulated, and protected none.

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands Yes.

Bushes in Beams and Non-watertight Partitions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed Yes state the material of which the bushes are made Lead.

Earthing Connections, state what earthing connections are fitted and their respective sectional areas through earth lamps.

are their connections made as per Rule Yes.

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule Yes **Emergency Supply**, state position and method of control of the emergency supply and how the generator is driven none.

Navigation Lamps, are these separately wired Yes, controlled by separate switch and separate fuses Yes, are the fuses double pole Yes, are the switches and fuses grouped in a position accessible only to the officers on watch Yes has each navigation lamp an automatic indicator as per Rule No **Secondary Batteries**, are they constructed and fitted as per Rule Yes.

Fittings, are all fittings on weather decks, in alokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight Yes are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected none.

are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected none how are the cables led none.

where are the controlling switches situated none.

are all fittings suitably ventilated ✓, are all switches and lampholders constructed wholly of non-ignitable, non-absorbent materials ✓.

Heating and Cooking Appliances, are they constructed and fitted as per Rule ✓, are air heaters constructed and fitted as per Rule ✓.

Searchlight Lamps, No. of ✓, whether fixed or portable ✓, are their fittings as per Rule ✓.

Arc Lamps, other than searchlight lamps, No. of ✓, are their live parts insulated from the frame or case ✓, are their fittings as per Rule ✓.

Motors, are their working parts readily accessible ✓, are the coils self-contained and readily removable for replacement ✓, are the brushes, brush holders, terminals and lubricating arrangements as per Rule ✓, are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material ✓, are they protected from mechanical injury and damage from water, steam or oil ✓ are their axes of rotation fore and aft ✓, if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type ✓, if not of this type, state distance of the combustible material horizontally or vertically above the motors ✓ and ✓.

have machines of over 100 BHP been inspected by the Surveyors during manufacture and testing ✓ **Control Gear and Resistances**, are the generator field and motor speed regulators, starters and controllers constructed and fitted as per Rule ✓ **Lighting Conductors**, where lightning conductors are required, are these fitted as per Rule ✓ **Ships carrying Oil having a Flash Point less than 150° F.** Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings. ✓ are all fuses of the filled cartridge type ✓ are they of an approved type ✓.

If portable lamps for use in dangerous spaces are supplied, are they of a self-contained, battery-fed type approved by the Home Office ✓.

Spare Gear, if the vessel is for open sea service have spares been supplied as per Rule ✓.

PARTICULARS OF GENERATING PLANT.									
DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.		
		Kilowatts.	Volts.	Ampères.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.	
MAIN	One	8	100	80	400.	Steam Engine			
AUXILIARY									
EMERGENCY						Machine No 30263			
ROTARY TRANSFORMER									

GENERATOR, LIGHTING AND HEATING CONDUCTORS.									
DESCRIPTION.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT. AMPERES.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
	No. per Pole.	Total Nominal Area per Pole Sq. Ins.	No.	Diameter.	Circuit.	Rule.			
MAIN GENERATOR	1	0.06	19	0.064	70	83		V.I.R.	LC + armoured.
EQUALISER CONNECTIONS									
AUXILIARY GENERATOR									
EMERGENCY GENERATOR									
ROTARY TRANSFORMER									
ENGINE ROOM	1	0.0029	3	0.036	5	12	20	"	"
BOILER ROOM	1	0.0029	3	0.036	2	12	40	"	"
AUXILIARY SWITCHBOARDS									
ACCOMMODATION	1	0.02214	7	0.064	30	46	150	"	"
Navigation Main	1	0.007	7	0.036	10	24	150	"	"
WIRELESS	1	0.010	7	0.044	10	31	150	"	"
SEARCHLIGHT									
MASTHEAD LIGHT	1	0.0029	3	0.036	2	12	150	"	"
SIDE LIGHTS	1	0.0029	3	0.036	1	12	30	"	LC
COMPASS LIGHTS									
POOP LIGHTS	1	0.0045	7	0.029	10	18	150	"	LC + armoured.
CARGO LIGHTS									
ARC LAMPS									
HEATERS									

MOTOR CONDUCTORS.										
DESCRIPTION.	No. of Motors.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT. AMPERES.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
		No. Per Pole.	Total Nominal Area per Pole Sq. Ins.	No.	Diameter.	In Circuit.	Rule.			
BALLAST PUMP										
MAIN BILGE LINE PUMPS										
GENERAL SERVICE PUMP										
EMERGENCY BILGE PUMP										
SANITARY PUMP										
CIRC. SEA WATER PUMPS										
CIRC. FRESH WATER PUMPS										
AIR COMPRESSOR										
FRESH WATER PUMP										
ENGINE TURNING GEAR										
ENGINE REVERSING GEAR										
LUBRICATING OIL PUMPS										
OIL FUEL TRANSFER PUMP										
WINDLASS										
WINCHES, FORWARD										
WINCHES, AFT										
STEERING GEAR—										
(a) MOTOR GENERATOR										
(b) MAIN MOTOR										
WORKSHOP MOTOR										
VENTILATING FANS										

All Conductors are of annealed copper conforming to British Standard Specification No. 7 (or International Electro-technical Commission Publication No. 28).

The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.

The foregoing is a correct description.

WM BROADY & SON
ENGL
HULL

Electrical Engineers.

Date 12th Aug 1936.

COMPASSES.

Distance between electric generators or motors and standard compass

70 ft

Distance between electric generators or motors and steering compass

The nearest cables to the compasses are as follows:—

A cable carrying 0.5 Ampères to feet from standard compass feet from steering compass.

A cable carrying 0.5 Ampères to feet from standard compass feet from steering compass.

A cable carrying Ampères feet from standard compass feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power Yes

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted Yes.

The maximum deviation due to electric currents was found to be no degrees on any course in the case of the standard compass, and no degrees on any course in the case of the steering compass.

FOR COCHRANE & SONS

J. Cochran

DIRECTOR

Builder's Signature.

Date 17 AUG 1936

Is this installation a duplicate of a previous case Yes If so, state name of vessel

"Kirkella"

General Remarks (State quality of workmanship, opinions as to class, &c.)

The electrical installation of this vessel has been fitted on board under special survey, tried under working conditions and found satisfactory.

Noted

Ym

27.8.36

Total Capacity of Generators 8 Kilowatts.

The amount of Fee ... £ 4 : - :

When applied for,

25 AUG 1936

When received,

26.9.36

Travelling Expenses (if any) £ :

L. Knoffart

Surveyor to Lloyd's Register of Shipping.

Committee's Minute FRI. 28 AUG 1936

Assigned

See Indl 5.6.47130