

With or Without
Disconnected Erections.

Standard & Type
STEEL STEAMER.

Received at London Office OCT. 28, 1918

Date of completion of report
Survey held at

State if Report is also sent on the Machinery of the Vessel

Port of

No.

Date, First Survey

Last Survey

1918

On the (State if Single, Twin, or Triple Screw)

TONNAGE under

Tonnage Deck

Do. between Tonnage Dk.

and 3rd and 4th Dk.

Total under Upper Dk.

Do. of Poop

Do. of Bridge House

Do. of Forecastle

Do. of Houses on Dk.

Do. of excess of Hatchways

Do. above Crown of

Engine Room

Gross Tonnage

Less Crew Space

Less above Crown of

Room

ine Room

igation Spaces

r Tonnage

m Beam

CLASS

Breadth (greatest moulded)

Depth, at middle of length from top of keel to top of
upper deck beams at side

Transverse Number

Length on deck from fore part of stem to after part of
stern post

Longitudinal Number

Depth "d," at middle of length (See Secs. 2 & 13)

Proportions—Depths to Length—Upper Deck Beam at
side to top of keel

Long Bridge Deck
Beam at side to top of keel

Rig

Master

Year of appointment

(1) As Master in service of
owner of present vessel;—191
(2) As Master of this
vessel—191

Built at

When built

Launched

By whom built

Owners

Managers

Residence

Port belonging to

Destined Voyage

If Surveyed while Building, Afloat, or in Dry Dock

Yes

TH on Deck	Feet.	Inches.	BREADTH—	Feet.	Inches.	DEPTH, ACTUAL—	Top of Floors to top of Upper Dk. Beams	Feet.	Inches.	No. of Decks with flat laid
er Rule	331	0	Moulded	46	6	Do. do. do.	Second Dk. Beams	23	23	one
Moulded depth, ft. 33 ins. 0 To Bridge Dk. Round of Upper										11 1/2 ins.
Moulded depth, ft. 25 ins. 6 To Upper Dk. Dk. Beam, Actual										11 1/2 ins.

FRAMING.						PILLARS.					
Inches in Ship.						Inches in Ship.					
Intermediate frames						PILLARS In 'tween Deck, size and spacing					
10 32 32 46 10 32 32 46						2 3/4 49 2 3/4 49					
6 3 48 6 3 48						4 1/2 5 1/2 49 4 1/2 5 1/2 49					
3 1/2 3 1/2 36 3 1/2 3 1/2 36						and Hatch end pillars as					
24 1/2 24 1/2						Profile plan.					
24 1/2 24 1/2						KEELSONS & STRINGERS.					
24 1/2 24 1/2						CENTRE LINE KEELSON, Vertical Plate above					
24 1/2 24 1/2						floors, Through Plate, or Intercostal Plate					
24 1/2 24 1/2						Rider Plate					
24 1/2 24 1/2						Flat Plate Keel Angles					
24 1/2 24 1/2						Horizontal Plates on Floors					
24 1/2 24 1/2						Angles or Bulb Angles					
24 1/2 24 1/2						SIDE KEELSONS, Number					
24 1/2 24 1/2						Angles or Bulb Angles					
24 1/2 24 1/2						Plate above floors, for length					
24 1/2 24 1/2						Intercostal Plate, for length					
24 1/2 24 1/2						Attached to outside Plating with Angle					
24 1/2 24 1/2						BILGE KEELSON, Angles					
24 1/2 24 1/2						Intercostal Plate for length					
24 1/2 24 1/2						Attached to outside Plating with Angle					
24 1/2 24 1/2						SIDE STRINGERS, Number					
24 1/2 24 1/2						Angle					
24 1/2 24 1/2						Intercostal Plate, for length					
24 1/2 24 1/2						Attached to outside plating with Angle					
24 1/2 24 1/2						Upper Deck Stringer Plate, br'dth & thickness					
24 1/2 24 1/2						(clear of Bridge)					
24 1/2 24 1/2						br'dth & thickness					
24 1/2 24 1/2						(in way of Bridge)					
24 1/2 24 1/2						Angle (clear of Bridge)					
24 1/2 24 1/2						Tie Plate at sides of Hatchways					
24 1/2 24 1/2						Deck, * Iron or Steel, for full lng.					
24 1/2 24 1/2						Thickness (clear of Bridge)					
24 1/2 24 1/2						(in way of Bridge)					
24 1/2 24 1/2						Wood Deck. Material & thickness					
24 1/2 24 1/2						Second Deck Stringer Plate, br'dth & thickness					
24 1/2 24 1/2						Angles on ditto, No.					
24 1/2 24 1/2						Tie Plates outside Hatchways					
24 1/2 24 1/2						Deck, * Iron or Steel, for lng.					
24 1/2 24 1/2						Wood Deck. Material & thickness					
24 1/2 24 1/2						Third Deck Stringer Plate, br'dth & thickness					
24 1/2 24 1/2						Angles on ditto, No.					
24 1/2 24 1/2						Tie Plates, outside Hatchways					
24 1/2 24 1/2						Deck, * Material and thickness					
24 1/2 24 1/2						Fourth and Fifth Deck Stringer Plate, breadth & thickness					
24 1/2 24 1/2						Angles on ditto, No.					
24 1/2 24 1/2						Tie Plates outside Hatchways					
24 1/2 24 1/2						Deck, Material & thickness					
24 1/2 24 1/2						Poop Deck Stringer Plate, breadth & thickness					
24 1/2 24 1/2						Angle on ditto					
24 1/2 24 1/2						Tie Plates					
24 1/2 24 1/2						Deck, Material and thickness					
24 1/2 24 1/2						Bridge Deck Stringer Plate, br'dth & thickness					
24 1/2 24 1/2						Angle on ditto					
24 1/2 24 1/2						Tie Plates					
24 1/2 24 1/2						Deck, Material and thickness					
24 1/2 24 1/2						Forecastle Deck Stringer Plate, br'dth & th'kns					
24 1/2 24 1/2						Angle on ditto					
24 1/2 24 1/2						Tie Plates					
24 1/2 24 1/2						Deck, Material and thickness					

* If Iron or Steel Deck, state if whole or part, and if Wood Deck is laid thereon.

002051-002061-0074 1/2

