

$$\begin{array}{r} 34 \cdot 0 \\ 36 \overline{) 6 \cdot 0} \\ \underline{17} \end{array}$$

Thickness of usual wood deck, less stringer
2 1/4" Wood sheathing from alt to Bridge floor

TELEPHONE No. 441.



Ramsden Square,

Barrow-in-Furness, August 20th 1924

LLOYD'S REGISTER
Recd. 21 AUG. 1924

Ans.

LONDON

The Secretary.

LONDON.

Dear Sir,

We are in receipt of your letter of the 19th inst; referring to the freeboard report No:2075, on the S.S."DEARNE", Messrs Vickers Ld: No:611; and in reply beg to state that the 3½" sheathing as shown on the approved plans is fitted on the main deck inside the bridge and in way of the statutory deck line.

It is regretted that this was not made clear on the report.

We are, Dear Sir,

Yours faithfully,

The Surveyors,

Kenneth Inglis

© 2021

Lloyd's Register

002085-002093-0111

Wm

W. B. D. W.
21.8.74

503 9718 8

1976-1977

THE UNIVERSITY OF CHICAGO

1875

• Will Xerox reproduce one to you at this special rate of \$1.00 per copy?

of the last case to the effect that the first is the second

ordered, "UNHAPPY" to me, ETOS:CH Project Publishers and co

no one in contact with anyone who was involved

1904

YOMDOX.

THE POLYMER

Q1104-11162

© 2021

Lloyd's Register
Foundation

Sheet
at