

Do. of space or spaces  
between Tonnage Dk.  
and Upper Dk.

Total

320.15

Gross Tonnage

353.82

11.1.18

Breadth (greatest moulded)

B 24'-10 1/2"

Depth, at middle of length from top of keel to top  
of beam at side of uppermost continuous  
deck. See Sec. 3 (1c)

D 14'-3"

Longitudinal Number (L x D)

= 1005

Launched Feb. 1<sup>st</sup> 1930 Yard

Builders Cochran & Sons

Owners Dinas Steam Tr

5c.7.28.

"How Silanion"

White  
Horse

F.E.

Received by Chief Ship Surveyor

Received from Chief Ship Surveyor

VESSEL'S NAME Sth Se K DINAMAR

Rpt.

Jul

No. 40685

The remarks of the Chief Ship Surveyor are desired on this case for the consideration of the Classing Committee.

("The endorsement to contain a succinct summary of any repairs that have been required and to show the cause or causes of such repairs, and also to bring out clearly any exceptional features in connection with the case, so that the Classing Committee may have all the salient points presented in the endorsement."—Extract from Sub-Committee's Report, 24/5/92.)

1<sup>st</sup> Long

Transverse No.

1995

Depth "d"

12.83

Framing: Table No.

Description

angle frames as approved

2<sup>nd</sup> Longitudinal No.

5477

Proportions

Length

9.82

Depth =

Deck Sheerstrake

as approved

Revised Rules

This vessel appears to have been built in accordance with the Rules and the approved plans, and it is submitted she is eligible to be classed

✠ 100 A.I. (Steel). Steam Trawler.

1 D<sup>1</sup>

B.K 7 1/2", H.B.H., Cem., Lloyds A.C.P.

Q 78', F 19'.

Vessel Lengthened 2.39  
See Mdb. 16529

2.3.30


Angles

DOUBLE BOTTOM.

Solid Floors, thickness and spacing

Are Frame and Reversed Frame  
joggled?

Bracket Floors, breadth and thickness



© 2020

002138-002130-0163

Poop Deck, Angle, [ or [

Spacing

Bridge Deck, Angle, [ or [

Spacing

Lloyd's Register  
Foundation