

Boilers one single ended marine type Working Pressure 160 lbs. Tested by hydraulic pressure to 320 lbs.  
 of Certificate 10523 Can each boiler be worked separately  Area of fire grate in each boiler 76 sq ft  
 ty valves to each boiler  Area of each valve  Pressure to which they are

(Received at London Office \_\_\_\_\_ 19\_\_\_\_)

358 Port Glasgow Date 16th Feby 1910

We request that the Marine boiler numbered as below to be made  
Blackie Thomson's No 399 by Lindsay Burnet & Co  
 be Specially Surveyed while building.

We hereby engage to pay Special Survey Fees as follows, viz. :-

For boilers up to 200 Nominal Horse Power, one shilling per Horse Power. For boilers over 200 Nominal Horse Power, one shilling per Horse Power for the first 200 Horse Power and fourpence per Horse Power above 200. The Nominal Horse Power to be reckoned at 15 square feet of heating surface. No fee to be less than £2 2s.

MEM.—In exceptional cases an additional charge will be made according to the services performed, and in all cases where travelling expenses are incurred by the Surveyors in connexion with the above services, they are to be defrayed by the parties interested.

Boiler No. 1268

This request is made upon the terms of the Rules and Regulations of Lloyd's Register of British and Foreign Shipping, which provide that:—

While the Committee use their best endeavours to ensure that the functions of the Society are properly executed, it is to be understood that neither the Committee nor the Society are under any circumstances whatever to be held responsible for any inaccuracy any report or certificate issued by the Society or its Surveyors, or in any entry in the Register Book or other publication of the Society, or for any error of judgment, default, or negligence of the Surveyors, or other Officers or Agents of the Society.



Signature H. H. Wallace  
 Lloyd's Register of British and Foreign Shipping,  
 71, Fenchurch Street, London. E.C.



Pitch of rivets  Working pressure of shell by rules  Diameter of flue  Material of flue plates   
 stiffened with rings  Distance between rings  Working pressure by rules  End plates: Thickness   
 Are they fitted with

enter the donkey

16-0"

lates welded on

rms 1 7/32 Pi

%

%

and Descrip

Thickness

y the rules 16

to ditto: Side

aterial of sta

ce: Material

tee are

steel TH

rules 219

h of stays 9

steel

rch of Stays

eater be shu

longitudinal