

STERNFRAME.

PLAN No. 2432.

FOR ENCLOSURE TO

Messrs. Lloyd's Register of Shipping,
Gulf

FROM

COCHRANE & SONS, LTD.

SHIPBUILDERS SELBY

DATE 13-7-29.

MATERIAL - FORGED IRON.

TO LLOYDS TESTS. ✓

SCALE. 1" = 1 FT. ✓

HOLES IN STERNFRAME 1" DIA.
5" PITCH. this end and
GUDGEONS ALL $7\frac{1}{8}$ " PROJECTION

FIRST HOLE
TO BE 7"
FROM TOP
OF POST. ✓

FIRST HOLE TO BE
ABOUT 4'-7" DOWN FROM
TOP OF POST. ✓

UPPER AND LOWER
SURFACES OF
GUDGEONS TO BE
SQUARE TO POST
AND TO BE DEAD
LEVEL. ✓

DETAIL OF PINTLES
1/2" STEEL BUSHES.

LAST HOLE TO
BE AS NEAR TO
BOSS AS
PRACTICABLE ✓

BOSS SIDES TO BE
TAPERED TO 5/8"
THICKER EACH SIDE
AT FORE END. ✓

BORE OF BOSS AND FORE AND AFTER
FACES OF BOSS TO BE SQUARE OFF
SHAFT CENTRE LINE.
THE SHAFT DROPS FROM AFT TO FORD
3/4" IN ~~4-1/2"~~ 5'-1" ✓

~~SCARPH NOT
TO BE
DRILLED~~

OVERALL LENGTH OF TAILPIECE. 9'-11" ^v

See 3 class

18-7-29

Cochrane & Sons - Ltd.
Selly-

Stern frame
No. 1064

S.S. "Cape Melville"

HULL REPORT No. 40461



© 2020

Lloyd's Register
Foundation

002165-002173-0052