

in accordance with the printed instructions :-

From centre of disc to top of statutory deck line	22	ft.	7	ins.
From centre of disc to top of statutory deck line	---	ft.	---	ins.

at "C" deck. } For all Seasons.
at awning or part-awning deck . . . }

of class

*see letter
13/6/23.*

It is concluded the thickness of the stronger plate of 'C' Dk at ends, and the extent of the treble riveted seams of shell plating are as approved and not as reported, and that it would appear that the length of the deep tank forward in No. 2 Hold is 46'-11" and not as reported, but the Surveyors should be requested to state if this is so.

They should also be requested to state the length of the Prowade Dk. for inclusion in the Register Book, and whether No 4 Hold can be used for water ballast and oil fuel or oil fuel only.

See Gls: - 9.6.23



© 2020

Lloyd's Register Foundation

002241-002248-0012 2/2

48 INB²
4x56-48
3x56-48
56-48-48
INB²-48
5x23
48-48-48
4x56-48
3x56-48
INB² 40
SITE -
40-48-48
4x56-48
3x56-48
1/2 INB²
40-48-48
4x56-48
3x56-48
6 LENGTH
5756 INL
70-44 OUT
4x56 INB²
x 56 "
IN/EGE EX/
60 TO 38 C
7.53.68-

002241-002248-0013