

FREEBOARD VERIFICATION FORM FOR STEAMERS.

Port Barnow.

When received in London Office

Vessel's Name "Moreton Bay"

Official No. _____

No. in Reg. Book 24815.Port of Registry (For Foreign Vessels) /Iron or Steel Steel State whether Classed by Lloyd's Register 100 R.I. Shellin & with RedName of Owners _____ Date of Verification 15th Sept. 1921.

I have to report that the Freeboard from the centre of disc to the top of the statutory deck line, and the lines in connection therewith, as given below, assigned by the Committee to this vessel, have been correctly marked on the vessel's sides, in accordance with the printed instructions:—

From centre of disc to top of statutory deck line 10 ft. 11 ins.From centre of disc to top of statutory deck line } ✓ ft. ✓ ins.
at awning or part-awning deck . . . }Fresh Water line above centre of disc . . . 8 ins.Indian Summer line above centre of disc . . . 8 ins.Winter line below centre of disc . . . 8 ins.~~Winter North Atlantic line below centre of disc~~ ✓ ins.Distance between the top of statutory deck line on vessel's side and the intersection of the continuation of upper side of Shelter at main, spar or upper dk. 3/4 ins.Steel wood or iron deck with the vessel's side at awning or pt. awning dk. ✓ ins.

NOTE.—It should be clearly shown whether the statutory deck line is set off from a wood or iron deck.

(Sgn.) T. S. Shuttle Surveyor.

(To be filled up in London Office.)

Statement No. _____ Date of Committee's Minute 19. 8. 21.

Particulars for record in Register Book.	{	Moulded Depth . . .	<u>43</u>	ft.	<u>6</u>	ins.
		Freeboard . . .	<u>10</u>	ft.	<u>11</u>	ins.
		Corresponding Draught	<u>33</u>	ft.	<u>0</u>	ins.

Freeboards compared and found correct by _____ Date _____

Is fee paid? _____ Form for Certificate _____

Instructions _____ Date _____

Certificate written _____ Noted for posting _____

When more than 12 passengers are being carried, whilst a British Passenger certificate is in force, the above loadlines shall not apply, & the maximum loadline for all seasons shall be at 3'-0 1/4" below the centre of disc.

Condition of Class

