

Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD.—STEAM SHIPS.

PARTICULARS RELATING TO ALL STEAM SHIPS EITHER FLUSH DECKED, OR WITH TOP GALLANT FORECASTLES, SHORT POOPS AND BRIDGE HOUSES DISCONNECTED, OR WITH TOP GALLANT FORECASTLES HAVING LONG POOPS, OR RAISED QUARTER DECKS CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE.

Port of Survey

Glasgow

Date of Survey

6th July 1925

Name of Surveyor

Ship's Name.

Rilea, S. B. Co

Port of Registry and Nationality.

S. S. No. 396

Official Number.

Gross Tonnage.

Date of Build.

Particulars of Classification.

+ 100 A. I. (Contemplated)

Number in Register Book

Registered dimensions from Ship's Register.

Mtd:- 169.66 x 28.5 x 12.0

Length on Loadline.

Frame Depth Rule

Ceiling Sheer

Peak Tanks

CORRECTED DIMENSIONS.

169.66

Moulded Depth as measured

12'-0"

NOTE.—If the depth is measured when vessel is afloat, the details of measurement should be reported.

Addition for Keel below base line for draught record.....inches.

CORRECTION FOR LENGTH.

Length of Ship on Loadline.....	169.66
Length in Table	144.00
Difference	25.66
Correction for 10ft., Table A.9 Table C. .5
× Difference divided by 10	2.31 (if required.) 1.28
If $\frac{6}{10}$ ths length covered divide by 2	+ 2 1/4" + 1 1/4"

CORRECTION FOR IRON DECK.

Proportion covered, if less than $\frac{1}{10}$ ths length covered

Thickness of usual wood deck, less stringer

upper deck sheathed with 3" wood

CORRECTION FOR ROUND OF BEAM.

Breadth at Gunwale amidships.....	28.5"
Round of Beam	7.5"
Normal round.....	4.125"
Difference	375 ÷ 2 = 187
Proportion of Deck uncovered (Para. 19)	778 : 144 - 1/4"

NOTE.—The round of beam should be reported on the full breadth of vessel at the gunwale.

Co-efficient of fineness.....

.64 given by Builders

Any modification necessary [Para. 4 (a) to (e)]*

Co-efficient as corrected

.68 Lowest in Tables.

Sheer { Stem..... 51 } 81 ÷ 2 = 40.6...Mean
at { Sternpost ... 80 }

Gradual. 30.05 30.0 } 57.5 ÷ 2 = 28.75

Sheer at $\frac{1}{2}$ of the length from { Stem 37.5 } 44.5 ÷ 2 = 22.25...Mean
{ Sternpost 17.0 }Gradual mean Sheer 28.75 || Standard mean Sheer [Table, Para. 18] | 18.37 |
Difference.....	10.38 ÷ 4 =
§ If limited as Para. 18 (f)	18.37 ÷ 4 = 2.29
	- 2 1/4"
Rise in Sheer { At front of bridge house..... ✓
from amidships [Para. 18 (e)] { At after end of forecastle ✓Fall in Sheer { ✓ ÷ 2 = -
Para. 18 (d) }

Length uncovered Correction

ALLOWANCE FOR DECK ERECTIONS:—

Freeboard, Table C.....	0" 3"
Correction for Length, if required (Para. 12, 13, and 14)	+ 1 1/4"
Freeboard by Table A, corrected for shear, and for length, if required (Para. 12, 13, and 14)	1" 10 3/4"
Difference	1" 6 1/2"
Percentage as below.....	8.69%
	1.60

Correction for R. Q. Dk. if engine and boiler openings not covered by bridge house (Para. 11)

Allowance for Deck Erections

Length.	Length allowed.	Height.
Forecastle.....	57.0	38.06
Bridge House		7.0
† Raised Qr. Dk.....		
Poop.....		
Total	38.6	= .227
Length of Ship	169.66	= 1.81 eighths

Corresponding percentage (Para. 11, 12, 13, or 14)

14.48 x 6/10 = 8.69

FREEBOARD recommended amidships from centre of Disc to top of Statutory Deck Line, Wood Deck:—

Fresh Water Line	above centre of Disc
Indian Summer Line	" " "
Winter Line	below " " "
Winter North Atlantic Line	" " "


* If the frames, skin planking, or ceiling are of unusual thickness the breadth of vessel to inside of ceiling should be reported if possible.

† In vessels obtaining an allowance for deck erections under Para. 11 where the sheer drops abaft amidships the height of the R.Q.D. is to be taken from the level of the top of the amidship beam.

§ In flush-decked vessels the total standard mean sheer means the sheer measured at the stem and sternpost. In vessels having poops and forecastles, it means the sheer measured at points distant one-eighth of the vessel's length from stem and sternpost.

+ State dimensions of freeing port area on back of this form.

The Surveyor should state whether the fall in sheer as reported is measured relatively to the straight line of keel or to the water line. If measured relatively to water line the vessel's draft at time of survey, and also the usual load draft forward and aft should be reported.



© 2021

Lloyd's Register Foundation