

Propeller 1 f. Description of longitudinal joint held No. of strengthening rings one Working pressure of furnace by  
bolts 30-10-18 plates: Material Steel Thickness: Sides 9/16 Back 9/16 Top 9/16 Bottom 9/16 Pitch of stays to  
16. 11. 18 Top Inders If stays are fitted with nuts or riveted heads nuts Working pressure by rules 135 Ma

ark on Do. 46005

arks on Do. 219 W.G.M.

L. Burnett  
24 Port Glasgow.

(Received at London Office

19

Date

NOV 13 1919

We request that the - Marine - Boiler numbered as below to be made  
oth Sons No 265 - by us -  
Specially Surveyed while building.

We hereby engage to pay Special Survey Fees as follows, viz.:-

For boilers up to 200 Nominal Horse Power, one shilling per Horse Power. For boilers over 200 Nominal Horse Power, one shilling per Horse Power for the first 200 Horse Power and fourpence per Horse Power above 200. The Nominal Horse Power to be reckoned at 15 square feet of heating surface. No fee to be less than £2 2s.

MEM.—In exceptional cases an additional charge will be made according to the services performed, and in all cases where travelling expenses are incurred by the Surveyors in connexion with the above services, they are to be defrayed by the parties interested.

No. 1646

This request is made upon the terms of the Rules and Regulations of Lloyd's Register of Shipping, provide that:—

While the Committee use their best endeavours to ensure that the functions of the Society are properly executed, it is to be held that neither the Committee nor the Society are under any circumstances whatever to be held responsible for any inaccuracy of report or certificate issued by the Society or its Surveyors, or in any entry in the Register Book or other publication of the Society, or for any error of judgment, default, or negligence of the Surveyors, or other Officers or Agents of the Society.



Signature

FOR LINDSAY BURNET & CO.

Malcolm H. Wallace.

71, Fenchurch Street, London, E.C.

002330-002339-0186

© 2020

Lloyd's Register

The Boiler has now been securely fitted on board  
its safely valves adjusted under steam