

Rpt. 4. *Part* **REPORT ON MACHINERY.** No. *3302A*

Received at London Office **MON. OCT. 6 - 1913**
 Date of writing Report *4 Oct* 19*13* When handed in at Local Office *10* Port of *Dublin*
 No. in Survey held at *Dublin* Date, First Survey *1st Aug* Last Survey *23 Aug 1913*
 Reg. Book. *Dublin* (Number of Visits) *5*
 on the *Steel S.S. "Patricia"* Tons { Gross *780.72*
 Master *Dublin* Built at *Dublin* By whom built *Dublin Dockyard Co Ltd* Net *342.42*
 Engines made at _____ By whom made _____ when made _____
 Boilers made at _____ By whom made _____ when made _____
 Registered Horse Power _____ Owners *M. Murphy & Co Ltd J O Dowd Mgr* Port belonging to *Cardiff*
 Nom. Horse Power as per Section 28 _____ Is Refrigerating Machinery fitted for cargo purposes _____ Is Electric Light fitted _____

ENGINES, &c.—Description of Engines No. of Cylinders _____ No. of Cranks _____
 Dia. of Cylinders _____ Length of Stroke _____ Revs. per minute _____ Dia. of Screw shaft _____ as per rule _____ Material of screw shaft _____
 Is the screw shaft fitted with a continuous liner the whole length of the stern tube _____ Is the after end of the liner made water tight in the propeller boss _____
 If the liner is in more than one length are the joints burned _____ If the liner does not fit tightly at the part between the bearings in the stern tube, is the space charged with a plastic material insoluble in water and non-corrosive _____
 If two liners are fitted, is the shaft lapped or protected between the liners _____ Length of stern bush _____
 Dia. of Tunnel shaft _____ as per rule _____ Dia. of Crank shaft journals _____ as per rule _____ Dia. of Crank pin _____ Size of Crank webs _____ Dia. of thrust shaft under collars _____
 Dia. of screw _____ Pitch of Screw _____ No. of Blades _____ State whether moveable _____ Total surface _____
 No. of Feed pumps _____ Diameter of ditto _____ Stroke _____ Can one be overhauled while the other is at work _____
 No. of Bilge pumps _____ Diameter of ditto _____ Stroke _____ Can one be overhauled while the other is at work _____
 No. of Donkey Engines _____ Sizes of Pumps _____ No. and size of Suctions connected to both Bilge and Donkey pumps _____
 In Engine Room _____ In Holds, &c. *4-2 1/2", 1-5" x 1 1/4" bore ? Donk suction*
 No. of Bilge Injections _____ sizes _____ Connected to condenser, or to circulating pump _____ Is a separate Donkey Suction fitted in Engine room & size _____
 Are all the bilge suction pipes fitted with roses _____ Are the roses in Engine room always accessible _____ Are the sluices on Engine room bulkheads always accessible _____
 Are all connections with the sea direct on the skin of the ship *yes* Are they Valves or Cocks *both*
 Are they fixed sufficiently high on the ship's side to be seen without lifting the stokehold plates _____ Are the Discharge Pipes above or below the deep water line *above*
 Are they each fitted with a Discharge Valve always accessible on the plating of the vessel *yes* Are the Blow Off Cocks fitted with a spigot and brass covering plate *yes*
 What pipes are carried through the bunkers *None* How are they protected _____
 Are all Pipes, Cocks, Valves, and Pumps in connection with the machinery and all boiler mountings accessible at all times _____
 Are the Bilge Suction Pipes, Cocks, and Valves arranged so as to prevent any communication between the sea and the bilges _____
 Dates of examination of completion of fitting of Sea Connections *13 Aug* of Stern Tube *13th Aug* Screw shaft and Propeller *23rd Aug*
 Is the Screw Shaft Tunnel watertight _____ Is it fitted with a watertight door _____ worked from _____

BOILERS, &c.—(Letter for record _____) Manufacturers of Steel _____
 Total Heating Surface of Boilers _____ Is Forced Draft fitted _____ No. and Description of Boilers _____
 Working Pressure _____ Tested by hydraulic pressure to _____ Date of test _____ No. of Certificate _____
 Can each boiler be worked separately _____ Area of fire grate in each boiler _____ No. and Description of Safety Valves to each boiler _____
 Area of each valve _____ Pressure to which they are adjusted _____ Are they fitted with easing gear _____
 Smallest distance between boilers or uptakes and bunkers or woodwork _____ Mean dia. of boilers _____ Length _____ Material of shell plates _____
 Thickness _____ Range of tensile strength _____ Are the shell plates welded or flanged _____ Descrip. of riveting: cir. seams _____
 long. seams _____ Diameter of rivet holes in long. seams _____ Pitch of rivets _____ Lap of plates or width of butt straps _____
 Per centages of strength of longitudinal joint _____ rivets _____ Working pressure of shell by rules _____ Size of manhole in shell _____
 plate _____
 Size of compensating ring _____ No. and Description of Furnaces in each boiler _____ Material _____ Outside diameter _____
 Length of plain part _____ top _____ Thickness of plates _____ crown _____ Description of longitudinal joint _____ No. of strengthening rings _____
 bottom _____
 Working pressure of furnace by the rules _____ Combustion chamber plates: Material _____ Thickness: Sides _____ Back _____ Top _____ Bottom _____
 Pitch of stays to ditto: Sides _____ Back _____ Top _____ If stays are fitted with nuts or riveted heads _____ Working pressure by rules _____
 Material of stays _____ Diameter at smallest part _____ Area supported by each stay _____ Working pressure by rules _____ End plates in steam space: _____
 Material _____ Thickness _____ Pitch of stays _____ How are stays secured _____ Working pressure by rules _____ Material of stays _____
 Diameter at smallest part _____ Area supported by each stay _____ Working pressure by rules _____ Material of Front plates at bottom _____
 Thickness _____ Material of Lower back plate _____ Thickness _____ Greatest pitch of stays _____ Working pressure of plate by rules _____
 Diameter of tubes _____ Pitch of tubes _____ Material of tube plates _____ Thickness: Front _____ Back _____ Mean pitch of stays _____
 Pitch across wide water spaces _____ Working pressures by rules _____ Girders to Chamber tops: Material _____ Depth and thickness of girder at centre _____ Length as per rule _____ Distance apart _____ Number and pitch of stays in each _____
 Working pressure by rules _____ Superheater or Steam chest; how connected to boiler _____ Can the superheater be shut off and the boiler worked separately _____
 Diameter _____ Length _____ Thickness of shell plates _____ Material _____ Description of longitudinal joint _____ Diam. of rivet holes _____ Pitch of rivets _____ Working pressure of shell by rules _____ Diameter of flue _____ Material of flue plates _____ Thickness _____
 If stiffened with rings _____ Distance between rings _____ Working pressure by rules _____ End plates: Thickness _____ How stayed _____
 Working pressure of end plates _____ Area of safety valves to superheater _____ Are they fitted with easing gear _____

VERTICAL DONKEY BOILER— *Manufacturers of Steel*

No. _____ Description _____

Made at _____ By whom made _____ When made _____ Where fixed _____

Working pressure tested by hydraulic pressure to _____ Date of test _____ No. of Certificate _____ Fire grate area _____ Description of Safety Valves _____

No. of Safety Valves _____ Area of each _____ Pressure to which they are adjusted _____ Date of adjustment _____

If fitted with easing gear _____ If steam from main boilers can enter the donkey boiler _____ Dia. of donkey boiler _____ Length _____

Material of shell plates _____ Thickness _____ Range of tensile strength _____ Descrip. of riveting long. seams _____

Dia. of rivet holes _____ Whether punched or drilled _____ Pitch of rivets _____ Lap of plating _____ Per centage of strength of joint _____ Rivets _____ Plates _____

Working pressure of shell by rules _____ Thickness of shell crown plates _____ Radius of do. _____ No. of stays to do. _____ Dia. of stays _____

Diameter of furnace Top _____ Bottom _____ Length of furnace _____ Thickness of furnace plates _____ Description of joint _____

Working pressure of furnace by rules _____ Thickness of furnace crown plates _____ Radius of do. _____ Stayed by _____

Diameter of uptake _____ Thickness of uptake plates _____ Thickness of water tubes _____ Dates of survey _____

SPARE GEAR. State the articles supplied :—

The foregoing is a correct description,

Manufacturer.

Dates of Survey while building { During progress of work in shops - - }
 { During erection on board vessel - - - }
 Total No. of visits _____

Is the approved plan of main boiler forwarded herewith

“ “ “ donkey “ “ “

Dates of Examination of principal parts—Cylinders _____ Slides _____ Covers _____ Pistons _____ Rods _____

Connecting rods _____ Crank shaft _____ Thrust shaft _____ Tunnel shafts _____ Screw shaft _____ Propeller _____

Stern tube _____ Steam pipes tested _____ Engine and boiler seatings _____ Engines holding down bolts _____

Completion of pumping arrangements _____ Boilers fixed _____ Engines tried under steam _____

Main boiler safety valves adjusted _____ Thickness of adjusting washers _____

Material of Crank shaft _____ Identification Mark on Do. _____ Material of Thrust shaft _____ Identification Mark on Do. _____

Material of Tunnel shafts _____ Identification Marks on Do. _____ Material of Screw shafts _____ Identification Marks on Do. _____

Material of Steam Pipes _____ Test pressure _____

General Remarks (State quality of workmanship, opinions as to class, &c.)

The Stern post has been bored, and the tube fitted, also the sea cocks. The screw, screw shaft & thrust shafts are in place. The vessel was towed from this port to Glasgow for completion of Machinery. Glasgow Surveyors notified.

Certificate (if required) to be sent to _____

The amount of Entry Fee .. £	:	:	When applied for,
Special £	:	:19.....
Donkey Boiler Fee £	:	:	When received,
Travelling Expenses (if any) £	:	:19.....

Committee's Minute

GLASGOW 18 NOV. 1913

Macmillan
 Ship & Engineer Surveyor to Lloyd's Register of British & Foreign Shipping.
 at Dublin

FRI. NOV. 21. 1913

Assigned See minute on G.L. Rpt. No. 33349



© 2020

Lloyd's Register Foundation