

REPORT ON ELECTRICAL EQUIPMENT.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

Received at London Office.....

Date of writing Report 7-11-42 When handed in at Local Office..... Port of Middlesbrough

No. in Survey held at Haveron Hill-on-Sea Date, First Survey 22-9-42 Last Survey 5-11-42
Reg. Book. (Number of Visits.....)

86313 on the S/S. "EMPIRE NUGGET" Tons {Gross.....
Net.....

Built at Haveron Hill-on-Sea By whom built Furness Shipbuilding Co. LTD. Yard No. 349 When built 1942

Owners The Ministry of War Transport Port belonging to Middlesbrough

Electrical Installation fitted by Furness Shipbuilding Co. Ltd Contract No. 349 When fitted 1942

Is vessel fitted for carrying Petroleum in bulk Yes Is vessel equipped with D.F. Yes E.S.D. Yes Gy.C. No Sub.Sig. No
Emergency only.

Have plans been submitted and approved Yes System of Distribution Two Wires insulated Voltage of supply for Lighting 110

Heating — Power 110 Direct or Alternating Current, Lighting Yes Power Yes If Alternating Current state periodicity — Prime Movers,

has the governing been tested and found as per Rule when full load is suddenly thrown on and off Yes Are turbine emergency governors fitted with a

trip switch as per Rule — Generators, are they compound wound Yes, are they level compounded under working conditions Yes,

if not compound wound state distance between generators — and from switchboard —. Where more than one generator is fitted are they

arranged to run in parallel No, are shunt field regulators provided Yes. Is the compound winding connected to the negative or positive pole

positive Have machines over 100 kw. been inspected by the Surveyors during manufacture and testing — Have certificates of

test for machines under 100 kw. been supplied Yes and the results found as per rule Yes Are the lubricating arrangements and the construction

of the generators as per rule Yes Position of Generators Engine room on raised platform aft of main

engine, is the ventilation in way of generators satisfactory Yes are they clear of inflammable material Yes, if situated

near unprotected combustible material state distance from same horizontally — and vertically —, are the generators protected from mechanical

injury and damage from water, steam and oil Yes, are the bedplates and frames earthed Yes and the prime movers and generators in metallic

contact Yes Switchboards, where are main switchboards placed on raised platform adjacent to generators

are they in accessible positions, free from inflammable gases and acid fumes Yes, are they protected from mechanical injury and damage from water, steam

and oil Yes, if situated near unprotected combustible material state distance from same horizontally — and vertically —, what insulation

material is used for the panels "Sindanyo", if of synthetic insulating material is it an Approved Type Yes, if of

semi-insulating material (slate or marble) are all conducting parts insulated therefrom as per Rule —. Is the frame effectually earthed Yes

Is the construction as per Rule Yes, including accessibility of parts Yes, absence of fuses on the back of the board Yes, individual fuses

to pilot and earth lamps, voltmeters, etc. Yes locking of screws and nuts Yes, labelling of apparatus and fuses Yes, fuses on the "dead"

side of switches Yes Description of Main Switchgear for each generator and arrangement of ~~main~~ switches a double pole

single throw quick-break knife switch and double-pole cartridge fuse.

and for each outgoing circuit a double-pole double-throw quick-break knife switch and double-pole

cartridge fuse.

Are compartments containing switchboards composed of fire-resisting material or lined as per Rule Yes Instruments on main switchboard Two

ammeters Two voltmeters — synchronising devices. For compound machines in parallel is the ammeter connected on the pole opposite to the

equaliser connection — Earth Testing, state means provided E. Lamps Coupled to E Through All Fuses

Switches, Circuit Breakers and Fuses, are they as per Rule Yes, are the fuses an approved type Yes, are all fuses labelled as

per Rule Yes. If circuit breakers are provided for the generators, at what overload current did they open when tested —, are the reversed current


protection devices connected on the pole opposite to the equaliser connection —, have they been tested under working conditions, and at what current

did they operate — Joint Boxes, Section Boards and Distribution Boards, is the construction and position as per Rule Yes

Cables, are they insulated and protected as per the appropriate Tables of the Rules Yes, if otherwise than as per Rule are they of an approved type —,

state maximum fall of pressure between bus bars and any point under maximum load less than 4.4 V. are the ends of all cables having a sectional area of 0.04

square inch and above provided with soldering sockets Yes Are paper insulated and varnished cambric insulated cables sealed at the ends Yes



002401-002409-0160 1/2

with insulating compound or waterproof insulating tape. Yes. Are all the cable runs in accessible positions, not exposed to drip or accumulation of water or oil, high temperatures or risk of mechanical damage. Yes, are cables laid under machines or floorplates. Yes, if so, are they adequately protected. Are cables in machinery spaces, galleys, laundries, etc., lead covered. Yes or run in conduit. State how the cables are supported and protected. All main cables carried insulated: In machinery spaces lead covered, returned and braided cables clipped to perforated metal tray on surface, along deck runways, clipped to steel framing: In accommodation V.C.L.C.B. cables clipped to wooden grounds & protected as necessary. All outgoing circuits for lighting V.I.R. insulated. Are all lead sheaths, armouring and conduits effectively bonded and earthed. Yes. Refrigerated chambers, are the cables and fittings as per Rule.

Are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands. Yes, where unarmoured cables pass through beams, etc., are the holes effectively bushed. Yes and with what material. Lead. Alternative Lighting, are the groups of lights in the engine and boiler rooms arranged as per Rule. Yes. Emergency Supply, state position.

Navigation Lamps, are they separately wired. Yes controlled by separate double pole switches. Yes and fuses. Yes. Are the switches and fuses in a position accessible only to the officers on watch. Yes, is an automatic indicator fitted. Yes. Secondary Batteries, are they constructed and fitted as per Rule. Yes, are they adequately ventilated. what is the battery capacity in ampere hours.

Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, weatherproof. Yes. Are fittings installed where readily combustible materials or inflammable or explosive dust or gases are likely to be present. Yes, if so, how are they protected. In lower deck centreline, D.T.S. "disprism" flameproof lighting fittings as approved, installed and where are the controlling switches fitted. outside dangerous spaces, are all fittings suitably ventilated. Yes, are all fittings and accessories constructed and installed as per Rule. Yes. Searchlight Lamps, No. of none fitted, whether fixed or portable. none fitted, are their fittings as per Rule. Heating and Cooking, is the general construction as per Rule.

are the frames effectually earthed. Yes, are heaters in the accommodation of the convection type. Yes. Motors, are all motors constructed and installed as per Rule. Yes and placed in well-ventilated compartments in which inflammable gases cannot accumulate and free from damage from water, steam and oil. Yes, if situated near unprotected combustible material state minimum distance from same horizontally. Yes and vertically. Yes. Are motors coupled to oil fuel transfer and unit pressure pumps capable of being stopped from a position accessible in the event of fire in the pump compartment. none fitted

Have motors of 100 BHP and over been inspected by the Surveyors during manufacture and testing. none fitted. Have certificates of test for motors under 100 BHP intended for essential services been supplied and the results found as per Rule. none fitted. Control Gear and Resistances, are they constructed and fitted as per Rule. Yes. Lightning Conductors, where required are they fitted as per Rule. none fitted. Ships carrying Oil having a Flash Point less than 150° F. Have all the special requirements of the Rules for such ships been complied with. Yes, are all fuses of the cartridge type. Yes are they of an approved type. Yes. Are the fittings for pump rooms, 'tween deck spaces, etc., in accordance with the special requirements for such ships. Yes. Are the cables lead covered as per Rule. Yes. Spare Gear, if the vessel is for open sea service have spares been provided as per Rule. Yes, are they suitably stored in dry situations. Yes. Insulation Tests, has the insulation resistance of all circuits and apparatus been tested and found satisfactory. Yes.

PARTICULARS OF GENERATING PLANT.

DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.	
		Kilowatts.	Volts.	Ampères.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.
MAIN	2	25	110	227	685	Single Cylinder Vertical Steam Engines		
EMERGENCY								
ROTARY TRANSFORMER								

GENERATOR CABLES.

DESCRIPTION.	KILOWATTS.	CONDUCTORS.		MAXIMUM CURRENT IN AMPERES.		APPROX. LENGTH (lead plus return feet).	INSULATED WITH.	HOW PROTECTED.
		No. in Parallel Per Pole.	Sectional Area or No. and Dia. of Strands. Sq. ins. or sq. mm.	In the Circuit.	Rule.			
MAIN GENERATOR	Port 25	1	37/072	227	246	40	V.C.	L.C.A.T.B.
"	Starboard 25	1	37/072	227	246	40	V.C.	L.C.A.T.B.
EMERGENCY GENERATOR								
ROTARY TRANSFORMER: MOTOR								
"	GENERATOR							

MAIN DISTRIBUTION CABLES.

DESCRIPTION.	CONDUCTORS.		MAXIMUM CURRENT IN AMPERES.		APPROX. LENGTH (lead plus return feet).	INSULATED WITH.	HOW PROTECTED.
	No. in Parallel Per Pole.	Sectional Area or No. and Dia. of Strands. Sq. ins. or sq. mm.	In the Circuit.	Rule.			
AUX. SWITCHBOARDS AND SECTION BOARDS							
Sub-switchboard (Main Feed)	1	37/072	39	246	712	V.C.	L.C.A.T.B.
" (Emergency Feed)	1	37/072	39	246	692	"	"
Off. Lighting Sub. Board	1	19/052	24	104	116	"	"

LIGHTING AND HEATING, ETC., CABLES.

WIRELESS (off sub-switchboard)	1	7/044	-	42	116	V.C.	L.C.T.B.
NAVIGATION LIGHTS	1	7/044	5	42	116	"	"
LIGHTING AND HEATING	(Auxiliary feed with D.P.D.T. switch fuses to Main Lighting Board)						
Engine Room Lighting D.B.	1	7/044	31	42	30	V.C.	L.C.A.T.B.
Forecastle Lighting D.B.	1	7/044	5	42	384	"	"
Main Hold D.B.	Distribution fuses mounted on sub-switchboard						
Mid-Portables D.B.							
Forecastle Room Lighting D.B.							
Officer's Lighting D.B. (off sub-switchboard)	1	7/044	18	42	52	V.C.	L.C.T.B.
Engineers Lighting D.B. (off aft Bd.)	1	7/044	10.5	42	100	"	L.C.A.T.B.
Off. Portables	1	7/029	1.6	15	98	V.I.R.	"
Emergency W.T.	1	7/044	-	42	280	V.C.	"
Engineers Lighting D.B.	1	7/044	12	42	16	V.C.	"

MOTOR CABLES.

ALL IMPORTANT MOTORS TO BE ENUMERATED.	No.	B.H.P.	CONDUCTORS.		MAXIMUM CURRENT IN AMPERES.		APPROX. LENGTH (lead plus return feet).	INSULATED WITH.	HOW PROTECTED.
			No. in Parallel Per Pole.	Sectional Area or No. and Dia. of Strands. Sq. ins. or sq. mm.	In the Circuit.	Rule.			
Off. Water Vent Fan.	1	4.75	1	7/044	32	42	132	V.C.	L.C.A.T.B.
Wind " " "	1	3.5	1	7/044	20	42	268	"	L.C.T.B.

The Electrical Equipment is installed in accordance with the approved plans and the requirements of the Rules.

All Insulated Conductors are guaranteed to have been tested at the maker's works as specified in the Rules.

The foregoing is a correct description. **FURNESS SHIPBUILDING Co. LIMITED**

P. P. Brown

Electrical Engineer

Date

19th Nov 43

COMPASSES.

Minimum distance between electric generators or motors and standard compass *280'*

Minimum distance between electric generators or motors and steering compass *276'*

The nearest cables to the compasses are as follows:—

A cable carrying *.14* Ampères *7* feet from standard compass *in the* feet from steering compass.

A cable carrying *.14* Ampères *in the* feet from standard compass *7* feet from steering compass.

A cable carrying Ampères feet from standard compass feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power *yes*

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted *yes*

The maximum deviation due to electric currents was found to be *nil* degrees on *every* course in the case of the

standard compass, and *nil* degrees on *every* course in the case of the steering compass.

J. J. Brown

Builder's Signature.

Date

Nov 19 1942

Is this installation a duplicate of a previous case *yes* If so, state name of vessel *S/S "Empire Dickens"*

Plans. Are approved plans forwarded herewith *no* If not, state date of approval *D. 28-9-41; S. 26-9-41*

Certificates. Are certificates of test for ~~motors engaged on essential services~~ and generators forwarded herewith *yes*

General Remarks (State quality of workmanship, whether insulation tests, etc., have been made, opinions as to class, etc.)

The electrical equipment of this vessel has been installed under special survey in accordance with the approved plans and the Ministry of Shipping Specification and amendments thereto. The materials used are of good quality and design and the workmanship is good. Upon completion the equipment was operated under test with satisfactory results and the insulation resistance of each circuit was measured and found good. This equipment is in my opinion suitable for a classed vessel.

*Noted
LJ
26/11/42*

Total Capacity of Generators *(2x25) 50* Kilowatts.

The amount of Fee ... *£27. 10. 0:* When applied for, *23/11/1942.*
Specification *6. 17. 6.*
Travelling Expenses (if any) £ : : When received, *.....19.....*

B. D. [Signature]
Surveyor to Lloyd's Register of Shipping.

FRI. 27 NOV 1942

Committee's Minute

Assigned

See Indb F.O. 17375

5m. 4. 8. Transfer. (MADE AND PRINTED IN ENGLAND.) (The Surveyors are requested not to write on or below the space for Committee's Minutes.)



© 2020

Lloyd's Register Foundation