

Do all the Frames extend to the top height in the Poop? *yes* Raised Quarter Deck? *no* Bridge House? *alt frames* Forecastle? *yes*
 To what height do the Reverse Frames extend? *none*
 Has the Poop or Raised Quarter Deck an efficient Iron Bulkhead at the fore end? *yes*
 Give particulars of the means for closing the openings in Bulkhead *no openings*
 Is the Poop or Raised Quarter Deck connected with the Bridge House? *no* Has the Bridge House an efficient Bulkhead at the fore end? *yes*
 Give particulars of the means for closing the openings in Bulkhead *W.T. Hinged Steel doors*
 What is the thickness of the Bridge Front plating? *3/8* and Coaming plate? *coaming & plating combined*
 Give scantlings and spacing of the Stiffeners *1/2" x 3" Bulk angles spaced 30"*
 Are bracket plates fitted at each end of the Stiffeners? *lugged top bottom* Are hor'l. brackets fitted connecting Bridge Bulk'd. with Bulwarks? *yes*
 Has the Bridge House an efficient Iron Bulkhead at the after end? *yes*
 How are the openings closed? *with 3" shifting boards extending half height, fixed in channels riveted to bulkheads*
 Is the Forecastle at least as high as the main or top-gallant rail? *yes* Has the Forecastle an efficient Iron or Wood Bulk'd. at after end? *yes*
 Are the Engine and Boiler openings covered by a Bridge, Poop, Raised Quarter Deck, or enclosed by a Strong Iron or Steel Deckhouse? *yes*
 If the openings are not so protected are the exposed parts of the Casings efficiently constructed?
 Give thickness of plating; scantlings and spacing of Stiffeners
 What is the height of the exposed Casings? *9' above Bridge deck beams* Are suitable means provided for closing all openings in them in bad weather? *yes*
 Are the Weather Deck Hatchways efficiently constructed and at least equal to the requirements of Section 28 of the Rules for 1904-5? Give particulars below:—


Position and Size.		No 1 14'-0" x 15'-0"		No 2 12'-0" x 15'-0"		No 3 16'-0" x 15'-0"		No 4 14'-0" x 15'-0"		Ship.	
Item.		Ship.	Rule.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.	Ship.	
COAMING.	Height above top of DECK	30"		30"		30"		30"			
	Sides.....	50		50		50		50			
	Ends.....	44		44		44		44			
SHIFTING BEAMS OR WEB PLATES.	Number	2		3		2		2			
	Section and Scantlings	12 13 x 31		14 x 34		12 13 x 31		12 13 x 31			
	Material	4 angle 3 1/2 x 40 steel		4 angle 3 1/2 x 40 steel		4 angle 3 1/2 x 40 steel		4 angle 3 1/2 x 40 steel			
* FORE AND AFTERS.	Number										
	Section and Scantlings										
	Material										
HATCHES Thickness		3		3		3		3			
Remarks.....											

* The depth of Fore and Afters should be stated from the underside of the hatches in all cases.

(If the sill of the lowest side scuttle will be less than 6 inches above the Indian Summer Load Line if assigned under the tables, state vertical distance from top of deck at side amidships to lower edge of lowest side scuttle.)

The following information is to be given in all Cases of vessels dealt with under Paras. 11, 12 (under 15 feet Moulded depth) and under Shelter Deck Rules.


What is the thickness of the Bridge Sheerstrake? *yes* Strake between Main and Bridge Sheerstrakes?
 Delete the words { The Crew are, are not, berthed in the bridge house.
 that do not apply { The arrangements to enable them to get backwards and forwards from their quarters are, are not satisfactory.
 Length of Bulwarks in well *3rd well 58'-0" after well 60'-0"*
 Area of Freeing Ports required by Para. 11 (e) each side of vessel = *12.3* Sq. ft. *after well 12.5*
 Ft. Tenths. Ft. Tenths. No. } Freeing Ports (each side of vessel) = *21.0* Sq. ft.
3rd well 4.0 x 1.75 x 3
aft. well 4.0 x 1.75 x 3
 Total deficiency or excess = *8.7* Sq. ft. *8.5*



Show hereon line of Floors or Tank Top with position of any Breaks in same; also height of Peak Tank tops, &c., &c.

State any special features in the construction of the Vessel *none*
 Builder's name and yard number *Messrs Hawthorn Leslie & Co. No 569*
 Names of sister vessels *none*
 Owners *Union Steamship Co of New Zealand*
 Address

Fee £ 5 : 0 : 0 Received by me *See F.B. Report.*



© 2020
 Lloyd's Register
 Foundation

W. HAWTHORN, L.
 ENGINEERS & SHIPBUILDERS
 TELEGRAPHIC ADDRESS: "LESLIE", NEWCASTLE
 TELEPHONE: 126, HEBBURN
 127, DO
 128, DO
 129, DO
 LONDON OFFICE: 54, VICTORIA STREET, WEST