

# Lloyd's Register of Shipping.

## SURVEYS FOR FREEBOARD.

(COMPUTATION FOR STEAMER, SAILING SHIP, TANKER.)

Ship's Name <b>BERGÖ</b>	Official Number	Nationality and Port of Registry <b>FINNISH MARIEHAMN</b>	Gross Tonnage <b>599 626</b>	Date of Build <b>1950</b>	Port of Survey <b>GRONINGEN</b>
Moulded Dimensions: Length <b>50635</b> Breadth <b>8850</b> Depth <b>4050</b> C.o.podd.st.					Date of Survey <b>2-1950</b>
Moulded displacement at moulded draught = 85 per cent. of moulded depth <b>1108 m<sup>3</sup></b>					Surveyor's Signature <i>[Signature]</i>
Coefficient of fineness for use with Tables <b>.718</b>					Particulars of Classification <input checked="" type="checkbox"/> <b>100 A1</b> <b>CONTEMPLATED</b>

**DEPTH FOR FREEBOARD (D).**  
Moulded depth **4050**  
Stringer plate **9**  
Sheathing on exposed deck  
 $T \left( \frac{L-S}{L} \right) =$   
R.Q.D. 50 u.u.  
Depth for Freeboard (D) = **4059**

**DEPTH CORRECTION.**  
(a) Where D is greater than Table depth  
(D - Table depth) R = **8.33(4059-3376) = +73 -/-**  
**683**  
(b) Where D is less than Table depth (if allowed)  
(Table depth - D) R =  
If restricted by superstructures

**ROUND OF BEAM CORRECTION.**  
Moulded Breadth (B) **8850 mm**  
Standard Round of Beam =  $\frac{B \times 49}{50} =$  **177**  
Ship's Round of Beam = **200**  
Difference **23**  
Restricted to  
Correction =  $\frac{\text{Diff}^2}{4} \times \left( 1 - \frac{S_1}{L} \right) = \frac{23^2}{4} \times 0.665 = -4 -/-$

**DEDUCTION FOR SUPERSTRUCTURES.**

	Mean Covered Length (S)	Equivalent Enclosed Length (S <sub>1</sub> )	Height	Height Correction	Effective Length (E)
Poop enclosed	—	—	—	—	—
" overhang	—	—	—	—	—
R.Q.D. enclosed	<b>11975</b>	<b>11975</b>	<b>1600</b>	<b>✓</b>	<b>11975</b>
" overhang	—	—	—	—	—
Bridge enclosed	—	—	—	—	—
" overhang aft	—	—	—	—	—
" overhang forward	—	—	—	—	—
Fore enclosed	<b>7310</b>	<b>7310</b>	<b>2150</b>	<b>✓</b>	<b>7310</b>
" overhang	<b>260</b>	<b>130</b>	<b>2150</b>	<b>✓</b>	<b>130</b>
Trunk aft	—	—	—	—	—
" forward	—	—	—	—	—
Tonnage opening aft	—	—	—	—	—
" forward	—	—	—	—	—
Total	<b>19545</b>	<b>19415</b>			<b>19415</b>

Standard Height of Superstructure **1830 -/-**  
" " R.Q.D. **1047 -/-**  
Deduction for complete superstructure **575 -/-**  
Percentage covered  $\frac{S}{L} =$  **38.60**  
" "  $\frac{S_1}{L} =$  **38.35**  
" "  $\frac{E}{L} =$  **22.09**  
Percentage from Table, Line A. **22.09**  
(corrected for absence of forecastle (if required)) **✓**  
Percentage from Table, Line B. **✓**  
(corrected for absence of forecastle (if required)) **✓**  
Interpolation for bridge less than 2L (if required) **✓**  
Deduction = **575 × 22.09 = -127 -/-**

**SHEER CORRECTION.**

Station	Standard Ordinate	S	M	Product	Actual Ordinate	Effective Ordinate	S	M	Product
A.P.	<b>676</b>	<b>1</b>	<b>676</b>	<b>724</b>	<b>724</b>	<b>1</b>	<b>724</b>	<b>1</b>	<b>724</b>
$\frac{1}{2}L$ from A.P.	<b>300</b>	<b>4</b>	<b>1200</b>	<b>285</b>	<b>285</b>	<b>4</b>	<b>1140</b>	<b>4</b>	<b>1140</b>
$\frac{2}{3}L$ "	<b>75</b>	<b>2</b>	<b>150</b>	<b>64</b>	<b>64</b>	<b>2</b>	<b>128</b>	<b>2</b>	<b>128</b>
Amidships	<b>✓</b>	<b>4</b>	<b>1</b>	<b>0</b>	<b>✓</b>	<b>4</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>
$\frac{2}{3}L$ from F.P.	<b>150</b>	<b>2</b>	<b>300</b>	<b>162</b>	<b>162</b>	<b>2</b>	<b>324</b>	<b>2</b>	<b>324</b>
$\frac{1}{2}L$ "	<b>601</b>	<b>4</b>	<b>2404</b>	<b>575</b>	<b>575</b>	<b>4</b>	<b>2300</b>	<b>4</b>	<b>2300</b>
F.P.	<b>1352</b>	<b>1</b>	<b>1352</b>	<b>1420</b>	<b>1420</b>	<b>1</b>	<b>1420</b>	<b>1</b>	<b>1420</b>
Total			<b>6082</b>				<b>6036</b>		

Correction =  $\frac{\text{Difference between sums of products}}{18} = \frac{46}{18} = +2.55$   
If limited on account of midship superstructure.

Mean actual sheer aft = **Deficient 7.75**  
Mean standard sheer aft =

Mean actual sheer forward = **Even**  
Mean standard sheer forward =

Length of enclosed superstructure forward of amidships = **Deficient Sheers**  
" " aft of " =

**Deduction for Tropical Freeboard.****Addition for Winter and Winter North Atlantic Freeboard.**

Depth to Freeboard Deck = **4059**  
Summer freeboard = **407**  
Moulded draught (d) = **3652**

**Deduction for Tropical freeboard and addition for**

Winter freeboard =  $\frac{d}{48}$  inches = **76 -/-**

Addition for Winter North Atlantic Freeboard (if required) = **76 + 51 = 127 -/-**

**Deduction for Fresh Water.**

Displacement in salt water at summer load water line **1108 m<sup>3</sup>**  
 $\Delta =$  **3.65 m<sup>3</sup>** per **6m** immersion at summer load water line  
 $T = \frac{\Delta}{40} = \frac{3.65}{40} = 0.091$

Deduction =  $\frac{\Delta}{40 T}$  inches = **82 -/-**

**TABULAR FREEBOARD corrected for Flush Deck (if required)**

Correction for coefficient = **1.398**  
**68 + 718 = 1.36**

Depth Correction **73**  
Deduction for superstructures **127**  
Sheer correction **4**  
Round of Beam correction **✓**  
Correction for Thickness of Deck amidships **✓**  
Other corrections, scantlings, etc. **✓**

**451**  
**464**  
**13.250**  
**-57**  
Summer Freeboard = **407**

**SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, Wood, Steel, Deck:—**

Tropical Fresh Water Line above Centre of Disc **158 -/-**  
Fresh Water Line " **82 -/-**  
Tropical Line " **76 -/-**  
Winter Line below " **76 -/-**  
Winter North Atlantic Line " **127 -/-**

Tropical Fresh Water Freeboard **249**  
Fresh Water " **325**  
Tropical " **331**  
Winter " **483**  
Winter North Atlantic " **534**



BERGÖ.

A new form should be prepared if any alterations that affect the freeboard have been made. If no such alterations have been made, the Surveyor should endorse the form on this side with his signature and the date.

Trade of ship OCEAN TRADE

Names of sister ships M.V. "YVONNE" (yard no. 376)

Builder's name and yard number BODEWES SCHEEPSWERVEN, MARTENSHOEK, YARD NO 377

Owners Mr. G. ERIKSON, MARIEHAMN, FINLAND.

Fee £ 195.-



© 2020

Lloyd's Register  
Foundation