

Chulmleigh 35534
 Goodleigh 35771
 Wimbleigh 36235

Index. No. 35080.
 (For London Office only).

Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD.

(COMPUTATION FOR STEAMER, ~~SAILING SHIP~~, TANKER.)

Ship's Name NORTHLEIGH	Official Number 165573	Nationality and Port of Registry British, London	Gross Tonnage	Date of Build 1937	Port of Survey
Moulded Dimensions: Length 424'-11 1/2" Breadth 56.0 Depth 37'-10"					Date of Survey 24.4.41
Moulded displacement at moulded draught = 85 per cent. of moulded depth					Surveyor's Signature
Coefficient of fineness for use with Tables 0.792 (estimated)					Particulars of Classification + 100 A1 with freeboard

Depth for Freeboard (D).	Depth correction.	Round of Beam correction.
Moulded depth ... 37.83	(a) Where D is greater than Table depth (D - Table depth) R = (37.83 - 28.33) x 3 = +18.65"	Moulded Breadth (B) 56.00'
Stringer plate ... 6.2"	(b) Where D is less than Table depth (if allowed) (Table depth - D) R = 9.55'	Standard Round of Beam = $\frac{B \times 12}{50} = 13.44"$
Sheathing on exposed deck $T \left(\frac{L-S}{L} \right) =$	If restricted by superstructures	Ship's Round of Beam = 13.00"
Depth for Freeboard (D) = 37.88		Difference 0.44"
		Restricted to
		Correction = $\frac{\text{Diff}}{4} \times \left(1 - \frac{S_1}{L} \right) = \frac{.44}{4} \times .9218 = +0.10"$

DEDUCTION FOR SUPERSTRUCTURES.

	Mean Covered Length (S)	Equivalent Enclosed Length (S ₁)	Height	Height Correction	Effective Length (E)
Poop enclosed ...					
" overhang ...					
R.Q.D. enclosed ...					
" overhang ...					
Bridge enclosed ...					
" overhang aft ...					
" overhang forward ...					
Fore enclosed ...	33.25	33.25	7.0'	7.0/7.5	31.03
" overhang ...					
Trunk aft ...					
" forward ...					
Tonnage opening aft ...					
" forward ...					
Total ...	33.25	33.25			31.03

Standard Height of Superstructure	7.5'
" " R.Q.D.	
Deduction for complete superstructure	42.00'
Percentage covered $\frac{S}{L} =$	7.82
" $\frac{S_1}{L} =$	
" $\frac{E}{L} =$	7.30
Percentage from Table, Line A.	3.65
(corrected for absence of forecastle (if required))	
Percentage from Table, Line B.	
(corrected for absence of forecastle (if required))	
Interpolation for bridge less than 2L (if required)	
Deduction =	42 x 0.365 = -15.33"

SHEER CORRECTION.

Station	Standard Ordinate	S	M	Product	Actual Ordinate	Effective Ordinate	S	M	Product
A.P. ...	52.50	1		52.50	49.56	49.56	1		49.56
1/4 L from A.P. ...	23.36	4		93.44	22.25	22.25	4		89.00
1/2 L " ...	5.775	2		11.55	5.00	5.00	2		10.00
Amidships ...		4					4		
3/4 L from F.P. ...	11.55	2		23.10	11.25	11.25	2		22.50
1/4 L " ...	46.72	4		186.88	44.00	44.00	4		176.00
F.P. ...	104.99	1		104.99	96.25	96.25	1		96.25
Total ...				422.46					443.31

Mean actual sheer aft =
 Mean standard sheer aft = } **Deficient.**

Mean actual sheer forward =
 Mean standard sheer forward =

Length of enclosed superstructure forward of amidships =
 " " aft of " = } **Defe. sheer.**

Correction = $\frac{\text{Difference between sums of products}}{18} \left(\frac{.75 - S}{2L} \right) = \frac{29.15}{18} \times \left(\frac{.75 - .0391}{.7109} \right) = +1.15"$
 If limited on account of midship superstructure.

Deduction for Tropical Freeboard.

Addition for Winter and Winter North Atlantic Freeboard.

Depth to Freeboard Deck = **37.88**
 Summer freeboard = **11.31**
 Moulded draught (d) = **26.57**

Deduction for Tropical freeboard and addition for

Winter freeboard = $\frac{d}{4}$ inches = **6.64 = 6 3/4"**

Addition for Winter North Atlantic Freeboard (if required)=

Deduction for Fresh Water.

Displacement in salt water at summer load water line

$\Delta =$

Tons per inch immersion at summer load water line

T =

Deduction = $\frac{\Delta}{40T}$ inches

= **7 1/4"**

TABULAR FREEBOARD corrected for Flush Deck (if required)

Correction for coefficient **79.34 + 1.73**
79.34 + 1.73
81.07

Correction for coefficient **79.34 + 1.73**
79.34 + 1.73
81.07

Depth Correction ... **28.65**

Deduction for superstructures ... **1.53**

Sheer correction ... **1.15**

Round of Beam correction ... **1.10**

Correction for Thickness of Deck amidships ... **19.63**

Other corrections, scantlings, etc. **to complete**

to a summer moulded draught **49.53**

of 26'-6 3/4" (26'-6 7/8 actual)

Summer Freeboard = **135.75**

SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, Wood, Steel, Deck :-

Tropical Fresh Water Line above Centre of Disc ... **14"**
 Fresh Water Line " " ... **7 1/4"**
 Tropical Line " " ... **6 3/4"**
 Winter Line below " " ... **6 3/4"**
 Winter North Atlantic Line " " ... **7 1/4"**

Tropical Fresh Water Freeboard ... **11'-3 3/4"**
 Fresh Water " " ... **10'-1 3/4"**
 Tropical " " ... **10'-8 1/2"**
 Winter " " ... **10'-9"**
 Winter North Atlantic " " ... **11'-10 1/2"**

25 APR 1941