

# REPORT ON ELECTRICAL EQUIPMENT.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

Received at London Office JUN -5 1940

Date of writing Report 20.5.1940 When handed in at Local Office 30 MAY 1940 Port of Liverpool

No. in Survey held at hothwick Date, First Survey 8/4/40 Last Survey 16/5/1940

Reg. Book. on the S.T. "SPARKLER" (Number of Visits 3)

Built at hothwick By whom built W.J. Yarwood & Sons Ltd. Port No. 625 When built 1940

Owners The Admiralty Port belonging to London.

Electric Light Installation fitted by W.J. Yarwood & Sons Ltd Contract No. 625 When fitted 1940

Is the Vessel fitted for carrying Petroleum in bulk ho.

System of Distribution Two wire.

Pressure of supply for Lighting 110 volts, Heating - volts, Power - volts.

Direct or Alternating Current, Lighting Direct Power -

If alternating current system, state frequency of periods per second -

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off Yes.

Generators, do they comply with the requirements regarding temperature rise Yes, are they compound wound Yes

are they over compounded 5 per cent. Yes, if not compound wound state distance between each generator -

Where more than one generator is fitted are they arranged to run in parallel - is an adjustable regulating resistance fitted in series with each shunt field Yes

Have certificates of test results for machines under 100 kw. been submitted and approved Yes Have machines over 100 kw. been inspected by the Surveyors during manufacture and testing -

Have certificates for generators under 100 kw. been supplied and approved Yes

Are all terminals accessible, clearly marked, and furnished with sockets Yes, are they so spaced or shielded that they cannot be accidentally earthed, short circuited, or touched Yes

Are the lubricating arrangements of the generators as per Rule Yes

Position of Generators In engine room, is the ventilation in way of the generators satisfactory Yes are they clear of all inflammable material Yes if situated near unprotected

woodwork or other combustible material, state distance of same horizontally from or vertically above the generators - and - are the generators protected from mechanical injury and damage from water, steam or oil Yes, are their axes of rotation fore and aft Yes

Earthing, are the bedplates and frames of the generating plant efficiently earthed Yes are the prime movers and their respective generators in metallic contact Yes

Main Switch Boards, where placed In engine room near generator

If the generators and main switchboard are not placed in the same compartment, is each generator provided with a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard -

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes Yes, are they protected from mechanical injury and damage from water, steam or oil Yes, if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the switchboards - and - are they constructed wholly of durable, non-ignitable non-absorbent materials Yes, is all insulation of high dielectric strength and of permanently high insulation resistance Yes

is it of an approved type Yes, if semi-insulating material is used, are all conducting parts insulated from the slab with mica or micanite or other non-hygroscopic insulating material, and the slab similarly insulated from its framework Sindanyo, is the non-hygroscopic insulating material of an approved type Yes, and is the frame effectively earthed Yes

Are the fittings as per Rule regarding: - spacing or shielding of live parts Yes, accessibility of all parts Yes, absence of fuses on back of board Yes, temperature rise of omnibus bars Yes, individual fuses to voltmeter, pilot or earth lamp Yes, are moving parts of switches alive in the "off" position ho, are all screws and nuts securing connections effectively locked Yes, are any fuses fitted on the live side of switches ho.

Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches


Double pole switch fuses for generator & each outgoing circuit.

Are turbine driven generators fitted with emergency trip switch as per rule - Are cupboards or compartments containing switchboards composed of fire-resisting material or lined with approved material - Instruments on main switchboard 1 ammeter 1

voltmeter - synchronising device for paralleling purposes. For compound machines is the ammeter connected on the opposite pole to equaliser connection

Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system

Earth Lamps. Switches, Circuit Breakers and Fusible Out-outs, do these comply with the requirements of the Rules. Yes are the fusible cutouts of an approved type Yes have the reversed



current protection devices been tested under working conditions — are all fuses labelled as per rule Yes

**Joint Boxes, Section and Distribution Boards.** is the construction, protection, insulation, material, and position of these as per rule Yes

**Cables:** Single, twin, concentric, or multicore Single are the cables insulated and protected as per Tables IV, V, X, XI, XII or XIII of the Rules Yes

If the cables are insulated otherwise than as per Rule, are they of an approved type — **Fall of Pressure,** state maximum between bus bars and any point of the installation under maximum load 1 Volt

**Cable Sockets,** are the ends of all cables having a sectional area of 0.04 square inch and above provided with soldering sockets all less than .04" **Paper Insulated and Varnished Cambric Insulated Cables,**

If conductors are paper or varnished cambric insulated, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound — or waterproof insulating tape — **Cable Runs,** are the cables fixed as far as possible in accessible positions

not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage Yes are cables laid under machines or floorplates no if so, are they adequately protected —

Are cables in machinery spaces, galleys, laundries, bathrooms and lavatories lead covered or run in conduit Yes

**Support and Protection of Cables,** state how the cables are supported and protected All cables V.I.R. run in gals. conduit.

If cables are run in wood casings, are the casings and caps secured by screws —, are the cap screws of brass —, are the cables run in separate grooves —. If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VIII —

**Refrigerated Chambers,** are the cables and fittings in accordance with the special requirements —

**Joints in Cables,** state if any, and how made, insulated, and protected None

**Watertight Glands and Deck Tubes,** are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands Yes **Bushes in Beams and Non-watertight Partitions,** where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed — state the material of which the bushes are made All cables in Conduit.

**Earthing Connections,** state what earthing connections are fitted and their respective sectional areas Conduit electrically continuous, banded & levelled. are their connections made as per Rule ✓

**Alternative Lighting,** are the groups of lights in the propelling machinery space arranged as per Rule Yes **Emergency Supply,** state position and method of control of the emergency supply and how the generator is driven —

**Navigation Lamps,** are these separately wired Yes controlled by separate switch and separate fuses Yes are the fuses double pole Yes are the switches and fuses grouped in a position accessible only to the officers on watch Yes

has each navigation lamp an automatic indicator as per Rule Yes **Secondary Batteries,** are they constructed and fitted as per Rule — are they ventilated as per Rule —

**Fittings,** are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight Yes are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected None

are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected None how are the cables led —

where are the controlling switches situated — are all fittings suitably ventilated Yes are all switches and lampholders constructed wholly of non-ignitable, non-absorbent materials Yes

**Heating and Cooking Appliances,** are they constructed and fitted as per Rule — are air heaters constructed and fitted as per Rule —

**Searchlight Lamps, No. of** — whether fixed or portable — are their fittings as per Rule —

**Motors,** are their working parts readily accessible — are the coils self-contained and readily removable for replacement — are the brushes, brush holders, terminals and lubricating arrangements as per Rule — are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material — are they protected from mechanical injury and damage from water, steam or oil — are their axes of rotation fore and aft — if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type — if not of this type, state distance of the combustible material horizontally or vertically above the motors — and —

have machines of over 100 BHP been inspected by the Surveyors during manufacture and testing — have certificates for all motors for essential services been supplied and approved — **Control Gear and Resistances,** are the generator field and motor speed regulators, starters and controllers constructed and fitted as per Rule Yes **Lightning Conductors,** where lightning conductors are required, are these fitted as per Rule Yes **Ships carrying Oil having a Flash Point less than 150° F.** Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings — are all fuses of the filled cartridge type — are they of an approved type —

If portable lamps for use in dangerous spaces are supplied, are they of a self-contained, battery-fed flameproof type approved for use in dangerous spaces —

**Spare Gear,** if the vessel is for open sea service have spares been supplied as per Rule Yes are they suitably stored in dry situations Yes.

PARTICULARS OF GENERATING PLANT.

DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.	
		Kilowatts.	Volts.	Ampères.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.
MAIN ...	DYE	2	110	18.2	1000	Steam Engine	—	—
AUXILIARY ...								
EMERGENCY ...								
ROTARY TRANSFORMER								

GENERATOR, LIGHTING AND HEATING CONDUCTORS.

DESCRIPTION.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT. AMPERES.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
	No. per Pole.	Total Nominal Area per Pole Sq. Ins.	No.	Diameter.	Circuit.	Rule.			
MAIN GENERATOR ...	1	.007	7	.036	18.2	24	20	Rubber	Gals. Conduit
EQUALISE CONNECTIONS ...									
AUXILIARY GENERATOR ...									
EMERGENCY GENERATOR ...									
ROTARY TRANSFORMER MOTOR GENERATOR ...									
ENGINE ROOM ...									
BOILER ROOM ...									
AUXILIARY SWITCHBOARDS ...									
SHIP LIGHTING, NAVIGATION.	1	.003	3	.036	11.5	12.0	8	"	"
	1	.003	3	.036	3.36	12.0	100	"	"
ACCOMMODATION ...									
WIRELESS ...									
SEARCHLIGHT ...									
MASTHEAD LIGHT ...	1	.002	3	.029	.36	7.8	100	"	"
SIDE LIGHTS ...	1	.002	3	.029	.36	7.8	40	"	"
COMPASS LIGHTS ...	1	.002	3	.029	.18	7.8	10	"	"
POOP LIGHTS ...									
CARGO LIGHTS ...									
HEATERS ...									

MOTOR CONDUCTORS.

DESCRIPTION.	No. of Motors.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT. AMPERES.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
		No. Per Pole.	Total Nominal Area per Pole Sq. Ins.	No.	Diameter.	In Circuit.	Rule.			
BALLAST PUMP ...										
MAIN BILGE LINE PUMPS ...										
GENERAL SERVICE PUMP ...										
EMERGENCY BILGE PUMP ...										
SANITARY PUMP ...										
CIRC. SEA WATER PUMPS ...										
CIRC. FRESH WATER PUMPS ...										
AIR COMPRESSOR ...										
FRESH WATER PUMP ...										
ENGINE TURNING GEAR ...										
ENGINE REVERSING GEAR ...										
LUBRICATING OIL PUMPS ...										
OIL FUEL TRANSFER PUMP ...										
WINDLASS ...										
WINCHES, FORWARD ...										
WINCHES, AFT ...										
STEERING GEAR—										
(a) MOTOR GENERATOR ...										
(b) MAIN MOTOR ...										
WORKSHOP MOTOR ...										
VENTILATING FANS ...										

The Electrical Equipment is installed in accordance with the approved plans.  
 All Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.  
 The foregoing is a correct description. (1938) LTD.

*Albert Yarwood*  
 W. J. YARWOOD & SONS (1938) LTD.  
 Managing Director

Electrical Engineers. Date 21. 5. 40

COMPASSES.

Minimum distance between electric generators or motors and standard compass \_\_\_\_\_

Minimum distance between electric generators or motors and steering compass 60 feet.

The nearest cables to the compasses are as follows:—

A cable carrying 3.36 Ampères — feet from standard compass 4 feet from steering compass.

A cable carrying .36 Ampères — feet from standard compass led into feet from steering compass.

A cable carrying Ampères feet from standard compass feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power Yes ✓

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted Yes. ✓

The maximum deviation due to electric currents was found to be \_\_\_\_\_ degrees on \_\_\_\_\_ course in the case of the standard compass, and *lit* degrees on *any* course in the case of the steering compass.

W. J. YARWOOD & SONS (1938) LTD.

*Albert Yarwood*  
 W. J. YARWOOD & SONS (1938) LTD.  
 Managing Director

Builder's Signature. Date 21. 5. 40

Is this installation a duplicate of a previous case *no*. If so, state name of vessel \_\_\_\_\_

General Remarks (State quality of workmanship, opinions as to class, &c. *The electrical equipment of the vessel has been fitted on board under special survey, tested under full working conditions & found satisfactory. The materials & workmanship are good.*)

*Noted.*  
*L.J.*  
*11/6/40*

Total Capacity of Generators 2. Kilowatts.

The amount of Fee ... £ 3 : 0 : 0

When applied for, 03 1 MAY 1940

Travelling Expenses (if any) £ :

When received.

14/6/19.40 *est. 1/6*

*L. Haffner*

Surveyor to Lloyd's Register of Shipping.

Committee's Minute LIVERPOOL - 4 JUN 1940

Assigned See Minute on *L.E. Machinery Report.*

2m.12.36.—Transfer. The Surveyors are requested not to write on or below the space for Committee's Minute.)



© 2020

Lloyd's Register Foundation