

PARTICULARS OF PROTECTION TO OPENINGS, ETC.

| HATCHWAYS ON FREEBOARD AND SUPERSTRUCTURE DECKS. | | | | | | | |
|--|-----------------------------|---------------------|--------------|-----------|---------|--|--|
| Description of Hatchway | No. 1 | No. 2 | No. 3 | No. 4 | | | |
| Dimensions of Hatchway | 24' 6" x 16' | 24' 6" x 16' | 24' 6" x 16' | 22' x 16' | | | |
| COAMINGS | Height above Deck | | | | | | |
| | Thickness { Sides { Ends | | | | | | |
| | Stiffeners | | | | | | |
| | Brackets, Stays | One; 100x11.5 mm. ✓ | Do. ✓ | Do. ✓ | Do. ✓ | | |
| HATCH BEAMS | Number | 4 x 5 | 5 | 5 | 4 x 5 | | |
| | Spacing | 2 x 1218 | Do. ✓ | Do. ✓ | 2 x 984 | | |
| | Scantling and Sketch | 2 x 1364 | Do. ✓ | Do. ✓ | 5 x A ✓ | | |
| | | 3 x A ✓ 2 x B ✓ | Do. ✓ | Do. ✓ | | | |
| | Bearing Surface | 3" x 1" ✓ | Do. | Do. | Do. | | |
| FORE AND AFTERS | Number | | | | | | |
| | Spacing | | | | | | |
| | Unsupported Lengths | | | | | | |
| | Scantling* and Sketch | | | | | | |
| | Bearing Surface | | | | | | |
| HATCH COVERS | Material | Wood (steel shod) ✓ | Do. | Do. | Do. | | |
| | Thickness | 3" | 3" | 3" | 3" | | |
| | How fitted | Lengthwise | Do. | Do. | Do. | | |
| | Bearing Surface | 3" | 3" | 3" | 3" | | |
| Spacing of Cleats | | | | | | | |
| Number of Tarpaulins | | | | | | | |

*Are wood fore and afters steel shod at all bearing surfaces? ✓
 Are battens and wedges efficient and in good condition?
 Are tarpaulins in good condition and in accordance with rule requirements?
 Are lashings provided in accordance with rule requirements?

Particulars of any special features:—

1218
 4
 | 1218 | 1218 | 1364 | 1364 | . | . |
 . 2 3 4 5

Notes
 A715
 4872
 1968
 6840

Endorsement at first survey and at surveys for renewal of Certificate:—

The fittings and appliances are in accordance with the particulars shown on this form (or as now modified) and are in good condition.

| 1364 | 1364 | 1218 | 1218 | 1218 | 1218 |
 A A A A A

2728
 4872
 7600