

Rpt. 11b
29 385

EXT

Bel 23/1/32

THU. 3rd FEB. 1921

Index No. 29385
(For London Office only.)

Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD.-STEAM SHIPS.

No 17775.

PARTICULARS RELATING TO ALL STEAM SHIPS ~~EITHER FLUSH DECKED, OR WITH TOP GALLANT FORECASTLES, SHORT POOPS AND BRIDGE HOUSES CONNECTED, OR WITH TOP GALLANT FORECASTLES HAVING LONG POOPS, OR BRIDGE HOUSES CONNECTED WITH BRIDGE HOUSES, OR OTHERWISE~~

Port of Survey Greenock
Date of Survey while Building
Name of Surveyor J. Macleod

Messrs R. Jamieson & Co. Ld N^o 334

Ship's Name "GOBEO"	Port of Registry and Nationality <u>Gillman</u>	Official Number	Gross Tonnage <u>approx 3400</u>	Date of Build. <u>1921</u>	Particulars of Classification. <u>100 A.I. Carrying petroleum in cylindrical tanks contemplated</u>
-------------------------------	--	-----------------	-------------------------------------	-------------------------------	--

Registered dimensions from Ship's Register. LENGTH. <u>330.2</u>	BREADTH. <u>48.05</u>	DEPTH. <u>22.45</u>	UNDER DECK TONNAGE. <u>2889.48</u>
Length on LOADLINE. <u>330.08</u>	Frame Depth Rule <u>48.05</u>	Ceiling Sheer <u>+20</u>	Peak Tanks <u>+72</u>
CORRECTED DIMENSIONS. <u>330.08</u>	<u>47.46</u>	<u>22.45</u>	<u>2889.48</u>

Moulded Depth as measured..... 24'8"

Addition for Keel below base line for draught record.... 2 1/4 inches.

NOTE - If the depth is measured when vessel is afloat, the details of measurement should be reported.

34.8
1.0
35.8
3.24
32.54

CORRECTION FOR LENGTH.

Length of Ship on Loadline.....	<u>330.08</u>	✓
Length in Table	<u>296</u>	✓
Difference	<u>34.08</u>	✓
Correction for 10ft., Table A.	<u>1.3</u>	Table C.
× Difference divided by 10	<u>4.43</u>	(if required.)
If 1/10ths length covered divide by 2	<u>2.21</u>	+ <u>2 1/4</u> ✓

Co-efficient of fineness..... .786

Modification necessary [Para. 4 (a) to (e)]* Both D. & A.

Co-efficient as corrected..... .77

CORRECTION FOR IRON DECK.

Proportion covered, if less than 1/10ths length covered... P.B. & C. courses 48.78

Thickness of usual wood deck, less stringer 3 1/2 Trunks 202

allowance 3 1/4 ✓

477

Sheer at 1/2 of the length from { Stem 30 } 76 ÷ 2 = 38 ... Mean

{ Sternpost 26 } 76 ÷ 2 = 38 ... Mean

Gradual mean Sheer 49.04

Standard mean Sheer [Table, Para. 18] 43.01 Correction

Difference..... 26.03 ÷ 4 = -6 1/2 ✓

§ If limited as Para. 18 (f)

CORRECTION FOR ROUND OF BEAM.

Breadth at Gunwale amidships..... 46'

Round of Beam 12"

Normal round..... 11 1/2"

Difference 1/2 ÷ 2 = 1/4

Proportion of Deck uncovered (Para. 19) ✓ ✓

NOTE - The round of beam should be reported on the full breadth of vessel at the gunwale.

Rise in Sheer from amidships { At front of bridge house..... ✓ }
[Para. 18 (e)] { At after end of forecastle ✓ }

Fall in Sheer { } ÷ 2 = ✓

Length uncovered Correction

Freeboard, Table A 5'-5"

Correction for Sheer -6 1/2

Correction for Length + 2 1/4

Allowance for Deck Erections 5-0 3/4

Correction for Round of Beam..... 1-0 1/2

Correction for fall in Sheer (if any)..... ✓

Correction for Iron Deck (if required) -3 1/4

Additions for non-compliance with provisions of Para. 11 (d) and (e) † 3-9

Other Corrections (if any)

ALLOWANCE FOR DECK ERECTIONS :-

Freeboard, Table C..... 2'-6 1/4 ✓

Correction for Length, if required (Para. 12, 13, and 14)

Freeboard by Table A. corrected for sheer, and for length, if required (Para. 12, 13, and 14) } 4-10 1/2 ✓

Difference 2-4 1/4 ✓

Percentage as below..... 43.9 %

Winter Freeboard 3'-9"

Summer Freeboard 3'-5"

Indian Summer Freeboard 3'-1"

N.A. Winter Freeboard

Correction necessary because clearside amidships, measured in accordance with the Statute is not taken at the intersection of the ~~wood~~ iron deck with side. 1 3/4 ✓

Winter Freeboard from deck line 3'-10 3/4 ✓

Summer " " " " 3'-6 3/4 ✓

Indian Summer " " " " 3'-2 3/4 ✓

N.A. Winter " " " "

	Length.	Length allowed.	Height.
Forecastle.....	<u>38</u>	<u>38</u>	<u>7'0"</u>
Bridge House	<u>96.25</u> (47.29)	<u>96.25</u>	<u>7'6"</u>
Trunk	<u>172.41</u> × <u>2.32</u> × <u>8</u>	<u>93.24</u> <u>34</u>	<u>7'0"</u>
.....	<u>22.45</u> (22.45).....	<u>22.45</u>	<u>7'6"</u>
Total		<u>310.94</u> <u>211.04</u>	
Length of Ship		<u>330.08</u> * <u>309.638</u>	
Corresponding percentage (Para. 11, 12, 13, or 14) }	<u>43.9</u> %		

FREEBOARD recommended amidships from centre of Disc to top of Statutory Deck Line, ~~Wood~~ (Iron) Deck :-

Fresh Water Line above centre of Disc 5 1/2"

Indian Summer Line " " " " 4

Winter Line below " " " " 4

Winter North Atlantic Line " " " "

State dimensions of freeing port area on back of this form.

† The Surveyor should state whether the fall in sheer as reported is measured relatively to the straight line of keel or to the water line. If measured relatively to water line the vessel's draft at time of survey, and also the usual draft forward and aft, should be reported.

¶ If the frames, skin planking, or ceiling are of unusual thickness the breadth of vessel to inside of ceiling should be reported if possible.

† In vessels obtaining an allowance for deck erections under Para. 11 where the sheer drops abaft amidships the height of the R.Q.D. is to be taken from the level of the top of the amidship beam.

§ In flush-decked vessels the total standard mean sheer means the sheer measured at the stem and sternpost. In vessels having poops and forecastles, it means the sheer measured at points distant one-eighth of the vessel's length from stem and stern-post.

MARKING REPORT

RECEIVED 10 JUN 1929

RECEIVED 23 FEB 1925

RECEIVED 14-2-21

002830-002837-0004

Do all the Frames extend to the top height in the Poop? *Yes* Raised Quarter Deck? Bridge House? *Yes* Forecastle? *Yes*
 To what height do the Reverse Frames extend? *B. A. framing*
 Has the Poop or Raised Quarter Deck an efficient Iron Bulkhead at the fore end? *Yes*
 Give particulars of the means for closing the openings in Bulkhead *No openings*
 Is the Poop or Raised Quarter Deck connected with the Bridge House? *By trunk* Has the Bridge House an efficient Bulkhead at the fore end? *Yes*
 Give particulars of the means for closing the openings in Bulkhead *two hinges W.T. Joints*
 What is the thickness of the Bridge Front plating? *.40* and Coaming plate? *.44*
 Give scantlings and spacing of the Stiffeners *8 x 32 x .54 B.A. spaced 28"*
 Are bracket plates fitted at each end of the Stiffeners? *Yes* Are hor'l. brackets fitted connecting Bridge Bulk'd. with Bulwarks? *Yes*
 Has the Bridge House an efficient Iron Bulkhead at the after end? *Yes*
 How are the openings closed? *Weather boards fitted in riveted channels*
 Is the Forecastle at least as high as the main or top-gallant rail? *Yes* Has the Forecastle an efficient Iron or Wood Bulk'd. at after end? *Yes*
 Are the Engine and Boiler openings covered by a Bridge, Poop, Raised Quarter Deck, or enclosed by a Strong Iron or Steel Deckhouse? *covered by trunk*
 If the openings are not so protected are the exposed parts of the Casings efficiently constructed?
 Give thickness of plating; scantlings and spacing of Stiffeners
 What is the height of the exposed Casings? Are suitable means provided for closing all openings in them in bad weather?
 Are the Weather Deck Hatchways efficiently constructed and at least equal to the requirements of Section 28 of the Rules for 1904-5? Give particulars below:—

Position and Size.	No 1 Hatch 7'-11 1/2" x 8'-0"									
Item.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.	Ship.	Rule.
COAMING.	Height above top of DECK	30"								
	Thickness	Sides.....	.44							
		Ends.....	.44							
SHIFTING BEAMS OR WEB PLATES.	Number	One			Oiltight Hatches 5'-6 1/2" x 3'-6"	4 1/16"			} fitted to each ext.	
	Section and Scantlings	7 1/2" x 3 x 1/4"			3'-9 1/2" x 2 1/4"	1 1/16"				
	Material	59 x 30 6 1/2"								
* FORE AND AFTERS.	Number	None								
	Section and Scantlings									
	Material									
HATCHES Thickness	2 1/2"									
Remarks.....										

* The depth of Fore and Afters should be stated from the underside of the hatches in all cases.


(If the sill of the lowest side scuttle will be less than 6 inches above the Indian Summer Load Line if assigned under the tables, state vertical distance from top of deck at side amidships to lower edge of lowest side scuttle.)

The following information is to be given in all Cases of vessels dealt with under Paras. 11, 12 (under 15 feet Moulded depth) and under Shelter Deck Rules.

What is the thickness of the Bridge Sheerstrake? _____ Strake between Main and Bridge Sheerstrakes? _____

Delete the words The Crew are, are not, berthed in the bridge house.
 that do not apply The arrangements to enable them to get backwards and forwards from their quarters are, are not satisfactory.

Length of Bulwarks in well _____
 Area of Freeing Ports required by Para. 11 (e) each side of vessel = _____ Sq. ft.
 Ft. Tenths. Ft. Tenths. No. }
 × × } Freeing Ports = _____ Sq. ft.
 (each side of vessel)
 × × }
 Total deficiency or excess = _____ Sq. ft.



Show hereon line of Floors or Tank Top with position of any Breaks in same; also height of Peak Tank tops, &c., &c.

State any special features in the construction of the Vessel *This vessel has been converted to carry petroleum in cylindrical tanks. No ship section and outline profile not forwarded for reference. A request form is attached.*

Owners Builders:— *Messrs R. Duncan & Co Ltd*
 „ Address _____

Fee £ 9 : - : - Received by me _____

