

Lloyd's Register of Shipping.
SURVEYS FOR FREEBOARD.

PARTICULARS IN RESPECT OF STEAM SHIPS HAVING SPAR OR AWNING DECKS.						Port of Survey
Proposed S. S. Steamer by Stablimento Dec...						Date of Survey 5/3/26
Ship's Name.		Port of Registry and Nationality.	Official Number.	Gross Tonnage.	Date of Build.	Name of Surveyor
Number in Register Book						Particulars of Classification.
Registered dimensions from Ship's Register.	LENGTH.	BREADTH.	DEPTH.	UNDER DECK Tonnage.	100 A. 1. with Ad. (Contemplated)	
Length on LOADLINE		Frame Depth Rule	Ceiling Sheer	Peak Tanks	Moulded Depth as measured 30-2 Main Deck.	
CORRECTED DIMENSIONS.					" " " 38-2 Spar or Awning Deck.	
Co-efficient of fineness					Addition for Keel below base line for draught record.....inches.	
Any modification necessary [Para. 4 (a) to (e)*]					NOTE.—If the depth is measured when vessel is afloat, the details of measurement should be reported.	
Co-efficient as corrected					CORRECTION FOR LENGTH:—	
Allowance for strength in excess of Lloyd's rules =					Length of Ship on Load Line.... 625	
State particulars—					Length in Table 362	
					Difference 263	
					Correction for 10ft. 8	
					x Difference ÷ 10 = 21.04 + 1.9	
					Height of 'Tween Decks.....	
					(From top of beam to top of beam at side)	
					Correction for Height of 'Tween Decks in Spar-decked Ships.....	
					Freeboard Table B or C 4 2 3/4	
					Correction for Length..... - 1 9	
					Correction for Height of 'Tween Decks in Spar-decked Ships..... 5 11 3/4	
					Correction for Strength in excess of Lloyd's rules.....	
					Correction for Iron Deck if required..... - 3 4	
					Other Corrections (if any)..... 5 8	
Sheer at Stem at 1/2 length from Stem					Winter Freeboard..... 5 8 1/4	
Sternpost... " " " Sternpost...					Summer Freeboard 5 2 1/4	
Drop in Sheer abaft amidships.....					Indian Summer Freeboard.....	
Round of Spar-deck Beam.....					N. A. Winter Freeboard.....	
" " Main-deck "					Correction necessary because clearside amidships measured in accordance with the Statute is not taken at inter-section of the wood or steel deck with side	
Length x Height. State if open or closed at ends.					Winter Freeboard from Deck Line 30	
Forecastle x					Summer " " 5	
Bridge..... x					Indian Summer " " 25	
Poop x					N. A. Winter " " 25	

FREEBOARD recommended amidships from centre of Disc to top of Statutory Deck Line, Wood (Steel) Deck:—

Fresh Water Line			above centre of Disc
Indian Summer Line	"	"	"
Winter Line			below	"	"
Winter North Atlantic Line	"	"	"

NOTE.—All vessels equal in strength to Lloyd's Spar-decked rule, or which, although in excess of that rule, do not come up to Lloyd's requirements for Ships of full scantlings to the upper deck, are to be considered as Spar-decked Ships, the freeboard for which will vary with their strength.
All vessels equal in strength to Lloyd's Awning-decked rule, or which, although in excess of that rule, do not come up to Lloyd's requirements for a Spar-decked Vessel, are to be considered as Awning-decked Ships, the freeboard for which will vary with their strength.

* If the frames, skin planking, or ceiling are of unusual thickness the breadth of vessel to inside of ceiling should be reported if possible.