Index No. 28645
(For London Office only.)

Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD.

PARTICULARS IN RESPECT OF STEAM SHIPS HAVING ~~SPAR OR~~ AWNING DECKS.

Port of Survey Copenhagen
Date ~~of Survey~~ 31. 1. 20.
Name of Surveyor

Ship's Name.	Port of Registry and Nationality.	Official Number.	Gross Tonnage.	Date of Build.	Particulars of Classification.
Steamer No. 315. Register Book					+ 100 A1. Awning decks with freeboard contemplated.

Length.	Breadth.	Depth.	Under Deck Tonnage.
425.56	55.3		
	Frame Depth 10 Rule " 6/4 -.64	Ceiling Sheer + 1.06 Load Tank	Peak Tanks
425.46	54.63	29.18	5165.

Moulded Depth ~~as measured~~ (amidships) 30'-6" Main Deck.
" " " 38'-6" ~~Spar or~~ Awning Deck.

NOTE.—If the depth is measured when vessel is afloat, the details of measurement should be reported.

Correction for Length :—

Length of Ship on Load Line	425.46
Length in Table	366.
Difference	59.46
Correction for 10ft.	.8
× Difference ÷ 10 =	4.7568

+ 4 3/4"

Fineness ..... .76
Rise of floor if necessary [to (e)*] ..... Coll. D.B.
Proportion corrected ..... .744

Strength in excess of Lloyd's rules = 2/

Deep bulb angle framing
Strengthened topsides
Three complete steel decks with beams to alternate frames.
3 W.T. Bulkheads. Collision to Awning Deck, rest to main deck.

Height of 'Tween Decks 8-0
(From top of beam to top of beam at side)
Correction for Height of 'Tween Decks in Spar-decked Ships .....

Freeboard Table ~~B or~~ C ..... 4'-6"
Correction for Length ..... + 4 3/4"
4 - 10 3/4"
Correction for Height of 'Tween Decks in Spar-decked Ships. Height of 'Tween decks from Steel Main DK to 3" Sheathing on Awning Deck. + 8 - 3"
13 - 1 3/4"
Correction for Strength in excess of Lloyd's rules ..... — 2 - 3
10 - 10 3/4"
Correction for Iron Deck if required ..... — 3 1/2"
10 - 7 1/4"
Other Corrections (if any) .....

Winter Freeboard	10'-7 1/4"
Summer Freeboard	10-0 1/4"
Indian Summer Freeboard	9-5 1/4"
~~N. A. Winter Freeboard~~	—

Correction necessary because clearside amidships measured in accordance with the Statute is not taken at intersection of the wood ~~or Iron~~ deck with side 13/4"

Winter Freeboard from Deck Line	10'-9"
Summer " " "	10'-2"
Indian Summer " "	9'-7"
~~N.A. Winter~~ Awning " "	

.... 124 at 1/3 length from Stem 1/3
...t... 61 " " " Sternpost... 2/
Drop in Sheer abaft amidships ..... —
...Deck.
...ck Beam ..... 13 3/4"
...eck " ..... 13 3/4"

Length	×	Height.	State if open or closed at ends.
	×		
	×		
	×		

ecommended amidships from centre of Disc to top of Statutory Deck Line, Wood (~~Iron~~) Deck :—

2.20.

Fresh Water Line	above	centre of Disc	10'-2"
Indian Summer Line	"	" "	7"
Winter Line	below	" "	7"
~~Winter North Atlantic Line~~	"	" "	7"

ll vessels equal in strength to Lloyd's Spar-decked rule, or which, although in excess of that rule, do not come up to Lloyd's requirements for Ships of full scantlings to the upper deck, are to be considered as Spar-decked Ships, the freeboard for which will vary with their strength.
ll vessels equal in strength to Lloyd's Awning-decked rule, or which, although in excess of that rule, do not come up to Lloyd's requirements for a Spar-decked Vessel, are to be considered as Awning-decked Ships, the freeboard for which will vary with their strength.

* If the frames, skin planking, or ceiling are of unusual thickness the breadth of vessel to inside of ceiling should be reported if possible.

Copy to Surveyor H. 2.20.

38-6
3
38-11

[P.T.O.

© 2021 Lloyd's Register Foundation
003065-003074-0139