

[illegible]

GENERAL REMARKS—(continued).

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop ✓ ft., R.Q.D. ✓ ft., Bridge 47-6 ft., Forecastle 21-10 1/2 ft. (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated ✓

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as should appear in the Register Book) 10* (Stl)

Official No. 145634 ; Signal Letters

State if Machinery is fitted aft Amidships

How are the surfaces preserved from oxidation? Inside Paint, Cement in DB in Machinery space Outside Paint

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors Cellular System

Where Fitted.	Length.	Water Capacity.	Where Fitted.	Length.	Water Capacity.
	Feet.	Tons.		Feet.	Tons.
Double bottom, aft,	80	152	Fore peak tank,	17-375	67
Double bottom, under Engines and Boilers,	32-5	41 7/16	After peak tank,	18-6	117
Double bottom, if under Engines only,	—	—	Deep tank, aft,		
Double bottom, if under Boilers only,	106-5	203	Deep tank, forward,		
Double bottom, forward,		431	Other tanks, if fitted,		
	Total capacity of double bottom		(If necessary, furnish further information by sketch.)		

* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules. Yes

Order for Special Survey No 5078

Date 17/6/24

No. 223 in builder's yard.

DATES of Surveys held while building

1924 Apr 7-23. 30. May 6. 13. 19. 27. June 4. 11. 13. 17. 18. 21. 24. July 4. 10. 11. 15. 19. 28. Aug 5. 11.

Total No. of Visits 22

Surveyor's Signature

Alex. Munro

© 2020

Lloyd's Register Foundation