

# "EMPIRE CONFIDENCE"

## PARTICULARS OF PROTECTION TO OPENINGS, ETC.

HATCHWAYS ON FREEBOARD AND SUPERSTRUCTURE DECKS.											
			FREEBOARD DK.			→		FORE PEAK		FORE PEAK	
Description of Hatchway			Nº 5	Nº 6	Nº 7	ON FOLE DECK.	ON SUPERSTRUCT. DECK FOR	ON FREEBOARD DK. FOR	ON FREEBOARD DK. AMIDSHIP	ON POOP DK. AFT.	TO CHAIN LOCKER AFT
Dimensions of Hatchway			34'-1" x 18'-0"	18'-4" x 18'-0"	5'-5" x 10'-0"	4'-0" x 2'-6"	4'-0" x 2'-6"	4'-0" x 3'-5"	1'-8" x 1'-8"	3'-3" x 2'-9"	1'-7" x 1'-7"
COAMINGS	{	Height above Deck	10"	10"	36"	36"			9" B.A.	36"	20"
		Thickness	Sides	.44"	.44"	.44"	.40"	.25"	3 1/2" x 3 1/2" x 36"	.40"	.38"
			Ends	.44"	.44"	.44"	.40"	.25"		.40"	.38"
		Stiffeners				✓✓	✓✓	✓	✓	✓✓	✓✓
Brackets, Stays			✓	✓	✓✓	✓✓	✓	✓	✓✓	✓✓	✓✓
HATCH BEAMS	{	Number	5	3							
		Spacing	5'-8"	4'-7"							
		Scantling and Sketch		4 3/4" x 2 1/4" x 40"	4 3/4" x 2 1/4" x 40"	✓	✓	✓	✓	✓	✓
				18" x 35"	18" x 35"						
Bearing Surface			4 1/2" x 2 1/2" x 36" 3" B.A.	4 1/2" x 2 1/4" x 36" 3" B.A.							
FORE AND AFTERS	{	Number									
		Spacing									
		Unsupported Lengths Scantling* and Sketch									
Bearing Surface			NONE			✓	✓	✓	✓	✓	✓
HATCH COVERS	{	Material	AS	AS	W.T.	WOOD	WOOD	WOOD	W.T. COVER	WOOD	W.T. COVER
		Thickness	Nº1	Nº1	BOLTS + NUTS	2 3/4"	2 3/4"	2 3/4"	✓	2 3/4"	✓
		How fitted	✓	✓		F.A.	F.A.	F.A.	BOLTS + NUTS	F.A.	BOLTS + NUTS
		Bearing Surface				3"	3"	3"		3"	
Spacing of Cleats			AS	AS	✓	17"	17"	✓✓	✓	17"	✓
Number of Tarpaulins			Nº1	Nº1	✓	12	1	✓		12	✓


\*Are wood fore and afters steel shod at all bearing surfaces?

Are battens and wedges efficient and in good condition?

Are tarpaulins in good condition and in accordance with rule requirements? *See back of report.*

Are lashings provided in accordance with rule requirements?

Particulars of any special features:—



© 2020

Lloyd's Register  
Foundation

003349-003349-0185