

REPORT ON ELECTRICAL EQUIPMENT.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

5 - MAY 1947

Received at London Office

Date of writing Report 1st April, 1947 When handed in at Local Office 1st April, 1947 Port of Galveston, Texas

No. in Survey held at Galveston, Texas Date, First Survey 20th Feb. Last Survey 1st March, 1947
Reg. Book. (Number of Visits 3)

75891 on the S/S "JAMES D. PHELAN" Tons { Gross 7176
Net 4380

Built at Richmond, Cal. By whom built Permanente Metals Corp. No. 2 When built 1943

Owners Scindia Steam Navigation Co. Port belonging to Bombay

Electric Light Installation fitted by - Contract No. - When fitted -

Is the Vessel fitted for carrying Petroleum in bulk No

System of Distribution Two wire Direct Current

Pressure of supply for Lighting 110 volts. Heating - volts, Power 110 volts,

Direct or Alternating Current, Lighting Direct Power -

If alternating current system, state frequency of periods per second -

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off Yes

Generators, do they comply with the requirements regarding temperature rise Yes, are they compound wound Yes

are they over compounded 5 per cent. -, if not compound wound state distance between each generator -

Where more than one generator is fitted are they arranged to run in parallel Yes, is an adjustable regulating resistance fitted in

series with each shunt field Yes Have certificates of test results for machines under 100 kw. been submitted and

approved - Have machines over 100 kw. been inspected by the Surveyors during manufacture and testing -

Are all terminals accessible, clearly marked, and furnished with sockets Yes, are they so spaced or shielded that they cannot be accidentally earthed,

short circuited, or touched Yes Are the lubricating arrangements of the generators as per Rule Yes

Position of Generators Generator Flat S.S. Engine Room after end, is the ventilation

in way of the generators satisfactory Yes are they clear of all inflammable material Yes if situated near unprotected

woodwork or other combustible material, state distance of same horizontally from or vertically above the generators - and -,

are the generators protected from mechanical injury and damage from water, steam or oil Yes, are their axes of rotation fore and aft Yes,

Earthing, are the bedplates and frames of the generating plant efficiently earthed Yes are the prime movers and their respective generators

in metallic contact Yes Main Switch Boards, where placed Generator Flat Eng. Room S. S. aft

If the generators and main switchboard are not placed in the same compartment, is each generator provided with

a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard -

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes Yes, are they protected from mechanical

injury and damage from water, steam or oil Yes, if situated near unprotected woodwork or other combustible material, state distance of same

horizontally from or vertically above the switchboards - and -, are they constructed wholly of durable, non-ignitable non-absorbent

materials Yes, is all insulation of high dielectric strength and of permanently high insulation resistance -,

is it of an approved type -, if semi-insulating material is used, are all conducting parts insulated from the slab with mica or micanite or other

non-hygroscopic insulating material, and the slab similarly insulated from its framework -, is the non-hygroscopic insulating material of an approved

type -, and is the frame effectively earthed Yes Are the fittings as per Rule regarding:—spacing or shielding of live parts

Yes, accessibility of all parts Yes, absence of fuses on back of board Yes, temperature rise of

omnibus bars -, individual fuses to voltmeter, pilot or earth lamp Yes, are moving parts of switches alive in the

"off" position No are all screws and nuts securing connections effectively locked Yes are any fuses fitted on the live side of

switches No Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches

Three pole disconnect switches, centre pole equalizer. Two pole carbon break circuit breaker

with overload protection each blade and under voltage reverse current protection.

Are turbine driven generators fitted with emergency trip switch as per rule - Are cupboards or compartments containing switchboards composed of


fire-resisting material or lined with approved material - Instruments on main switchboard 3 ammeters 3 volt-

meters 3 synchronizing device for paralleling purposes. For compound machines is the ammeter connected on the opposite pole to equalizer connection

Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system

earth lamps Switches, Circuit Breakers and Fusible Cut-outs,

do these comply with the requirements of the Rules Yes are the fusible cutouts of an approved type Yes have the reversed



current protection devices been tested under working conditions... **Yes** Joint Boxes, Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per rule... **Yes** To A.I.E.E. Standards

Cables: Single, twin, ~~conductor~~ multicore... **Yes** are the cables insulated and protected as per Tables IV, V, X or XI of the Rules... **Standards**

If the cables are insulated otherwise than as per Rule, are they of an approved type... **Yes** Fall of Pressure, state maximum between bus bars and any point of the installation under maximum load... **2.96 volts** Cable Sockets, are the ends of all cables having a sectional area of 0.04 square inch and above provided with soldering sockets... **Yes** Paper Insulated and Varnished Cambric Insulated Cables.

If conductors are paper or varnished cambric insulated, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound... or waterproof insulating tape... Cable Runs, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage... **Yes** Are cables in machinery spaces, galleys, laundries, bathrooms and lavatories lead covered or run in conduit... **Lead covered**

Support and Protection of Cables, state how the cables are supported and protected... **Clipped to steel hangers and (or bulkheads) protected by sheet steel covers in holds.**

If cables are run in wood casings, are the casings and caps secured by screws... are the cap screws of brass... are the cables run in separate grooves... If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VIII... **A.I.E.E.**

Refrigerated Chambers, are the cables and fittings in accordance with the special requirements... **Yes** Junction boxes.

Joints in Cables, state if any, and how made, insulated, and protected... **Junction boxes**

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands... **Yes** Bushes in Beams and Non-watertight Partitions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed... state the material of which the bushes are made... **Cables efficiently grounded**

Earthing Connections, state what earthing connections are fitted and their respective sectional areas... **Cables efficiently grounded**

are their connections made as per Rule... **Yes**

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule... **Yes** Emergency Supply, state position and method of control of the emergency supply and how the generator is driven... **Emergency Supply**

Navigation Lamps, are these separately wired... **Yes** controlled by separate switch and separate fuses... **Yes** are the fuses double pole... **Yes** are the switches and fuses grouped in a position accessible only to the officers on watch... **Yes**

has each navigation lamp an automatic indicator as per Rule... **Yes** Secondary Batteries, are they constructed and fitted as per Rule... **Yes**

Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight... **Yes** are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected... **Yes**

are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected... **No** how are the cables led

where are the controlling switches situated... **Yes** are all fittings suitably ventilated... **Yes** are all switches and lampholders constructed wholly of non-ignitable, non-absorbent materials... **Yes**

Heating and Cooking Appliances, are they constructed and fitted as per Rule... are air heaters constructed and fitted as per Rule... **Yes**

Searchlight Lamps, No. of... **One** whether fixed or portable... **fixed** are their fittings as per Rule... **Yes**

Arc Lamps, other than searchlight lamps, No. of... are their live parts insulated from the frame or case... are their fittings as per Rule... **Yes**

Motors, are their working parts readily accessible... **Yes** are the coils self-contained and readily removable for replacement... **Yes** are the brushes, brush holders, terminals and lubricating arrangements as per Rule... **Yes** are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material... **Yes** are they protected from mechanical injury and damage from water, steam or oil... **Yes** are their axes of rotation fore and aft... if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type... **Totally enclosed**

if not of this type, state distance of the combustible material horizontally or vertically above the motors... **and**

have machines of over 100 BPH been inspected by the Surveyors during manufacture and testing... **Control Gear and Resistances**, are the generator field and motor speed regulators, starters and controllers constructed and fitted as per Rule... **A.I.E.E.** Lightning Conductors, where lightning conductors are required, are these fitted as per Rule... **Ships carrying Oil having a Flash Point less than 150°F.** Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings... are all fuses of the filled cartridge type... are they of an approved type... **Yes**

If portable lamps for use in dangerous spaces are supplied, are they of a self-contained, battery-fed type approved by the Home Office... **Yes**

Spare Gear, if the vessel is for open sea service have spares been supplied as per Rule... **Yes**

PARTICULARS OF GENERATING PLANT.									
DESCRIPTION OF GENERATOR	No. of	RATED AT				DRIVEN BY		WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.	
		Kilowatts.	Volts.	Amperes.	Revs. per Min.	Reciprocating steam engine		Fuel Used.	Flash Point of Fuel.
MAIN ...	3	20	120	167	400	Reciprocating steam engine			
AUXILIARY ...									
EMERGENCY ...									
ROTARY TRANSFORMER									

GENERATOR, LIGHTING AND HEATING CONDUCTORS.									
DESCRIPTION.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT AMPERES.		Approximate Length (Lead and Return) Feet.	Insulated with	HOW PROTECTED
	No. per Pole.	Total Nominal Area per Pole Sq. Ins.	No.	Diameter.	Circuit.	Rule.			
MAIN GENERATOR	3	250,000	37	82.2	167	280	50	Varn. Camb.	L.C. & armoured
EQUALISER CONNECTIONS	3	41,700	7	77.2	-	84	50	" "	" "
AUXILIARY GENERATOR			19	83.7	Accepted (See "Lara Beam")				
EMERGENCY GENERATOR					fitted as per 8515				
ROTARY (MOTOR TRANSFORMER) (GENERATOR)									
ENGINE ROOM and BOILER ROOM Lighting (L1)	1	66,400	7	97.4	58.36	83	120	" "	" "
AUXILIARY SWITCHBOARDS									
Boat dk. accom (L7)	1	106,000	19	83.7	48.42	184	190	" "	" "
Wheelhouse (L8)	1	26,300	7	61.2	12.42	46.5	240	" "	" "
Bridge dk. accom (L9)	1	106,000	19	83.7	48.17	184	200	" "	" "
ACCOMMODATION									
Amidship (L3)	1	106,000	19	83.7	56.67	184	190	" "	" "
Amidship (L4)	1	106,000	19	83.7	50.22	184	150	" "	" "
Aft deck house (L6)	1	66,400	7	97.4	24.36	83	440	" "	" "
WIRELESS	1	26,300	7	61.2	22.00	46.5	190	" "	" "
SEARCHLIGHT (L10)	1	10,400	7	38.5	4.16	25.5	420	" "	" "
MASTHEAD LIGHT	1	4,110	7	94.2	.42	13	440	" "	" "
SIDE LIGHTS	1	4,110	7	24.2	.42	13	110	" "	" "
COMPASS LIGHTS	1	4,110	7	24.2	1.67	13	-	" "	" "
PERISCOPE LIGHTS									
CARGO LIGHTS Fwd. (L2)	1	66,400	7	97.4	24.63	83	410	" "	" "
WATER TIGHT LAMPS Aft. (L5)	1	66,400	7	97.4	22.91	83	160	" "	" "
HEATERS									

MOTOR CONDUCTORS.										
DESCRIPTION.	No. of Motors.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT AMPERES.		Approximate Length (Lead and Return) Feet.	Insulated with	HOW PROTECTED
		No. per Pole.	Total Nominal Area per Pole Sq. Ins.	No.	Diameter.	In Circuit.	Rule.			
BALLAST PUMP										
MAIN BILGE LINE PUMPS										
GENERAL SERVICE PUMP										
EMERGENCY BILGE PUMP										
SANITARY PUMP										
CIRC. SEA WATER PUMPS										
CIRC. FRESH WATER PUMPS										
AIR COMPRESSOR										
FRESH WATER PUMP	2	1	4110	7	24.2	6.22	13	100	Varn. Camb.	L.C. & armoured
ENGINE TURNING GEAR										
ENGINE REVERSING GEAR										
LUBRICATING OIL PUMPS										
OIL FUEL TRANSFER PUMP										
WINDLASS										
WINCHES, FORWARD										
Refrigerator	1	1	83,700	19	66.4	59.39	134	200	" "	" "
WINCHES, AFT										
STEERING GEAR—										
(a) MOTOR GENERATOR										
(b) MAIN MOTOR										
WORKSHOP MOTOR										
VENTILATING FANS										

All Conductors are of annealed copper conforming to British Standard Specification No. 7 (or International Electro-technical Commission Publication No. 28).

The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.

The foregoing is a correct description.

..... Electrical Engineers.

Date.....

COMPASSES.

Distance between electric generators or motors and standard compass.....

Distance between electric generators or motors and steering compass.....

The nearest cables to the compasses are as follows:—

A cable carrying..... Ampères..... feet from standard compass..... feet from steering compass.

A cable carrying..... Ampères..... feet from standard compass..... feet from steering compass.

A cable carrying..... Ampères..... feet from standard compass..... feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power.....

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted.....

The maximum deviation due to electric currents was found to be..... degrees on..... course in the case of the standard compass, and..... degrees on..... course in the case of the steering compass.

..... Builder's Signature

Date.....

Is this installation a duplicate of a previous case..... If so, state name of vessel.....

General Remarks (State quality of workmanship, opinions as to class, &c.....)

The electrical installation on board the vessel was fitted to the plans approved by the American Bureau of Shipping in 1943 and plans available have been generally in accordance with the Rules. The materials and workmanship were satisfactory and the installation has been examined under full load, tested as per Rules, and found satisfactory. It is the opinion of the undersigned that the electrical installation is eligible to be classed with this Society.

Total Capacity of Generators..... 60..... Kilowatts.

The amount of Fee £ \$100.00 : { When applied for, 27/3/ 1947

Traveling Expenses (if any) £ : : { When received, 19.....

James Findlay
Surveyor to Lloyd's Register of Shipping.

Committee's Minute..... NEW YORK APR 16 1947 949

Assigned *Elec. Light*.....

Im-5-44.—Transfer. Printed in U.S.A.
(The Surveyors are requested not to write on or below the space for Committee's Minute)



© 2020

Lloyd's Register Foundation