

Rpt. 13.

No. 12516

REPORT ON ELECTRICAL EQUIPMENT.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

Received at London Office

Date of writing Report

19

When handed in at Local Office

12.5.39

Port of

TRIESTE

No. in Survey held at

Monfalcone

Date, First Survey

28.2.39

Last Survey

3.5.

1939

Reg. Book.

(Number of Visits.....5.....)

88666 on the

M. J. James J. Maguire

Tons

Gross 10525

Net 6065

Built at

Monfalcone

By whom built

Cant. Min. dell'Adm.

Yard No.

1207

When built

1939

Owners

Oriental Tanker Co.

Port belonging to

London

Electric Light Installation fitted by

C.R.D.A. Off. Elettromeccaniche

Contract No.

—

When fitted

1939

Is the Vessel fitted for carrying Petroleum in bulk

yes

System of Distribution

2 wire

Pressure of supply for Lighting

115

volts, Heating

—

volts, Power

115

volts.

Direct or Alternating Current, Lighting

direct

Power

direct

If alternating current system, state frequency of periods per second

—

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off

yes

Generators, do they comply with the requirements regarding temperature rise

yes

are they compound wound

yes

are they over compounded 5 per cent.

yes

if not compound wound state distance between each generator

—

Where more than one generator is fitted are they arranged to run in parallel

no

is an adjustable regulating resistance fitted in

series with each shunt field

yes

Have certificates of test results for machines under 100 kw. been submitted and

approved

yes

Have machines over 100 kw. been inspected by the Surveyors during manufacture and testing

—

Have certificates for generators under 100 kw. been supplied and approved

yes

(on Rating Plate Nos. 106278 & 106279)

Are all terminals accessible, clearly marked, and furnished with sockets

yes

are they so spaced or shielded that they cannot be accidentally earthed,

short circuited, or touched

yes

Are the lubricating arrangements of the generators as per Rule

yes

Position of Generators

in C.R. platform

is the ventilation

in way of the generators satisfactory

yes

are they clear of all inflammable material

yes

if situated near unprotected

woodwork or other combustible material, state distance of same horizontally from or vertically above the generators

—

and

are the generators protected from mechanical injury and damage from water, steam or oil

yes

are their axes of rotation fore and aft

yes

Earthing, are the bedplates and frames of the generating plant efficiently earthed

yes

are the prime movers and their respective generators

in metallic contact

yes

Main Switch Boards, where placed

near generators

If the generators and main switchboard are not placed in the same compartment, is each generator provided with

a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard

—

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes

yes

are they protected from mechanical

injury and damage from water, steam or oil

yes

if situated near unprotected woodwork or other combustible material, state distance of same

horizontally from or vertically above the switchboards

—

and

are they constructed wholly of durable, non-ignitable non-absorbent

materials

yes

is all insulation of high dielectric strength and of permanently high insulation resistance

yes

is it of an approved type

yes

if semi-insulating material is used, are all conducting parts insulated from the slab with mica or micanite or other

non-hygroscopic insulating material, and the slab similarly insulated from its framework

—

is the non-hygroscopic insulating material of an approved

type

yes

and is the frame effectively earthed

yes

Are the fittings as per Rule regarding:— spacing or shielding of live parts

accessibility of all parts

yes

absence of fuses on back of board

yes

temperature rise of

yes

omnibus bars

yes

individual fuses to voltmeter, pilot or earth lamp

yes

are moving parts of switches alive in the

“off” position

no

are all screws and nuts securing connections effectively locked

yes

are any fuses fitted on the live side of

switches

no

Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches

Double pole automatic air breaker for generators. Double pole air switch with fuse to each pole for all outgoing circuits. Are turbine driven generators fitted with emergency trip switch as per rule. Are cupboards or compartments containing switchboards composed of

fire-resisting material or lined with approved material

—

Instruments on main switchboard

4

ammeters

2

voltage

—

synchronising device for paralleling purposes. For compound machines is the ammeter connected on the opposite pole to equaliser connection

no equality

Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system

Contacts for Voltmeter & green & red lamps

Switches, Circuit Breakers and Fusible Cut-outs,


do these comply with the requirements of the Rules

yes

are the fusible cutouts of an approved type

yes

have the reversed



Lloyd's Register Foundation

003458-003465-0375 1/2

current protection devices been tested under working conditions *yes* are all fuses labelled as per rule *yes*

Joint Boxes, Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per rule *yes*

Cables: Single, twin, concentric, or multicore *imperfect* the cables insulated and protected as per Tables IV, V, X, XI, XII or XIII of the Rules *yes*

If the cables are insulated otherwise than as per Rule, are they of an approved type *yes* Fall of Pressure, state maximum between bus bars and any point of the installation under maximum load *5 Volts*

Cable Sockets, are the ends of all cables having a sectional area of 0.04 square inch and above provided with soldering sockets *yes*

Paper Insulated and Varnished Cambric Insulated Cables, If conductors are paper or varnished cambric insulated, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound *—*, or waterproof insulating tape *—*

Cable Runs, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage *yes* are cables laid under machines or floorplates *no* if so, are they adequately protected *—*

Are cables in machinery spaces, galleys, lavatories, bathrooms and lavatories lead covered *yes* or run in conduit *yes*

Support and Protection of Cables, state how the cables are supported and protected *steel plating & clips*

If cables are run in wood casings, are the casings and caps secured by screws *—*, are the cap screws of brass *—*, are the cables run in separate grooves *—* If *steel braided* and lead covered cables are secured by metal clips, are the clips spaced as per Table VIII *yes*

Refrigerated Chambers, are the cables and fittings in accordance with the special requirements *—*

Joints in Cables, state if any, and how made, insulated, and protected *WT junction boxes*

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands *yes*

Bushes in Beams and Non-watertight Partitions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently finished *yes* state the material of which the bushes are made *lead*

Earthing Connections, state what earthing connections are fitted and their respective sectional areas *—*, are their connections made as per Rule *—*

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule *yes* Emergency Supply, state position and method of control of the emergency supply and how the generator is driven *none*

Navigation Lamps, are these separately wired *yes*, controlled by separate switch and separate fuses *yes*, are the fuses double pole *yes*, are the switches and fuses grouped in a position accessible only to the officers on watch *yes*

has each navigation lamp an automatic indicator as per Rule *yes* Secondary Batteries, are they constructed and fitted as per Rule *yes*

are they ventilated as per Rule *yes*

Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight *yes* are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected *steel plates*

are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected *in Bridge*

Space above the Cargo Tank in tubes, how are the cables led *—*

where are the controlling switches situated *outside of space*

are all fittings suitably ventilated *yes*, are all switches and lampholders constructed wholly of non-inflammable, non-absorbent materials *yes*

Heating and Cooking Appliances, are they constructed and fitted as per Rule *none*, are air heaters constructed and fitted as per Rule *none*

Searchlight Lamps, No. of *1* whether fixed or portable *fixed*, are their fittings as per Rule *yes*

Motors, are their working parts readily accessible *yes*, are the coils self-contained and readily removable for replacement *yes*

are the brushes, brush holders, terminals and lubricating arrangements as per Rule *yes*, are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material *yes*

are they protected from mechanical injury and damage from water, steam or oil *yes* are their axes of rotation fore and aft *yes* if situated near unprotected ropework or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type *all motors drip proof*

, if not of this type, state distance of the combustible material horizontally or vertically above the motors *—* and *—*

have machines of over 100 BHP been inspected by the Surveyors during manufacture and testing *none* have certificates for all motors for essential services been supplied and approved *yes*

Control Gear and Resistances, are the generator field and motor speed regulators, starters and controllers constructed and fitted as per Rule *yes*

Lightning Conductors, where lightning conductors are required, are these fitted as per Rule *steel mast*

Ships carrying Oil having a Flash Point less than 150° F. Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings *yes*

are all fuses of the filled cartridge type *yes* are they of an approved type *yes*

If portable lamps for use in dangerous spaces are supplied, are they of a self-contained, battery-fed flameproof type approved for use in dangerous spaces *yes*

Spare Gear, if the vessel is for open sea service have spares been supplied as per Rule *yes* are they suitably stored in dry situations *yes*

PARTICULARS OF GENERATING PLANT.

DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.	
		Kilowatts.	Volts.	Ampères.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.
MAIN	2	30 x 2	115	261 x 2	375	Steam Engine		
AUXILIARY								
EMERGENCY								
ROTARY TRANSFORMER								

GENERATOR, LIGHTING AND HEATING CONDUCTORS.

DESCRIPTION.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
	No. per Pole.	Total Nominal Area per Pole Sq. Ins.	No.	Diameter.	Circuit.	Rule.			
MAIN GENERATOR	2	150	37	2.2	261	268	75	rubber	Lead covered & steel braided
EQUALISER CONNECTIONS									
AUXILIARY GENERATOR									
EMERGENCY GENERATOR									
ROTARY TRANSFORMER									
ENGINE ROOM With 23 Circuits	1	25 x 3 7/8	—	—	48	—	—	bare	Copper bars
BOILER ROOM	1	2 7/8	1	1.6	10	13	—	rubber	Lead covered & steel braided
AUXILIARY SWITCHBOARDS in Bridge Deck	1	120	37	2	141	180	500	"	" " " "
Upper Deck & Poop Stores	1	48	19	1.85	51	97	180	"	" " " "
	1	4	7	0.9	21	24	90	"	" " " "
ACCOMMODATION									
WIRELESS S.B.	1	15	7	1.60	20	46		"	Lead covered & steel braided
SEARCHLIGHT TEAM circuit	1	4	7	0.9	5	24		"	" " " "
MASTHEAD LIGHT	1	2.5	7	0.7	12	15		"	" " " "
SIDE LIGHTS	1	2.5	7	0.7	12	15		"	" " " "
COMPASS LIGHTS	1	2.5	7	0.7	14	15		"	" " " "
POOP LIGHTS	1	2.5	7	0.7	12	15		"	" " " "
CARGO LIGHTS	1	2.5	7	0.7	1	15		"	" " " "
HEATERS									

MOTOR CONDUCTORS.

DESCRIPTION.	No. of Motors.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
		No. Per Pole.	Total Nominal Area per Pole Sq. Ins.	No.	Diameter.	In Circuit.	Rule.			
BALLAST PUMP										
MAIN BILGE LINE PUMPS										
GENERAL SERVICE PUMP										
EMERGENCY BILGE PUMP										
SANITARY PUMP	1	1	2.5	7	0.70	5	15	45	rubber	Lead covered & steel braided
CIRC. SEA WATER PUMPS										
CIRC. FRESH WATER PUMPS										
AIR COMPRESSOR										
FRESH WATER PUMP	1	1	4	7	0.9	17	24	60	"	" " " "
ENGINE TURNING GEAR	1	1	35	19	1.60	78	90	90	"	" " " "
ENGINE REVERSING GEAR										
LUBRICATING OIL PUMPS	1	1	2.5	7	0.70	7	15	90	"	" " " "
OIL FUEL TRANSFER PUMP										
WINDLASS										
WINCHES, FORWARD										
WINCHES, AFT										
STEERING GEAR										
(a) MOTOR Generator	1	1	6	7	1.1	30	31	240	"	" " " "
(b) MOTOR Indicator	1	1	2.5	7	0.70	3	15	130	"	" " " "
WORKSHOP MOTOR	6	1	50	19	1.85	113	113	200	"	" " " "
BOILER FAN	2	1	97	37	1.85	157	157	90	"	" " " "
GALLEY S.B.		1	70	19	2.15	132	132	240	"	" " " "
REFRIG. ENG. S.B.	3	1	25	19	1.3	59	64	210	"	" " " "
CHORE CONN S.B.	—	—	185	37	2.5	200	232	120	"	" " " "

The Electrical Equipment is installed in accordance with the approved plans.

All Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.

The foregoing is a correct description.

CANTIERI RIUNITI DELL' ADRIATICO
Officine Elettromeccaniche

By R. di Lufan Electrical Engineers.

Date 10/5/39

COMPASSES.

Minimum distance between electric generators or motors and standard compass

} 250' - 0"

Minimum distance between electric generators or motors and steering compass

The nearest cables to the compasses are as follows:—

A cable carrying 20 Ampères 12 feet from standard compass 16 feet from steering compass.

A cable carrying Ampères feet from standard compass feet from steering compass.

A cable carrying Ampères feet from standard compass feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power yes

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted yes

The maximum deviation due to electric currents was found to be nil degrees on — course in the case of the standard compass, and — degrees on — course in the case of the steering compass.

CANTIERI RIUNITI DELL' ADRIATICO
Officine Elettromeccaniche

By R. di Lufan Builder's Signature.

Date 10/5/39

Is this installation a duplicate of a previous case yes If so, state name of vessel Edwy Brown & John A Brown

General Remarks (State quality of workmanship, opinions as to class, &c.)

This installation has been made in accordance with the Rules, approved plans and factory letters. The material and workmanship are good. The installation has been tested on board complete under full load condition and also tested for insulating condition and found in order.

Noted
L. J.
25/5/39

Total Capacity of Generators 60 Kilowatts.

The amount of Fee ...

£ 25 36

When applied for,

13/5/39

When received,

25. 5. 1939

Travelling Expenses (if any) £

Committee's Minute

Assigned

See Tri. 36. 12516

R. Luparier
Surveyor to Lloyd's Register of Shipping