

Received by Chief Ship Surveyor

Received from Chief Ship Surveyor

ESSEL'S NAME Stl T.S. M.V. PORT. FREMANTLERpt. Bel No. 9717

The remarks of the Chief Ship Surveyor are desired on this case for the consideration of the Classing Committee.

("The endorsement to contain a succinct summary of any repairs that have been required and to show the cause or causes of such repairs, and also to bring out clearly any exceptional features in connection with the case, so that the Classing Committee may have all the salient points presented in the endorsement."—Extract from Sub-Committee's Report, 24/5/92.)


1st Long
 Transverse No. 20328 Depth "d" 18.7

Framing: Table No. _____ Description Channel frames with revised frames as approved

2nd Longitudinal No. 50284 Proportions $\frac{\text{Length}}{\text{Depth}} = \underline{10.97}$

Deck Sheerstrake as approved

Revised Rules



This vessel appears to have been built in accordance with the Rules and the approved plans, and it is submitted she is eligible to be classed **✠ 100 A.1. (Steel)** "with freeboard," as recommended. The Summer freeboard of 6ft - 0in from centre of disc to top of statutory deck line at _____ deck, now marked on the vessel's sides, to be inserted in the classification certificate, and recorded in the Register Book, and further, the remaining freeboards, as shown on the accompanying verification form to be inserted in the certificate of classification.

2 D^{ks} (Stl) + Shelter Dk (Stl - ws)


Cell D.B. 405' 16585, A.P.T. 1005.

F.K. duct keel forward of machinery space 15ft.

8 B.H. (Coll B.H to shelter Dk, 7 B.H to 2nd D^k), ft am, Lloyd's A.C.P.

F 52'.

003549-003555-0120 1/2



© 2020

Lloyd's Register Foundation

P.T.O.

Concluded the thickness of the lowest strake of the Collision bulkhead
is as approved but the surveyor should be requested to state if
is so.

Surveyor should also be requested to state whether the record for the repairs
should be "ft rem ft asp"

See letter
12-4-27

S
12-4-27

IN SHIP	
1/2	46
1/2	46
"	"
	64
1/2	60
	70
	46
	60
	50
	50
	51
	58
	046
	36
	50
	60



© 2020

Lloyd's Register
Foundation

0120 1/2