

1	124	75	28	5	105	100	105	5	-	
7	77	75	28	5	77	63	63	14	14	
11	66	66	66	18	66	51	48*	16	18	* - renewed
2	66	74	61	18	66	63	48*	3	18	or doubled.
8	66	66	66	18	66	61	58	5	8	
3	80	66	74	3	80	77	73	3	7	
6	80	78	78	2	10th May, 1957.					
7	76	63	13	13	76	71	73	5	3	
11	76	70	6	6	76	71	62	5	14	
2	76	51*	15	15	76	62	56	14	20	
8	84	60*	22	22	84	54*	30			

451, 78, 96, 503 - As recommended. et to sternframe solepiece
 (10,54) being specially examined next drydocking
 "STAWAC SYDNEY" As recommended, except that a record of TS centre
 has been assigned. I shall be glad if in this and in future
 or cases you will furnish to worn minimum mean diameter of
 main cable recommended to be renewed. report (11,55) that the
 lined in dry dock, bottom coated and the requirements of
 4338 - As recommended. S. complied with.

On account of wear and tear during operation in
 bottom and side shell plating, structure in all of cargo hold
 the report, the cargo hold is to be
 tied out to the side of the
 required to be replaced
 ed in the cargo hold



© 2020

Lloyd's Register
 Foundation

003631-003639-0103

003631-003639-0104/12