



REQUIREMENTS OF SECTION 20 OF THE SHIP RULES TO BE COMPLIED WITH WHERE APPLICABLE.
FLASH POINT OF THE OIL FUEL NOT TO BE LOWER THAN 150°F
MASTS, WINCHES, VINGERS, STEERING GEAR AND DONKEY BOILER TO BE SUPPORTED TO
SURVEYORS SATISFACTION.

SKETCH OF FORE PEAK
AND ENGINE ROOM TO BE
SUBMITTED FOR APPROVAL
ALSO COVER STEAM AND FRESH WATER
PIPING

NOTE:
SINGLE RIVETED OVERLAPPED BUTTS MARKED +
DOUBLE
THREE-PLATE
QUADRUPLE-PLATE

DIMENSIONS:
LENGTH 100' 0" 100' 0" 100' 0"
BREADTH MOULDED 35' 0" 35' 0" 35' 0"
DEPTH MOULDED 35' 0" 35' 0" 35' 0"

ALL BULBS/LES N.B. 38A 1924
OR GERMAN STANDARDS 1927

CLASS:
LOYD'S 100 A1 CARRYING PETROLEUM IN BULK

Solihullburg 1st July 1915
NORDANVIR

AKTIEBOLAGET GOTAVÄRKEN		REK. NO.
438		438
LONGITUDINAL SECTION AND PLANS (to bulk)		
BY	SCALE 1:100	DATE 27.7.15
BY	SCALE 1:100	DATE 27.7.15
BY	SCALE 1:100	DATE 27.7.15