

REPORT ON ELECTRIC FITTINGS.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

Received at London Office 10 APR 1935

Date of writing Report 25-3-1935. When handed in at Local Office

19

Port of

Rotterdam

No. in Survey held at Rotterdam Date, First Survey 2-1-35 Last Survey 5-3-1935

Reg. Book.

(Number of Visits 10)

on the M.T. Rapana

Tons

Gross 7986

Net 4754

Built at Rotterdam By whom built Werf Wilton Yard No. 654 When built 1934-35.

Owners Anglo Saxon Petroleum Comp. Port belonging to Gravenhage

Electric Light Installation fitted by N.V. Electrotechn. Bur. A. de Hoop. Contract No. When fitted 1934-35.

Is the Vessel fitted for carrying Petroleum in bulk yes

System of Distribution Two wire

Pressure of supply for Lighting 110 volts. Heating — volts. Power 110 volts.

Direct or Alternating Current, Lighting direct current Power direct current

If alternating current system, state frequency of periods per second

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off yes

Generators, do they comply with the requirements regarding rating yes, are they compound wound yes

are they over compounded 5 per cent. yes, if not compound wound state distance between each generator

Where more than one generator is fitted are they arranged to run in parallel no, is an adjustable regulating resistance fitted in series with each shunt field yes

Are all terminals accessible, clearly marked, and furnished with sockets yes, are they so spaced or shielded that they cannot be accidentally earthed, short circuited, or touched yes Are the lubricating arrangements of the generators as per Rule yes

Position of Generators in motorroom

is the ventilation in way of the generators satisfactory yes, are they clear of all inflammable material yes

if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the generators and, are the generators protected from mechanical injury and damage from water, steam or oil yes

are their axes of rotation fore and aft yes

Earthing, are the bedplates and frames of the generating plant efficiently earthed yes are the prime movers and their respective generators in metallic contact yes

Main Switch Boards, where placed in motorroom

If the generators and main switchboard are not placed in the same compartment, is each generator provided with a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes yes

are they protected from mechanical injury and damage from water, steam or oil yes, if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the switchboards and

are they constructed wholly of durable, non-ignitable non-absorbent materials yes, is all insulation of high dielectric strength and of permanently high insulation resistance yes, if semi-insulating material is used, are all conducting parts insulated from the slab

with mica or micanite or other non-hygroscopic insulating material, and the slab similarly insulated from its framework and is the frame effectually earthed yes

Are the fittings as per Rule regarding: — spacing or shielding of live parts yes, accessibility of all parts yes, absence of fuses on back of board yes, proportion of omnibus

bars yes, individual fuses to voltmeter, pilot or earth lamp yes, connections of switches yes

Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches For each dynamo:

one main double pole circuit breaker and double pole fuses.

For each outgoing circuit a double pole change over switch and double pole fuses


Instruments on main switchboard 2 ammeters 2 voltmeters synchronising device for paralleling purposes.

Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system

earth lamps

Switches, Circuit Breakers and Fusible Cut-outs, do these comply with the requirements of the Rules yes

Joint Boxes Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per rule yes



Lloyd's Register Foundation

003824-003831-0168 1/2

Cables: Single, twin, concentric, or multicore single and twin are the cables insulated and protected as per Tables IV or V of the Rules yes

Fall of Pressure, state maximum between bus bars and any point of the installation under maximum load 2 volt

Cable Sockets and other connections, are the ends of all cables having a sectional area of 0.04 square inch and above provided with soldering sockets yes

Paper Insulated Cables. If cables are paper covered, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound

Cable Runs, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage yes

Support and Protection of Cables, state how the cables are supported and protected Supported by metal clips and protected by tubes and armouring

If cables are run in wood casings, are the casings and caps secured by screws, are the cap screws of brass, are the cables run in separate grooves. If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VIII yes

Refrigerated Chambers, if lights are fitted, are the cables and fittings in accordance with the special requirements yes

Joints in Cables, state if any, and how made, insulated, and protected

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands yes

Bushes in Beams and Non-watertight Partitions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed yes state the material of which the bushes are made Lead

Earthing Connections, state what earthing connections are fitted and their respective sectional areas

are their connections made as per Rule

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule yes

Emergency Supply, state position and method of control of the emergency supply and how the generator is driven

Navigation Lamps, are these separately wired yes, controlled by separate switch and separate fuses yes, are the fuses double pole yes, are the switches and fuses grouped in a position accessible only to the officers on watch yes, has each navigation lamp an automatic indicator as per Rule yes

Secondary Batteries, are they constructed and fitted as per Rule

Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight yes, are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected

are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected fitted in gas-tight boxes, how are the cables led in gas-tight tubes

where are the controlling switches situated in chartroom

Searchlight Lamps, No. of 1, whether fixed or portable portable, are their fittings as per Rule yes

Arc Lamps, other than searchlight lamps, No. of, are their live parts insulated from the frame or case, are their fittings as per Rule

Motors, are their working parts readily accessible yes, are the coils self-contained and readily removable for replacement yes, are the brushes, brush holders, terminals and lubricating arrangements as per Rule yes, are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material yes, are they protected from mechanical injury and damage from water, steam or oil yes, are their axes of rotation fore and aft yes, if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type, if not of this type, state distance of the combustible material horizontally or vertically above the motors and

Control Gear and Resistances, are the generator field and motor speed regulators, starters and controllers constructed and fitted as per Rule yes

Lightning Conductors, where lightning conductors are required, are these fitted as per Rule yes

Ships carrying Oil having a Flash Point less than 150° F. Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings yes

If portable lamps for use in dangerous spaces are supplied, are they of a type approved by the Home Office

PARTICULARS OF GENERATING PLANT.										
DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.			
		Kilowatts.	Volts.	Ampères.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.		
MAIN ...	1	16.40	110	145	390	Steam engine	Scrubland Forge			
AUXILIARY ...	1	16.40	110	145	390	Diesel motor	Rustin Hornby			
EMERGENCY ...										
ROTARY TRANSFORMER										
									Renewed 7.23 June. 10/1458.	
									1.	
GENERATOR, LIGHTING AND HEATING CONDUCTORS.										
DESCRIPTION.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT. AMPERES.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.	
	No. per Pole.	Total Effective Area per Pole Sq. Ins. 7/25	No.	Diameter.	In Circuit.	Rule.				
MAIN GENERATOR ...	1	95	19	2.53	145	152	50	rubber	Lead covered and armoured	
EQUALISER CONNECTIONS										
AUXILIARY GENERATOR...	1	95	19	2.53	145	152	50			
EMERGENCY GENERATOR										
ROTARY TRANSFORMER { MOTOR GENERATOR...										
ENGINE ROOM...	1	1.5	1	1.39	3	7.7	75			
BOILER ROOM...										
AUXILIARY SWITCHBOARDS										
Motor room	1	10	7	1.35	37	38	50			
Cargo Lights	1	10	7	1.35	12	38	480			
Navigation	1	10	7	1.35	6	38	480			
Forecastle	1	16	7	1.71	13	48	720			
Aft	1	16	7	1.71	36	48	70			
ACCOMMODATION ...	1	1.5	1	1.39	1.5	7.7	90			
Saloon	1	16	7	1.71	30	4.8	480		Lead covered and armoured	
WIRELESS	1	16	7	1.71	15	48	480			
SEARCHLIGHT	1	35	19	1.53		78	850			
MASTHEAD LIGHT	1	1.5	1	1.39	1.5	7.7	360			
SIDE LIGHTS	1	1.5	1	1.39	0.5	7.7	90			
COMPASS LIGHTS	1	1.5	1	1.39	0.2	7.7	60			
POOP LIGHTS	1	1.5	1	1.39	0.5	7.7	820			
CARGO LIGHTS	1	1.5	1	1.39	2	7.7	80			
ARC LAMPS										
HEATERS										
MOTOR CONDUCTORS.										
DESCRIPTION.	No. of Motors.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT. AMPERES.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
		No. Per Pole.	Total Effective Area per Pole Sq. Ins. 7/25	No.	Diameter.	In Circuit.	Rule.			
BALLAST PUMP										
MAIN BILGE LINE PUMPS										
GENERAL SERVICE PUMP										
EMERGENCY BILGE PUMP										
SANITARY PUMP										
CIRC. SEA WATER PUMPS										
CIRC. FRESH WATER PUMPS...										
AIR COMPRESSOR										
FRESH WATER PUMP										
ENGINE TURNING GEAR...	1	1	70	19	2.17	120	148	90	rubber	Lead covered and armoured
ENGINE REVERSING GEAR										
LUBRICATING OIL PUMPS										
OIL FUEL TRANSFER PUMP...										
WINDLASS										
WINCHES, FORWARD										
WINCHES, AFT										
STEERING GEAR—										
(a) MOTOR GENERATOR...										
(b) MAIN MOTOR										
WORKSHOP MOTOR										
VENTILATING FANS										
Separator	1	1	4	7	0.86	16	21	90		
Drill	1	1	4	7	0.86	16	21	72		
Lathe	1	1	2.5	1	1.79	12	15	86		
Grinding mach.	1	1	6	7	1.05	24	28	30		
Trim pump	1	1	6	7	1.05	24	28	110		
Aux. switch board workshop	1	35	19	1.53	65	78	165			

All Conductors are of annealed copper conforming to British Standard Specification No. 7.

The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.

The foregoing is a correct description.

N.V. Electrotechn. Bureau A. de Hoop.

Electrical Engineers.

Date 25-2-'35

COMPASSES.

Distance between electric generators or motors and standard compass 300 ft

Distance between electric generators or motors and steering compass 200 ft

The nearest cables to the compasses are as follows:—

A cable carrying 0.2 Ampères 2 feet from standard compass 2 feet from steering compass.

A cable carrying Ampères feet from standard compass feet from steering compass.

A cable carrying Ampères feet from standard compass feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power Yes

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted Yes

The maximum deviation due to electric currents was found to be nihil degrees on every course in the case of the standard compass, and nihil degrees on any course in the case of the steering compass.

WILTON FIJENOORD.

(N.V. WILTON's Machinefabriek en Scheepswerf
(WILTON's Engineering and Shipyard)
Wijk aan Zee, Holland.
"FIJENOORD" N.V.)

Builder's Signature.

Date

Is this installation a duplicate of a previous case yes If so, state name of vessel M.T. Sunetta.
Platt Rep No 23510 E

General Remarks (State quality of workmanship, opinions as to class, &c. The installation has been fitted in accordance with the Society's

Rules, approved plans and Secretary's letters, material tested as required and workmanship good. It has been tested and found working satisfactorily during a trial and merits in my opinion the approval of the Committee

Noted

11/4/35

Total Capacity of Generators 32 Kilowatts.

The amount of Fee £ 276.1

When applied for, 6.4.1935

Travelling Expenses (if any) £

When received, 14.5.35

Surveyor to Lloyd's Register of Shipping.

Committee's Minute

FRI. 12 APR 1935

Assigned

See Ref. 7E 236024



© 2020

Lloyd's Register Foundation