

REPORT ON ELECTRIC FITTINGS.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL) 12 MAR 1931

Date of writing Report 6th March 1931 When handed in at Local Office 10 Port of Copenhagen

No. in Survey held at Elsinore Date, First Survey 29th Dec 1929 Last Survey 26th February 1931

Reg. Book. 89470 on the Steel S. ALEXANDRA (Number of Visits 12) Tons Gross 1462.61
Net 765.92

Built at Elsinore By whom built Msk. Helsingør Jernskibs- og Maskinbyggeri Yard No. 200 When built 1931

Owners Det Forenede Dampskibs Selskab Port belonging to Esbjerg

Electric Light Installation fitted by Msk. Helsingør Jernskibs- og Maskinbyggeri Contract No. When fitted 1931

Is the Vessel fitted for carrying Petroleum in bulk No

System of Distribution Two wire direct current

Pressure of supply for Lighting 110 volts, Heating volts, Power 110 volts.

Direct or Alternating Current, Lighting direct current Power direct current

If alternating current system, state frequency of periods per second

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off yes

Generators, do they comply with the requirements regarding rating yes, are they compound wound yes

are they over compounded 5 per cent. yes, if not compound wound state distance between each generator

Where more than one generator is fitted are they arranged to run in parallel , is an adjustable regulating resistance fitted in series with each shunt field yes

Are all terminals accessible, clearly marked, and furnished with sockets yes, are they so spaced or shielded that they cannot be accidentally earthed, short circuited, or touched yes Are the lubricating arrangements of the generators as per Rule yes

Position of Generators In the engine room

is the ventilation in way of the generators satisfactory yes, are they clear of all inflammable material yes

if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the generators 1.5 meter vertically above, are the generators protected from mechanical injury and damage from water, steam or oil yes

are their axes of rotation fore and aft yes

Earthing, are the bedplates and frames of the generating plant efficiently earthed yes are the prime movers and their respective generators in metallic contact yes

Main Switch Boards, where placed In the engine room

If the generators and main switchboard are not placed in the same compartment, is each generator provided with a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes yes

are they protected from mechanical injury and damage from water, steam or oil yes, if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the switchboards Not situated near unprotected work

are they constructed wholly of durable, non-ignitable non-absorbent materials yes, is all insulation of high dielectric strength and of permanently high insulation resistance yes, if semi-insulating material is used, are all conducting parts insulated from the slab with mica or micanite or other non-hygroscopic insulating material, and the slab similarly insulated from its framework yes

and is the frame effectively earthed yes Are the fittings as per Rule regarding: — spacing or shielding of live parts

yes, accessibility of all parts yes, absence of fuses on back of board yes, proportion of omnibus bars yes, individual fuses to voltmeter, pilot or earth lamp yes, connections of switches yes

Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches

For the generator: A double pole switch and a double pole fuse


For each outgoing circuit: A double pole switch and a double pole fuse

Instruments on main switchboard 1 ammeters 1 voltmeters synchronising device for paralleling purposes.

Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system 2 earth testing lamps

Switches, Circuit Breakers and Fusible Cut-outs, do these comply with the requirements of the Rules yes

Joint Boxes Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per rule yes



Cables: Single, twin, concentric, or multicore *Single & twin* are the cables insulated and protected as per Tables IV or V of the Rules *Table IV*.

Fall of Pressure, state maximum between bus bars and any point of the installation under maximum load *3 Bars*

Cable Sockets and other connections, are the ends of all cables having a sectional area of 0.04 square inch and above provided with soldering sockets *ye.*

Paper Insulated Cables. If cables are paper covered, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound *ye.*

Cable Runs, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage *ye.*

Support and Protection of Cables, state how the cables are supported and protected *Lead covered and steel wire armoured cables used, supported by clips, and where necessary protected by steel tubes*

If cables are run in wood casings, are the casings and caps secured by screws *ye.*, are the cap screws of brass *ye.*, are the cables run in separate grooves *ye.* If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VIII *ye.*

Refrigerated Chambers, if lights are fitted, are the cables and fittings in accordance with the special requirements *ye.*

Joints in Cables, state if any, and how made, insulated, and protected *No joints in cables*

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands *ye.*

Bushes in Beams and Non-watertight Partitions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed *ye.* state the material of which the bushes are made *lead*

Earthing Connections, state what earthing connections are fitted and their respective sectional areas *ye.*

are their connections made as per Rule *ye.*

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule *ye.*

Emergency Supply, state position and method of control of the emergency supply and how the generator is driven *ye.*

Navigation Lamps, are these separately wired *ye.*, controlled by separate switch and separate fuses *ye.*, are the fuses double pole *ye.* are the switches and fuses grouped in a position accessible only to the officers on watch *ye.*

has each navigation lamp an automatic indicator as per Rule *ye.*

Secondary Batteries, are they constructed and fitted as per Rule *ye.*

Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight *ye.* are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected *The stumps in the holds are fitted under the deck, enclosed in glass globe, protected by heavy gun iron* are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected *ye.*

how are the cables led *ye.*

where are the controlling switches situated *ye.*

Searchlight Lamps, No. of *ye.*, whether fixed or portable *ye.*, are their fittings as per Rule *ye.*

Are Lamps, other than searchlight lamps, No. of *ye.*, are their live parts insulated from the frame or case *ye.*, are their fittings as per Rule *ye.*

Motors, are their working parts readily accessible *ye.*, are the coils self-contained and readily removable for replacement *ye.* are the brushes, brush holders, terminals and lubricating arrangements as per Rule *ye.*, are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material *ye.*

are they protected from mechanical injury and damage from water, steam or oil *ye.* are their axes of rotation fore and aft *ye.* if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type *Not situated near wood* not of this type, state distance of the combustible material horizontally or vertically above the motors *ye.* and *ye.*

Control Gear and Resistances, are the generator field and motor speed regulators, starters and controllers constructed and fitted as per Rule *ye.*

Lightning Conductors, where lightning conductors are required, are these fitted as per Rule *ye.*

Ships carrying Oil having a Flash Point less than 150° F. Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings *ye.*

If portable lamps for use in dangerous spaces are supplied, are they of a type approved by the Home Office *ye.*

PARTICULARS OF GENERATING PLANT.

DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.	
		Kilowatts.	Volts.	Ampères.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.
MAIN	1	10	110	91	500	Vertical steam engine		
AUXILIARY								
EMERGENCY								
ROTARY TRANSFORMER								

GENERATOR, LIGHTING AND HEATING CONDUCTORS.

DESCRIPTION.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT.		Approximate Length. (Lead and Return.) Feet. <i>ft.</i>	Insulated with	HOW PROTECTED.
	No. per Pole.	Total Effective Area per Pole Sq. Ins. <i>sq. ins.</i>	No.	Diameter. <i>dia.</i>	In Circuit.	Rule.			
MAIN GENERATOR	1	50	19	1.83	91	98.3	4	Vulcanized rubber	Lead covered and steel wire armoured
EQUALISER CONNECTIONS									
AUXILIARY GENERATOR									
EMERGENCY GENERATOR									
ROTARY TRANSFORMER MOTOR GENERATOR									
ENGINE ROOM	1	2.5	7	0.67	14	15.5	6	"	"
BOILER ROOM									
AUXILIARY SWITCHBOARDS									
ACCOMMODATION SALOON	1	16	7	1.70	19	48.7	100	"	"
OFFICERS	1	4	7	0.85	13	22	50	"	"
AFT	1	4	7	0.85	8	22	70	"	"
LAMPS IN HOLDS	1	6	7	1.05	17	28.7	50	"	"
WIRELESS NAVIGATION LAMPS	1	10	7	1.35	22	38	110	"	"
SEARCHLIGHT	1	2.5	7	0.67	13	15.5	110	"	"
MASTHEAD LIGHT	1	1.5	1	1.38	10.3	10	100-160	"	"
SIDE LIGHTS	1	1.5	1	1.38	10.3	10	20-20	"	"
COMPASS LIGHTS	1	1.5	1	1.38	10.13	10	4-8	"	"
POOP LIGHTS	1	1.5	1	1.38	10.3	10	160	"	"
CARGO LIGHTS									
ARC LAMPS									
HEATERS									

MOTOR CONDUCTORS.

DESCRIPTION.	No. of Motors.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT.		Approximate Length. (Lead and Return.) Feet. <i>ft.</i>	Insulated with	HOW PROTECTED.
		No. Per Pole.	Total Effective Area per Pole Sq. Ins. <i>sq. ins.</i>	No.	Diameter. <i>dia.</i>	In Circuit.	Rule.			
BALLAST PUMP										
MAIN BILGE LINE PUMPS										
GENERAL SERVICE PUMP										
EMERGENCY BILGE PUMP										
SANITARY PUMP										
CIRC. SEA WATER PUMPS										
CIRC. FRESH WATER PUMPS										
AIR COMPRESSOR										
FRESH WATER PUMP	1	1	1.5	1	1.38	6	10	10	varnished lead covered steel wire armoured	
ENGINE TURNING GEAR										
ENGINE REVERSING GEAR										
LUBRICATING OIL PUMPS										
OIL FUEL TRANSFER PUMP										
WINDLASS										
WINCHES, FORWARD										
WINCHES, AFT										
STEERING GEAR—										
(a) MOTOR GENERATOR										
(b) MAIN MOTOR										
WORKSHOP MOTOR										
VENTILATING FANS										
REFRIGERATING MACH.	1	1	1.5	1	1.38	4	10	14	"	"

RETAIN

RETAIN

All Conductors are of annealed copper conforming to British Standard Specification No. 7.
The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.
The foregoing is a correct description.

AKTIESELSKABET
HELSINGØRS JERNSKIBS- OG MASKINBYGGERI Electrical Engineers.

Date 9. MRS. 1931

COMPASSES.

Distance between electric generators or motors and standard compass 30 meters

Distance between electric generators or motors and steering compass 30 meters

The nearest cables to the compasses are as follows:—

A cable carrying 2 Ampères 6 feet from standard compass 4 feet from steering compass.

A cable carrying 0.13 Ampères to lamp 12 feet from standard compass and in feet from steering compass.

A cable carrying Ampères feet from standard compass feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power yes.

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted yes.

The maximum deviation due to electric currents was found to be 0 degrees on all course in the case of the standard

compass, and 0 degrees on all course in the case of the steering compass.

AKTIESELSKABET
HELSINGØRS JERNSKIBS- OG MASKINBYGGERI Builder's Signature.

Date 9. MRS. 1931

Is this installation a duplicate of a previous case No If so, state name of vessel

General Remarks (State quality of workmanship, opinions as to class, &c. The electric installation as above)

described has been fitted in accordance with the Rules, the approved plan and the requirements contained in the Secretary's letter E dated 5th December 1930. The material used and the workmanship are of good description. The electric installation has been tested under full power working condition and found satisfactory.

It is submitted that this vessel is eligible for THE RECORD.

Elec light
JMA 13/3/31

Recommend the vessel to have notation of ELECTRIC LIGHT in the Register Book

Total Capacity of Generators 10 Kilowatts.

The amount of Fee £ 182.00 : When applied for, 10.3.1931

Travelling Expenses (if any) £ : : When received, 11.4.1931

ASBY
A.C. Jensen
Surveyor to Lloyd's Register of Shipping.

WED. 8 APR 1931

Committee's Minute

Assigned

Elec light



© 2020

Lloyd's Register Foundation

Im. 11.22.—Transfer.
(The Surveyors are requested not to write on or below the space for Committee's Minute.)