Preliminary

Index No.
(For London Office only.)

Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD.

Ship Nos 18 & 19

PARTICULARS IN RESPECT OF STEAM SHIPS HAVING SPAR OR AWNING DECKS.

Port of Survey Bilbao
Date ~~of Survey~~ 17. 3. 20
Name of Surveyor

Espanola Bilbao

Ship's Name.	Port of Registry and Nationality.	Official Number.	Gross Tonnage.	Date of Build.	Particulars of Classification.
No 25 in Register Book					100 A1 Awning deck with fbd. contemp.

Length.	Breadth.	Depth.	Under Deck Tonnage.
	43.2 ex.		
280.02	Frame Depth 6 Rule „ 5½	Ceiling Sheer — .21	Peak Tanks

Moulded Depth as measured 18-9¼ Main Deck.
„ „ „ 26-9 Spar or Awning Deck.

NOTE.—If the depth is measured when vessel is afloat, the details of measurement should be reported.

...ient of fineness ..... given as .773
...odification necessary ...ra. 4 (a) to (e)*]
...ient as corrected ..... Say .78

...nce for strength in excess of Lloyd's rules =

...articulars—

CORRECTION FOR LENGTH :—

Length of Ship on Load Line	280.02
Length in Table	225.25
Difference	54.77
Correction for 10ft.	.6
× Difference ÷ 10 =	3.2862
	+ 3¼

Height of 'Tween Decks 7-11¾
(From top of beam to top of beam at side)
Correction for Height of 'Tween Decks in Spar-decked Ships .....

Freeboard Table ~~B or~~ C	1-1½
Correction for Length	+ 3¼
	1-4¾
Correction for Height of 'Tween Decks ~~in Spar-decked Ships~~	7-11¾
	9-4½
Correction for Strength in excess of Lloyd's rules	2-11½
	6-5
Correction for Iron Deck if required	— 3½
	6-1½
Other Corrections (if any)	—

16.75 ÷ .55 = 30.45
38.00
36) 7.55
.21

Stem ..... 38 } 28½ mean at ⅛ length from Stem ..... 23 5/8 } 16.75 mean
Sternpost... 19 } „ „ „ Sternpost... 9 7/8 }
Drop in Sheer abaft amidships.....

Winter Freeboard (4)	6-1½
Summer Freeboard	5-9½
Indian Summer Freeboard	5-5½
N. A. Winter Freeboard	6-3½

...f Spar-deck Beam.....
..., Main-deck „ .....

	Length	× Height.	State if open or closed at ends.
...e	26.25 ×	7-6	
.....	68.25 ×	8-0	
.....	31.50 ×	7-6	

Correction necessary because clearside amidships measured in accordance with the Statute is not taken at intersection of the ~~wood or~~ iron deck with side } 1¾

Winter Freeboard from Deck Line	6-3¼
Summer „ „ „	5-11¼
Indian Summer „ „	5-7¼
N.A. Winter „ „ „	6-5¼

...ARD recommended amidships from centre of Disc to top of Statutory Deck Line, ~~Wood~~ (Iron) Awning Deck :— 5-11"

Fresh Water Line	above centre of Disc	5½
Indian Summer Line	„ „ „	4
Winter Line	below „ „	4
Winter North Atlantic Line	„ „ „	6

26-11¼
8-11½
7-11¾

...TE.—All vessels equal in strength to Lloyd's Spar-decked rule, or which, although in excess of that rule, do not come up to Lloyd's requirements for Ships of full scantlings to the upper deck, are to be considered as Spar-decked Ships, the freeboard for which will vary with their strength.
All vessels equal in strength to Lloyd's Awning-decked rule, or which, although in excess of that rule, do not come up to Lloyd's requirements for a Spar-decked Vessel, are to be considered as Awning-decked Ships, the freeboard for which will vary with their strength.

* If the frames, skin planking, or ceiling are of unusual thickness the breadth of vessel to inside of ceiling should be reported if possible.

P.T.O.

26-11¼
21-0
5-11¼

© 2020 Lloyd's Register Foundation

004321-004325-0114