Rpt. 11c.

B.T. COPY

Index No. 283
(For London Office only.)

Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD.

PARTICULARS IN RESPECT OF STEAM SHIPS HAVING SPAR OR AWNING DECKS.

Port of Survey

Date of ~~Survey~~ 30th January 33.

Name of Surveyor

Ship's Name.	Port of Registry and Nationality.	Official Number.	Gross Tonnage.	Date of Build.	Particulars of Classification.
AFRICAN MARINER. "~~BOIS SOLEIL~~" Gillett's Tubeless S.B.Co No 10 Number in Register Book	LONDON ~~French~~ BRITISH	144428	6.554	1919-12	✠ 100A1 Shelter Dk with freeboard

	Length.	Breadth.	Depth.	Under Deck Tonnage.
Registered Dimensions from Ship's Register.	412.5	55.65	34.5	6222.40
Length on Loadline	411.6	Frame Depth 4½ Rule " 7/72 7½×2=15 = .1.25	Ceiling +.20 Sheer +.08 No ceiling fitted Tank top limit	Peak Tanks (included) Cruiser Stern -22 Frame Transom -33 Double bottom raised H.T. under +.80
Corrected Dimensions.	411.6	54.4	34.78	6245.40

Moulded Depth as measured 28'-8¾" Main Deck.

" " " 38'-1½" Complete Shelter ~~Spar or Awning~~ Deck.

Underside of keel below base line = 1 5/8"

Addition for Keel below base line for draught record.....inches.

NOTE.—If the depth is measured when vessel is afloat, the details of measurement should be reported.

Co-efficient of fineness ..... .80

Any modification necessary [Para. 4 (a) to (e)*] } -.02 C.D.B.

Co-efficient as corrected ..... .78 say .76 to upper Dk

CORRECTION FOR LENGTH :—

Length of Ship on Load Line..... 411.6

Length in Table 344.75

Difference..... 66.85

Correction for 10ft..... 7

× Difference ÷ 10 = 4.68 + 4¾"

Allowance for strength in excess of Lloyd's rules = 2'-8½"

State particulars— as per plans approved for N1 Type Standard Vessels.

Strengthened F.O.P. sides
Deep framing
2 Steel decks
6 W.T. bulkheads 6 to shelter
2 to upper

Height of 'Tween Decks..... 7'-11½" from stem to 20 frame
(From top of beam to top of beam at side) 9'-4¾" " 20 frame to stem

Correction for Height of 'Tween Decks in Spar-decked Ships.....

Sheer flat from 46 to 108 frame and thence in fair curve to Stem and Stern.

Sheer at Stem ..... 7'-11" at ⅛ length from Stem .....

Sternpost... 6'-10" " " " Sternpost...

Drop in Sheer abaft amidships.....

Round of Spar-deck Beam..... nil

" " Main-deck " ..... nil No Camber on Dk.

	Length	×	Height.	State if open or closed at ends.
Forecastle	40-0	×	7'-6" mean	Open
Bridge.....		×		
Poop.....		×		

Freeboard Table ~~B or~~ C	3'-10½"
Correction for Length.....	+ 4¾"
	4'-3¼"
Correction for Height of 'Tween Decks in ~~Spar-decked Ships~~.....	9'-4¾"
	13-8
Correction for Strength in excess of Lloyd's rules.....	2-8½"
	10-1½"
Correction for Iron Deck if required.....	-3½"
	10-8
Other Corrections (if any).....	
Winter Freeboard.....	10-8
Summer Freeboard	10-1
Indian Summer Freeboard.....	9-6
~~N.A. Winter Freeboard~~.....	—

Correction necessary because clearside amidships measured in accordance with the Statute is not taken at intersection of the wood or steel deck with side ..... nil

Winter Freeboard from Deck Line .....

Summer " " " .....

Indian Summer " " .....

N.A. Winter " " " .....

J. C.B. 30.1.33

SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, ~~Wood~~, SHELTER Steel, Deck :—

Tropical Fresh Water Line above Centre of Disc ...	365 m/m	Tropical Fresh Water Freeboard	3073 m/m
Fresh Water Line " " ...	188 m/m	Fresh Water "	2708 m/m
Tropical Line " "	177 m/m	Tropical "	2885 m/m
Winter Line below "	178 m/m	Winter "	2896 m/m
~~Winter North Atlantic Line~~ " "	—	~~Winter North Atlantic~~ "	3251 m/m
			—

31 JAN 1933

F.W. .022 (11633 — 3073)
= 188 m/m

1m.6.32.

RECEIVED MARKING FORM 5 SEP 1936 RECEIVED MARKING FORM 1 SEP 1933

Lloyd's Register Foundation