

15 JAN 1945

Rpt. 13.—

No. 4801 (d)

REPORT ON ELECTRICAL EQUIPMENT

[OTHER THAN FOR THE PROPULSION OF THE VESSEL]

Received at London Office

15 JAN 1945

Date of writing Report 17 - 11 - 1944 When handed in at Local Office 19 Port of BRISBANE

No. in Reg. Book Survey held at BRISBANE Date: First Survey 10 - 5 - 44 Last Survey 17 - 11 - 1944 (Number of Visits 3)

on the S. S. "RIVER FITZROY" Tons { Gross 5107.9 Net 2788.21

Built at BRISBANE By whom built EVANS DEAKIN & CO. LTD. Yard No. 12 When built 1944

Owners COMMONWEALTH OF AUSTRALIA Port belonging to BRISBANE

Electrical Installation fitted by HARBURTON FRANKI (BRISBANE) LTD. Contract No. When fitted 1944

Is vessel fitted for carrying Petroleum in bulk No Is vessel equipped with D.F. YES E.S.D. YES Gy.C. ✓ Sub.Sig. ✓

Have plans been submitted and approved YES System of Distribution TWO WIRE Voltage of supply for Lighting 220

Heating 220 Power 220 Direct or Alternating Current, Lighting DC. Power DC. If Alternating Current, state frequency ✓ Prime Movers

has the governing been tested and found efficient when the whole load is suddenly thrown on and off YES Are turbine emergency governors fitted with a

trip switch as per Rule ✓ Generators, are they compound wound No. See attached cuts, are they level compounded under working conditions ✓

if not compound wound, state distance between generators 3 FEET and from switchboard 15 FEET Where more than one generator is fitted, are they

arranged to run in parallel YES, are shunt field regulators provided YES Is the compound winding connected to the negative or positive pole

Have machines over 100 kw. been inspected by the Surveyors during manufacture and testing ✓ Have certificates of

test for machines under 100 kw. been supplied YES and the results found as per rule YES Are the lubricating arrangements and the construction

of the generators as per rule YES Position of Generators STARBOARD SIDE OF ENGINE ROOM.

is the ventilation in way of generators satisfactory YES, are they clear of inflammable material YES, if situated

near unprotected combustible material, state distance from same horizontally ✓ and vertically ✓, are the generators protected from mechanical

injury and damage from water, steam and oil YES, are the bedplates and frames earthed YES and the prime movers and generators in metallic

contact YES Switchboards, where are main switchboards placed STARBOARD SIDE OF ENGINE ROOM, NEAR AFTER BULKHEAD

ABOVE GENERATORS.

are they in accessible positions, free from inflammable gases and acid fumes YES, are they protected from mechanical injury and damage from water, steam

and oil YES, if situated near unprotected combustible material, state distance from same horizontally ✓ and vertically ✓, what insulation

material is used for the panels "MISCOLITE" (SECTY'S LETTER E. 22. 2. 43), if of synthetic material is it an Approved Type YES, if of

semi-insulating material (slate or marble) are all conducting parts insulated therefrom as per Rule ✓ Is the frame effectually earthed YES

Is the construction as per Rule YES, including accessibility of parts YES, absence of fuses on the back of the board YES, individual fuses

to pilot and earth lamps, voltmeters, etc. YES, locking of screws and nuts YES, labelling of apparatus and fuses YES, fuses on the "dead"

side of switches YES Description of Main Switchgear for each generator and arrangements of equaliser switches. :-

300 AMP. AIR CIRCUIT BREAKER, FITTED WITH TIME LAG OVERLOAD PROTECTION ON BOTH POLES. NO-VOLTAGE

AND TIME LAG CURRENT RELEASE.

and for each outgoing circuit 200 AMP. D.P. QUICK BREAK KNIFE SWITCHES AND D.P. FUSES.

Are compartments containing switchboards composed of fire-resisting material or lined as per Rule ✓ Instruments on main switchboard 3

ammeters 3 voltmeters ✓ synchronising devices. For compound machines in parallel is the ammeter connected on the pole opposite to the

equaliser connection ✓ Earth Testing, state means provided EARTH LAMPS.

Switches, Circuit Breakers and Fuses, are they as per Rule YES, are the fuses an approved type YES, are all fuses, labelled as per Rule YES, are the reversed current protection devices connected on the pole opposite to the equaliser connection ✓, have they been tested under working conditions YES. Joint Boxes, Section Boards and Distribution Boards, is the construction and position as per Rule YES. Cables, are they insulated and protected as per the appropriate Tables of the Rules YES, if otherwise than as per Rule, are they of an approved type ✓ state maximum fall of pressure between bus bars and any point under maximum load 6.5 VOLTS, are the ends of all cables having a sectional area of 0.04 square inch and above provided with soldering sockets YES. Are paper insulated and varnished cambric insulated cables sealed at the exposed ends ✓ with insulating compound ✓ or waterproof insulating tape ✓. Are all the cable runs in accessible positions, not exposed to drip or accumulation of water or oil, high temperatures or risk of mechanical damage YES, are cables laid under machines or floorplates YES, if so, are they adequately protected YES. Are cables in machinery spaces, galleys, laundries, etc., lead covered YES or run in conduit NO. State how the cables are supported and protected SECURED BY CLIPS TO PERFORATED TRAYS, WITH SHEET METAL COVERS IN POSITIONS WHERE EXPOSED TO POSSIBLE DAMAGE.

Are all lead sheaths, armouring and conduits effectually bonded and earthed YES. Refrigerated chambers, are the cables and fittings as per Rule YES. Are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands YES, where unarmoured cables pass through beams, etc., are the holes effectively bushed YES and with what material LEAD. Alternative Lighting, are the groups of lights in the engine and boiler rooms arranged as per Rule YES. Emergency ^{LIGHTING} Supply, state position ENGINE ROOM CASING and method of control RELAY.

Navigation Lamps, are they separately wired YES controlled by separate double pole switches YES and fuses YES. Are the switches and fuses in a position accessible only to the officers on watch YES, is an automatic indicator fitted YES. Secondary Batteries, are they constructed and fitted as per Rule YES, are they adequately ventilated YES. Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, weatherproof YES. Are fittings installed where readily combustible materials or inflammable or explosive dust or gases are likely to be present NO ^{EXCEPT AS HEREUNDER}, if so, how are they protected -.

SPECIAL N.T. ADMIRALTY FITTINGS IN AFTER STORE. (USED AS A MAGAZINE - WAR EMERGENCY)

and where are the controlling switches fitted IN CREWS ACCOMMODATION SPACE AFT are all fittings suitably ventilated YES. are all fittings and accessories constructed and installed as per Rule YES. Searchlight Lamps, No. of ✓, whether fixed or portable ✓, are their fittings as per Rule ✓. Heating and Cooling, is the general construction as per Rule YES. are the frames effectually earthed YES, are heaters in the accommodation of the convection type YES. Motors, are all motors constructed and installed as per Rule YES and placed in well-ventilated compartments in which inflammable gases cannot accumulate and free from damage from water, steam and oil YES, if situated near unprotected combustible material, state minimum distance from same horizontally ✓ and vertically ✓. Have motors of 100 BHP and over been inspected by the Surveyors during manufacture and testing ✓. Have certificates of test for motors under 100 BHP intended for essential services been supplied and the results found as per Rule YES. Control Gear and Resistances, are they constructed and fitted as per Rule YES. Lightning Conductors, where required are they fitted as per Rule YES. Ships carrying Oil having a Flash Point less than 150° F. Have all the special requirements of the Rules for such ships been complied with ✓, are all fuses of the cartridge type ✓ are they of an approved type ✓. If portable lamps for use in dangerous spaces are supplied, are they of a self-contained battery-fed flameproof type ✓. Spare Gear, if the vessel is for open sea service have spares been provided as per Rule YES, are they suitably stored in dry situations YES. Insulation Tests, has the insulation resistance of all circuits and apparatus been megger tested and found satisfactory YES.

PARTICULARS OF GENERATING PLANT.

DESCRIPTION OF GENERATOR	No. of	RATED AT				DRIVEN BY	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE	
		Kilowatts	Volts	Ampères	Revs. per Min.		Fuel Used	Flash Point of Fuel
MAIN	1	35 ✓	225 ✓	156 ✓	650 ✓	RECIPROCATING STEAM ENGINE	✓	✓
	1	35 ✓	225 ✓	156 ✓	650 ✓	" " "	✓	✓
	1	25 ✓	225 ✓	111 ✓	1100 ✓	4 CYL. OIL ENGINE.	LIGHT DIESELOIL.	215° F.
EMERGENCY	✓							
ROTARY TRANSFORMER	✓							

GENERATOR CABLES.

DESCRIPTION	KILOWATTS	CONDUCTORS		MAXIMUM CURRENT IN AMPERES		APPROX. LENGTH (lead plus return feet)	INSULATED WITH	HOW PROTECTED
		No. in Parallel Per Pole	Sectional Area or No. and Dia. of Strands sq. ins. or sq. mm.	In the Circuit	Rule			
MAIN GENERATOR	Nº 1. 35	1	37/083	156	184 ✓	92	RUBBER	LEAD COVERED
" " EQUALISER	Nº 2. 35	1	37/083	156	184 ✓	92	"	"
" " "	Nº 3. 25	1	37/083	111 156	184 ✓	67	"	"
EMERGENCY GENERATOR								
ROTARY TRANSFORMER: MOTOR								
" " GENERATOR								

MAIN DISTRIBUTION CABLES.

AUX. SWITCHBOARDS AND SECTION BOARDS								
CIRCUIT	G	1	19/064	80	83 ✓	200	RUBBER	LEAD COVERED
"	H	1	7/064	40	46 ✓	80	"	" "
"	J	1	19/064	80	83 ✓	54	"	" "
"	L	1	7/029	15	15 ✓	128	"	" "
(SHORE CONNECTION)	"	K	1	37/083	156	184 ✓	94	" "

LIGHTING AND HEATING, ETC., CABLES

WIRELESS	Circuit B.	1	7/036	15.25	24 ✓	462	RUBBER	LEAD COVERED
NAVIGATION LIGHTS	" A.A	1	7/036	2.5	24 ✓	474	"	"
LIGHTING AND HEATING	" A	1	7/064	15.23	46 ✓	474	"	"
"	" C	1	19/052	44.5	64 ✓	60	"	"
"	" D	1	37/083	156.79	214 *	66	"	"
"	" E	1	37/083	83.17	184 ✓	60	"	"
"	" F	1	7/044	19.55	31 ✓	80	"	"
* ADMIRALTY RATING.								

MOTOR CABLES.

ALL IMPORTANT MOTORS TO BE ENUMERATED	No.	B.H.P.						
STOKER MOTOR.	2	5	1	7/044	20.5	31 ✓	398	RUBBER
COAL CRUSHER MOTOR.	1	7.5	1	7/044	30	31 ✓	238	"
REFRIG. COMPRESSOR MOTORS	2	3	1	7/036	16.4	24	234	"
" PUMP MOTORS	2	1	1	19/052	34	64 ✓		"
LATHE MOTOR.	1	2	1	3/036	8.5	10 ✓	225	"
DRILL MOTOR.	1	.5	1	1/044	2.2	5 ✓	200	"
SANITARY PUMP MOTOR.	1	2	1	3/036	8.1	10 ✓	65	"
12 INCH FAN MOTORS.	8	1.5	1	3/036	6.7	10 ✓	560	"
AXIAL FLOW FAN MOTORS.	2	1.5	1	3/036	7	10 ✓	230	"
ASH EXTRACTOR MOTOR.	1	2	1	3/036	8.5	10 ✓	72	"
OIL PURIFIER MOTOR.	1	.33	1	1/044	1.7	5 ✓	170	"

LEAD COVERED CABLES ARE PROTECTED BY METAL GUARDS AT PLACES WHERE THEY ARE LIABLE TO SUSTAIN MECHANICAL DAMAGE)

The Electrical Equipment is installed in accordance with the approved plans and the requirements of the Rules.

All Insulated Conductors are guaranteed to have been tested at the maker's works as specified in the Rules.

The foregoing is a correct description.

For and on behalf of
WARRILLON, FRANKI (QUEENSLAND) LIMITED.
Allen J. Harbison
General Manager

Electrical Engineers.

Date 18th Nov. 1944

COMPASSES.

Minimum distance between ^{12 1/2" FAN} electric generators or motors and standard compass 25 FEET.

Minimum distance between electric ^{12 1/2" FAN} generators or motors and steering compass 20 FEET.

The nearest cables to the compasses are as follows:—

A cable carrying .09 Amperes LED INTO feet from standard compass LED INTO feet from steering compass.

A cable carrying .36 Amperes 4 feet from standard compass 3 feet from steering compass.

A cable carrying .15 Amperes 9 feet from standard compass 5 feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power YES.

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted YES.

The maximum deviation due to electric currents was found to be NIL degrees on ANY course in the case of the standard compass, and NIL degrees on ANY course in the case of the steering compass.

EVANS DEAR & CO. LIMITED.

Builder's Signature.

Date 18th Nov 1944

Is this installation a duplicate of a previous case YES. If so, state name of vessel "RIVER BURDEKIN"

General Remarks (State quality of workmanship, whether insulation tests, etc., have been made, opinions as to class, etc.)

THE ELECTRICAL INSTALLATION OF THIS VESSEL HAS BEEN CONSTRUCTED AND FITTED ON BOARD IN ACCORDANCE WITH THE RULES AND APPROVED PLANS. THE MATERIALS AND WORKMANSHIP ARE GOOD. INSULATION RESISTANCE TESTS AND THE TRIALS REQUIRED BY THE RULES HAVE BEEN SATISFACTORILY CARRIED OUT AND, IN MY OPINION, THE INSTALLATION IS NOW ELIGIBLE FOR CLASSIFICATION WITH THE SOCIETY.

Noted

23.1.45

Total Capacity of Generators 95 ✓ Kilowatts.

The amount of Fee ... £ 64 : 0 :
Travelling Expenses (if any) £ ✓ :
When applied for, 19
When received, 19

J.E. Norths. & A. McEnry
Surveyor to Lloyd's Register of Shipping.

Committee's Minute

FRI. 26 JAN 1945

Assigned

See F.E. machy. rpt.